

SCHEDULE 13

Maximum permitted weights, etc

(see regulation 87(2))

Part I

Maximum permitted laden weights of (1) trailers and (2) heavy motor cars and motor cars not fitted with road friendly suspension; in each case not forming part of an articulated vehicle

1. The maximum permitted laden weight of a two or three axle vehicle to which this Part applies of a description specified in column 2 of Table I shall, for the purposes of regulation 87, be the weight specified in column 3 of that item.

2. In the case of a vehicle to which this Part applies and which is not of a description specified in an item in column 2 of Table I, the maximum permitted laden weight shall, for the purposes of regulation 87, be the weight specified in column 4 of Table II in the item which is appropriate having regard to columns 2 and 3 of that Table.

TABLE I

Maximum permitted laden weights of certain two and three axle vehicles

(1) <i>Item</i>	(2) <i>Description of vehicle</i>	(3) <i>Maximum permitted laden weight (kg)</i>
1.	A two axle trailer in which— (a) the two axles are closely-spaced, and (b) the distance between the foremost axle of the trailer and the rearmost axle of the drawing vehicle is at least 4.2m.	18,000
2.	A three axle trailer in which— (a) the three axles are closely-spaced, and (b) the distance between the foremost axle of the trailer and the rearmost axle of the drawing vehicle is at least 4.2m.	24,000
3.	A two axle motor vehicle which is a goods vehicle in which the distance between the foremost and rearmost axles is at least 3.0m.	17,000
4.	A two axle trailer in which the distance between the foremost	18,000

Status: This is the original version (as it was originally made). This item of legislation is currently only available in its original format.

(1) <i>Item</i>	(2) <i>Description of vehicle</i>	(3) <i>Maximum permitted laden weight (kg)</i>
	axle and the rearmost axle is at least 3.0m.	

TABLE II

Maximum permitted laden weights of vehicles not falling within table i

(1) <i>Item</i>	(2) <i>No. of axles</i>	(3) <i>Distance between foremost and rearmost axles (metres)</i>	(4) <i>Maximum permitted laden weight (kg)</i>
1.	2	Less than 2.65	14,230
2.	2	At least 2.65	16,260
3.	3 or more	Less than 3.0	16,260
4.	3 or more	At least 3.0 but less than 3.2	18,290
5.	3 or more	At least 3.2 but less than 3.9	20,330
6.	3 or more	At least 3.9 but less than 4.9	22,360
7.	3	At least 4.9	25,000
8.	4 or more	At least 4.9 but less than 5.6	25,000
9.	4 or more	At least 5.6 but less than 5.9	26,420
10.	4 or more	At least 5.9 but less than 6.3	28,450
11.	4 or more	At least 6.3	30,000