

**Status:** This is the original version (as it was originally made). This item of legislation is currently only available in its original format.

SCHEDULE 13

**Maximum permitted weights, etc**

**Part I**

Maximum permitted laden weights of (1) trailers and (2) heavy motor cars and motor cars not fitted with road friendly suspension; in each case not forming part of an articulated vehicle

2. In the case of a vehicle to which this Part applies and which is not of a description specified in an item in column 2 of Table I, the maximum permitted laden weight shall, for the purposes of regulation 87, be the weight specified in column 4 of Table II in the item which is appropriate having regard to columns 2 and 3 of that Table.

**TABLE I**

Maximum permitted laden weights of certain two and three axle vehicles

| (1)<br><i>Item</i> | (2)<br><i>Description of vehicle</i>  | (3)<br><i>Maximum permitted laden weight (kg)</i> |
|--------------------|---|---|
| 1.                 | A two axle trailer in which—<br>(a) the two axles are closely-spaced, and<br>(b) the distance between the foremost axle of the trailer and the rearmost axle of the drawing vehicle is at least 4.2m.     | 18,000  |
| 2.                 | A three axle trailer in which—<br>(a) the three axles are closely-spaced, and<br>(b) the distance between the foremost axle of the trailer and the rearmost axle of the drawing vehicle is at least 4.2m. | 24,000  |
| 3.                 | A two axle motor vehicle which is a goods vehicle in which the distance between the foremost and rearmost axles is at least 3.0m.   | 17,000  |
| 4.                 | A two axle trailer in which the distance between the foremost axle and the rearmost axle is at least 3.0m.  | 18,000  |

**Status:** This is the original version (as it was originally made). This item of legislation is currently only available in its original format.

**TABLE II**

Maximum permitted laden weights of vehicles not falling within table i

| (1)<br><i>Item</i> | (2)<br><i>No. of axles</i> | (3)<br><i>Distance between<br/>foremost and<br/>rearmost axles<br/>(metres)</i> | (4)<br><i>Maximum permitted<br/>laden weight (kg)</i> |
|--------------------|----------------------------|---|---|
| 1.                 | 2                          | Less than 2.65  | 14,230  |
| 2.                 | 2                          | At least 2.65   | 16,260  |
| 3.                 | 3 or more                  | Less than 3.0   | 16,260  |
| 4.                 | 3 or more                  | At least 3.0 but less than 3.2  | 18,290  |
| 5.                 | 3 or more                  | At least 3.2 but less than 3.9  | 20,330  |
| 6.                 | 3 or more                  | At least 3.9 but less than 4.9  | 22,360  |
| 7.                 | 3                          | At least 4.9  | 25,000  |
| 8.                 | 4 or more                  | At least 4.9 but less than 5.6  | 25,000  |
| 9.                 | 4 or more                  | At least 5.6 but less than 5.9  | 26,420  |
| 10.                | 4 or more                  | At least 5.9 but less than 6.3  | 28,450  |
| 11.                | 4 or more                  | At least 6.3  | 30,000  |