

## SCHEDULE 6

### RENDERING REQUIREMENTS

#### Part II

### METHODS OF RENDERING

#### METHOD 6

#### ADDED FAT CONTINUOUS ATMOSPHERIC

##### *Equipment*

1. The premises shall be equipped with apparatus to crush specified risk material to the appropriate particle size, at least one cooker to cook the specified risk material, sufficient capacity of hot water and steam production to render specified risk material in accordance with this method, and equipment to separate protein from tallow and store those products.

##### *Crushing*

2. The raw material shall be reduced in size by crushing so that the particle size does not exceed 30 millimetres. Final reduction equipment shall be checked daily and its condition recorded. Any broken equipment shall be repaired without delay to ensure that the final particle size is achieved.

##### *Cooking*

3. The material shall be passed into a steam heated vessel where a consistent level of hot liquid tallow is maintained by recycling tallow as appropriate. Passage of the raw material through the vessel shall be controlled by means of displacement and mechanical restrictions to ensure that the cooked dried material is discharged with all of its residual moisture removed as water vapour. The maximum feed rate for raw material, the maximum tallow recycle rate, and the minimum discharge temperature will be set for the vessel in the approval for the premises granted under these Regulations. The material shall be maintained at a temperature in excess of 100°C for at least 16 minutes, a temperature in excess of 110°C for at least 13 minutes, a temperature in excess of 120°C for at least 8 minutes and a temperature in excess of 130°C for at least 3 minutes. Material may be cooked so that two or more time-temperature requirements are carried out at the same time. The times and temperatures achieved during the cooking process must be recorded on a permanent recording system.

##### *Separation and storage of final products*

4. On discharge from the vessel, any surplus tallow not required to maintain the vessel's operating level shall be removed, and the material separated into its tallow and protein components. Protein and tallow shall be stored separately.

##### *Records*

5. All records shall be kept for one year.