STATUTORY INSTRUMENTS

1999 No. 3194

HEALTH AND SAFETY

The Chemicals (Hazard Information and Packaging for Supply) (Amendment) (No. 3) Regulations 1999

Made - - - - 29th November 1999
Laid before Parliament 30th November 1999
Coming into force - - 4th January 2000

The Secretary of State, being the designated Minister(1) for the purpose of section 2(2) of the European Communities Act 1972(2) in relation to the regulation and control of classification, packaging and labelling of dangerous substances and preparations, and for measures related to consumer protection, in the exercise of the powers conferred on him by the said section 2(2) hereby makes the following Regulations:—

- 1. These Regulations may be cited as the Chemicals (Hazard Information and Packaging for Supply) (Amendment) (No. 3) Regulations 1999 and shall come into force on 4th January 2000.
- **2.** The Chemicals (Hazard Information and Packaging for Supply) Regulations 1994(3) are amended by substituting for Part III of Schedule 6 the contents of the Schedule to these Regulations.

Kim Howells,
Parliamentary Under-Secretary of State for
Consumers and Corporate Affairs,
Department of Trade and Industry

29th November 1999

⁽¹⁾ S.I. 1976/897 and 1993/2661.

⁽²⁾ S.I. 1972 c. 68.

⁽³⁾ S.I. 1994/3247, amended by S.I. 1996/1092 which inserted Part III of Schedule 6. The 1994 Regulations have also been amended by S.I. 1999/197 and S.I. 1999/3165 in a manner not relevant to these Regulations.

SCHEDULE Regulation 2

NEW PART III OF SCHEDULE 6 TO THE PRINCIPAL REGULATIONS

PART III

SUBSTANCES REQUIRING ADDITIONAL LABELLING PHRASE A

Category 1 and 2 Carcinogenic, Mutagenic and Toxic for Reproduction substances requiring additional labelling phrase

The substances referred to in regulation 9(3A) are specified in the table below

Carcinogenic substance of Category 1

Substances	Index Number	EC number	CAS number	Notes
Chromium trioxide	024-001-00-0	215-607-8	1333-82-0	
Zinc chromates including zinc potassium chromate	024-007-00-3			
nickel monoxide	028-003-00-2	215-215-7	1313-99-1	
nickel dioxide	028-004-00-8	234-823-3	12035-36-8	
dinickel trioxide	028-005-00-3	215-217-8	1314-06-3	
nickel sulphide	028-006-00-9	240-841-2	16812-54-7	
nickel subsulphide	028-007-00-4	234-829-6	12035-72-2	
diarsenic trioxide; arsenic trioxide	033-003-00-0	215-481-4	1327-53-3	
arsenic pentoxide; arsenic oxide	033-004-00-6	215-116-9	1303-28-2	
arsenic acid and its salts	033-005-00-1			
lead hydrogen arsenate	082-011-00-0	232-064-2	7784-40-9	
benzene	601-020-00-8	200-753-7	71-43-2	
vinyl chloride; chloroethylene	602-023-00-7	200-831-0	75-01-4	
Bis (chloromethyl) ether	603-046-00-5	208-832-8	542-88-1	
Chloromethyl methyl ether;	603-075-00-3	203-408-1	107-30-2	

Substances	Index Number	EC number	CAS number	Notes
chlorodimethyl ether				
2-naphthylamine; beta- naphthylamine	612-022-00-3	202-080-4	91-59-8	
benzidine; 4,4'- diaminobiphenyl; biphenyl-4,4'- ylenediamine	612-042-00-2	202-199-1	92-87-5	
salts of benzidine	612-070-00-5			
salts of 2- naphthylamine	612-071-00-0			
biphenyl-4- ylamine; xenylamine; 4- aminobiphenyl	612-072-00-6	202-177-1	92-67-1	
salts of biphenyl-4- ylamine; salts of xenylamine; salts of 4- aminobiphenyl	612-073-00-1			
Tar, coal; coal tar (The byproduct from the destructive distillation of coal. Almost black semisolid. A complex combination of aromatic hydrocarbons, phenolic compounds, nitrogen bases and thiophene.)	648-081-00-7	232-361-7	8007-45-2	
Tar, coal, high-temp.; Coal tar (The condensation product obtained by cooling, to approximately ambient temperature, the gas evolved in the high temperature	648-082-00-2	266-024-0	65996-89-6	

Substances	Index Number	EC number	CAS number	Notes
(greater than 700°C (1292°F)) destructive distillation of coal. A black viscous liquid denser than water. Composed primarily of a complex mixture of condensed ring aromatic hydrocarbons. May contain minor amounts of phenolic compounds and aromatic nitrogen bases.)				
Tar, coal, low-temp.; Coal oil (The condensation product obtained by cooling, to approximately ambient temperature, the gas evolved in low temperature (less than 700°C (1292°F)) destructive distillation of coal. A black viscous liquid denser than water. Composed primarily of condensed ring aromatic hydrocarbons, phenolic compounds, aromatic nitrogen bases, and their alkyl derivatives.)	648-083-00-8	266-025-6	65996-90-9	
Tar brown-coal; (An oil distilled from brown-coal tar. Composed	648-145-00-4	309-885-0	101316-83-0	

Substances	Index Number	EC number	CAS number	Notes
primarily of aliphatic, naphthenic and one-to three-ring aromatic hydrocarbons, their alkyl derivatives, heteroaromatics and one-and two-ring phenols boiling in the range of approximately 150°C to 360°C (302°F to 680°F).)				
Tar, brown-coal, low temp; (A tar obtained from low temperature carbonization and low temperature gasification of brown coal. Composed primarily of aliphatic, naphthenic and cyclic aromatic hydrocarbons, heteroaromatic hydrocarbons and cyclic phenols.)	648-146-00-X	309-886-6	101316-84-1	
Coke (coal tar), high temperature pitch	648-157-00-X		140203-12-9	
Coke (coal tar), mixed coal-high temperature pitch	648-158-00-5		140203-13-0	
Coke (coal tar) low temperature, high temperature pitch	648-159-00-0		140413-61-2	
Distillates (petroleum), light paraffinic; Unrefined or mildly	649-050-00-0	265-051-5	64741-50-0	

Substances	Index Number	EC number	CAS number	Notes
refined baseoil (A complex combination of hydrocarbons produced by vacuum distillation of the residuum from atmospheric distillation of crude oil. It consists of hydrocarbons having carbon numbers predominantly in the range of C ₁₅ through C ₃₀ and produces a finished oil with a viscosity of less than 100 SUS at 100°F (19 cS at 40°C). It contains a relatively large proportion of saturated aliphatic hydrocarbons normally present in this distillation range of crude oil.)				
Distillates (petroleum), heavy paraffinic; Unrefined or mildly refined baseoil (A complex combination of hydrocarbons produced by vacuum distillation of the residuum from atmospheric distillation of crude oil. It consists of hydrocarbons having carbon	649-051-00-6	265-052-0	64741-51-1	

Substances	Index Number	EC number	CAS number	Notes
numbers predominantly in the range of C_{20} through C_{50} , and produces a finished oil with a viscosity of at least 100 SUS at 100°F (19 cSt at 40°C). It contains a relatively large proportion of saturated aliphatic hydrocarbons.)				
Distillates (petroleum), light naphthenic; Unrefined or mildly refined baseoil (A complex combination of hydrocarbons produced by vacuum distillation of the residuum from atmospheric distillation of crude oil. It consists of hydrocarbons having carbon numbers predominantly in the range of C ₁₅ through C ₃₀ , and produces a finished oil with a viscosity of at least 100 SUS at 100°F (19 cSt at 40°C). It contains relatively few normal paraffins.)	649-052-00-1	265-053-6	64741-52-2	
Distillates (petroleum), heavy naphthenic; Unrefined or mildly refined baseoil	649-053-00-7	265-054-1	64741-53-3	
		,		

Substances	Index Number	EC number	CAS number	Notes
(A complex combination of hydrocarbons produced by vacuum distillation of the residuum from atmospheric distillation of crude oil. It consists of hydrocarbons having carbon numbers predominantly in the range of C ₂₀ through C ₅₀ , and produces a finished oil with a viscosity of at least 100 SUS at 100°F (19 cSt at 40°C). It contains	Index Number	EC number	CAS number	Notes
relatively few normal paraffins.)				
Distillates (petroleum), acid-treated heavy naphthenic; Unrefined or mildly refined baseoil (A complex combination of hydrocarbons obtained as a raffinate from a sulfuric acid treating process. It consists of hydrocarbons having carbon numbers predominantly in the range of C ₂₀ through C ₅₀ , and produces a finished oil with a viscosity of at least 100 SUS at 100°F (19 cSt at	649-054-00-2	265-117-3	64742-18-3	

Substances	Index Number	EC number	CAS number	Notes
40°C). It contains relatively few normal paraffins.)				
Distillates (petroleum), acid-treated light naphthenic; Unrefined or mildly refined baseoil (A complex combination of hydrocarbons obtained as a raffinate from a sulfuric acid treating process. It consists of hydrocarbons having carbon numbers predominantly in the range of C ₁₅ through C ₃₀ , and produces a finished oil with a viscosity of at least 100 SUS at 100°F (19 cSt at 40°C). It contains relatively few normal paraffins.)	649-055-00-8	265-118-9	64742-19-4	
Distillates (petroleum), acid-treated heavy paraffinic; Unrefined or mildly refined baseoil (A complex combination of hydrocarbons obtained as a raffinate from a sulfuric acid process. It consists predominantly of saturated hydrocarbons having carbon	649-056-00-3	265-119-4	64742-20-7	

Substances	Index Number	EC number	CAS number	Notes
numbers predominantly in the range of C ₂₀ through C ₅₀ , and produces a finished oil with a viscosity of at least 100 SUS at 100°F (19 cSt at 40°C).)				
Distillates (petroleum), acid-treated light paraffinic; Unrefined or mildly refined baseoil (A complex combination of hydrocarbons obtained as a raffinate from a sulfuric acid treating process. It consists predominantly of saturated hydrocarbons having carbon numbers predominantly in the range of C ₁₅ through C ₃₀ , and produces a finished oil with a viscosity of at least 100 SUS at 100°F (19 cSt at 40°C).)	649-057-00-9	265-121-5	64742-21-8	
Distillates (petroleum), chemically neutralized heavy paraffinic; Unrefined or mildly refined baseoil (A complex combination of hydrocarbons obtained from a	649-058-00-4	265-127-8	64742-27-4	
		10		

Substances	Index Number	EC number	CAS number	Notes
treating process to remove acidic materials. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C ₂₀ through C ₅₀ , and produces a finished oil with a viscosity of at least 100 SUS at 100°F (19 cSt at 40°C). It contains a relatively large proportion of aliphatic hydrocarbons.)				
Distillates (petroleum), chemically neutralized light paraffinic; Unrefined or mildly refined baseoil (A complex combination of hydrocarbons produced by a treating process to remove acidic materials. It consists of hydrocarbons having carbon numbers predominantly in the range of C ₁₅ through C ₃₀ , and produces a finished oil with viscosity of at least 100 SUS at 100°F (19 cSt at 40°C).)	649-059-00-X	265-128-3	64742-28-5	
Distillates (petroleum),	649-060-00-5	265-135-1	64742-34-3	
(penoicum),		11		

Substances	Index Number	EC number	CAS number	Notes
chemically neutralized heavy naphthenic; Unrefined or mildly refined baseoil (A complex combination of hydrocarbons produced by a treating process to remove acidic materials. It consists of hydrocarbons having carbon numbers predominantly in the range of C ₂₀ through C ₅₀ , and produces a finished oil with a viscosity of at least 100 SUS at 100°F (19 cSt at 40°C). It contains relatively few normal paraffins.)				
Distillates (petroleum), chemically neutralized light napthenic; Unrefined or mildly refined baseoil (A complex combination of hydrocarbons produced by a treating process to remove acidic materials. It consists of hydrocarbons having carbon numbers predominantly in the range of C ₁₅ through C ₃₀ , and produces a	649-061-00-0	265-136-7	64742-35-4	

Substances	Index Number	EC number	CAS number	Notes
finished oil with				
a viscosity of at				
least 100 SUS at				
100°F (19 cSt at				
40°C). It contains				
relatively few				
normal paraffins.)				
erionite	650-012-00-0		12510-42-8	
asbestos	650-013-00-6		132207-33-1	
			132207-32-0	
			12172-73-5	
			77536-66-4	
			77536-68-6	
			77536-67-5	

Carcinogenic substances of Category 2

Substances	Index number	EC number	CAS number	Notes
beryllium	004-001-00-7	231-150-7	7440-41-7	
beryllium compounds with the exception of aluminium beryllium silicates	004-002-00-2			
sulfallate (ISO); 2-chlorallyl diethyldithiocarba	006-038-00-4 mate	202-388-9	95-06-7	
dimethylacarbamo chloride	oy 0 06-041-00-0	201-208-6	79-44-7	
diazomethane	006-068-00-8	206-382-7	334-88-3	
hydrazine	007-008-00-3	206-114-9	302-01-2	
N,N- dimethylhydrazine	007-012-00-5	200-316-0	57-14-7	
1,2- dimethylhydrazine	007-013-00-0		540-73-8	
salts of hydrazine	007-014-00-6			
hydrazobenzene; 1,2- diphenylhydrazine	007-021-00-4	204-563-5	122-66-7	
hydrazine bis(3- carboxy-4- hydroxybenzensul	007-022-00-X fonate)	405-030-1		

Substances	Index number	EC number	CAS number	Notes
hexamethylphosph triamide; hexamethylphosph		211-653-8	680-31-9	
dimethyl sulphate	016-023-00-4	201-058-1	77-78-1	
diethyl sulphate	016-027-00-6	200-589-6	64-67-5	
1,3- propanesultone	016-032-00-3	214-317-9	1120-71-4	
dimethylsulfamoy	1c016ri01&3-00-9	236-412-4	13360-57-1	
calcium chromate	024-008-00-9	237-366-8	13765-19-0	
strontium chromate	024-009-00-4	232-142-6	7789-06-2	
chromium III chromate; chromic chromate	024-010-00-X	246-356-2	24613-89-6	
potassium bromate	035-003-00-6	231-829-8	7758-01-2	
cadmium oxide	048-002-00-0	215-146-2	1306-19-0	
cadmium chloride	048-008-00-3	233-296-7	10108-64-2	
cadmium sulphate	048-009-00-9	233-331-6	10124-36-4	
butane [1] and isobutane [2] (containing >= 0.1% butadiene (203-450-8))	601-004-01-8	203-448-7[1] 200-857-2[2]	106-97-8[1] 75-28-5[2]	
1,3-butadiene; buta-1,3-diene	601-013-00-X	203-450-8	106-99-0	
benzo[a]pyrene; benzo[d,e,f]chryse	601-032-00-3	200-028-5	50-32-8	
benzo[a]anthracen	e601-033-00-9	200-280-6	56-55-3	
benzo[b]fluoranthe benzo[e]acephenai		205-911-9	205-99-2	
benzo[j]fluoranthe	en601-035-00-X	205-910-3	205-82-3	
benzo[k]fluoranthe	erte01-036-00-5	205-916-6	207-08-9	
dibenz[a,h]anthrac	ee6θ1-041-00-2	200-181-8	53-70-3	
1,2- dibromoethane; ethylene dibromide	602-010-00-6	203-444-5	106-93-4	
1,2- dichloroethane;	602-012-00-7	203-458-1	107-06-2	

Substances	Index number	EC number	CAS number	Notes
ethylene dichloride				
1,2-dibromo-3- chloropropane	602-021-00-6	202-479-3	96-12-8	
α,α,α- trichlorotoluene; benzotrichloride	602-038-00-9	202-634-5	98-07-7	
1,3-dichloro-2- propanol	602-064-00-0	202-491-9	96-23-1	
hexachlorobenzene	e 602-065-00-6	204-273-9	118-74-1	
1,4- dichlorobut-2-ene	602-073-00-X	212-121-8	764-41-0	
ethylene oxide; oxirane	603-023-00-X	200-849-9	75-21-8	
1-chloro-2,3- epoxypropane; epichlorhydrin	603-026-00-6	203-439-8	106-89-8	
propylene oxide; 1,2- epoxypropane; methyloxirane	603-055-00-4	200-879-2	75-56-9	
styrene oxide, (epoxyethyl) benzene; phenyloxirane	603-084-00-2	202-476-7	96-09-3	
4-amino-3- fluorophenol	604-028-00-X	402-230-0	399-95-1	
3-propanolide; 1,3-propiolactone	606-031-00-1	200-340-1	57-57-8	
urethane(INN); ethyl carbamate	607-149-00-6	200-123-1	51-79-6	
methyl acrylamidomethox (containing >= 0.1% acrylamide)	607-190-00-X yacetate	401-890-7	77402-03-0	
methyl acrylamidoglycolar (containing >= 0.1% acrylamide)	607-210-00-7 te	403-230-3	77402-05-2	
acrylonitrile	608-003-00-4	203-466-5	107-13-1	
2-nitropropane	609-002-00-1	201-209-1	79-46-9	
5- nitroacenaphthene	609-037-00-2	210-025-0	602-87-9	

Substances	Index number	EC number	CAS number	Notes
2- nitronaphthalene	609-038-00-8	209-474-5	581-89-5	
4-nitrobiphenyl	609-039-00-3	202-204-7	92-93-3	
nitrofen (ISO); 2,4- dichlorophenyl 4- nitrophenyl ether	609-040-00-9	217-406-0	1836-75-5	
2-nitroanisole	609-047-00-7	202-052-1	91-23-6	
methyl-ONN- azoxymethyl acetate; methyl azoxy methyl acetate	611-004-00-2	209-765-7	592-62-1	
disodium (5-[(4'- ((2,6-hydroxy-3- ((2-hydroxy-5- sulphophenyl)azo) biphenyl)-4- yl)azo[salicylato(4 (2-); CI Direct Brown 95		240-221-1	16071-86-6	
4-o-tolylazo- o-toluidine; 4- amino-2', 3- dimethylazobenze fast garnet GBC base; AAT; o- aminoazotoluene	611-006-00-3 ne;	202-591-2	97-56-3	
4- aminoazobenzene	611-008-00-4	200-453-6	60-09-3	
2-methoxyaniline; o-anisidine	612-035-00-4	200-963-1(o)	90-04-0	
3,3'- dimethooxybenzid o-dianisidine	612-036-00-X line;	204-355-4	119-90-4	
salts of 3,3'- dimethoxybenzidin salts of o- odianisidine	612-037-00-5 ne;			
3,3'- dimethylbenzidine o-tolidine	612-041-00-7	204-358-0	119-93-7	
4,4'- diaminodiphenylm	612-051-00-1 nethane;	202-974-4	101-77-9	

Substances	Index number	EC number	CAS number	Notes
4,4'- methylenedianiline		Lo number	Olao number	110163
3,3'- dichlorobenzidine 3,3'- dichlorobiphenyl- ylenediamine	•	202-109-0	91-94-1	
salts of 3,3'- dichlorobenzidine salts of 3,3'- dichlorobiphenyl- ylenediamine	•			
N- nitrosodimethylam dimethylnitrosami		200-549-8	62-75-9	
2,2'-dichloro-4,4'-methylenedianiline 4,4'-methylene bis(2-chloroaniline)		202-918-9	101-14-4	
salts of 2,2'- dichloro-4,4- methylenedianiline salts of 4,4'- methylenebis (2- chloroaniline)	612-079-00-4 e;			
salts of 3,3'- dimethylbenzidine salts of o- toluidine	612-081-00-5			
1-methyl-3- nitro-1- nitrosoguanidine	612-083-00-6	200-730-1	70-25-7	
4,4'-methylenedi- o-toluidine	612-085-00-7	212-658-8	838-88-0	
2,2'- (nitrosoimino) bisethanol	612-090-00-4	214-237-4	1116-54-7	
o-toluidine	612-091-00-X	202-429-0	95-53-4	
nitrosodipropylam	in 6 el 2-098-00-8	210-698-0	621-64-7	
4-methyl-m- phenylenediamine	612-099-00-3	202-453-1	95-80-7	
ethyleneimine; aziridine	613-001-00-1	205-793-9	151-56-4	

Substances	Index number	EC number	CAS number	Notes
2- methylaziridine; propyleneimine	613-033-00-6	200-878-7	75-55-8	
captafol (ISO); 1,2,3,6-tetrahydro-N-(1,1,2,2-tetrachloroethylthiphthalimide	613-046-00-7 o)	219-363-3	2425-06-1	
carbadox (INN); methyl 3- (quinoxalin-2- ylmethylene) carbazate 1,4- dioxide; 2- (methoxycarbonyl quinoxaline 1,4- dioxide	613-050-00-9 hydrazonomethyl)	229-879-0	6804-07-5	
acrylamide	616-003-00-0	201-173-7	79-06-1	
thioacetamide	616-026-00-6	200-541-4	62-55-5	
Distillates (coal tar), benzole fraction; Light Oil (A complex combination of hydrocarbons obtained by the distillation of coal tar. It consists of hydrocarbons having carbon numbers primarily in the range of C ₄ to C ₁₀ and distilling in the approximate range of 80°C to 160°C (175°F to 320°F).)		283-482-7	84650-02-2	
Tar oils, brown-coal; Light Oil (The distillate from lignite tar boiling in the range of approximately 80°C to 250°C (176°F to 482°F).	648-002-00-6	302-674-4	94114-40-6	J

Substances	Index number	EC number	CAS number	Notes
Composed primarily of aliphatic and aromatic hydrocarbons and monobasic phenols.)				
Benzol forerunnings (coal); Light oil redistillate, low boiling (The distillate from coke oven light oil having an approximate distillation range below 100°C (212°F). Composed primarily of C ₄ to C ₆ aliphatic hydrocarbons.)	648-003-00-1	266-023-5	65996-88-5	J
Distillates (coal tar), benzole fraction, BTX-rich; Light Oil redistillate, low boiling (A residue from the distillation of crude benzole to remove benzole fronts. Composed primarily of benzene, toluene and xylenes boiling in the range of approximately 75°C to 200°C (167°F to 392°F).)	648-004-00-7	309-984-9	101896-26-8	J
Aromatic hydrocarbons, C _{6—10} , C ₈ -rich; Light Oil redistillate, low boiling	648-005-00-2	292-697-5	90989-41-6	J

Substances	Index number	EC number	CAS number	Notes
Solvent naphtha (coal), light; Light Oil redistillate, low boiling	648-006-00-8	287-498-5	85536-17-0	J
Solvent naphtha (coal), xylene- styrene cut; Light Oil redistillate, intermediate boiling	648-007-00-3	287-502-5	85536-20-5	J
Solvent naphtha (coal), coumarone- Styrene contg.; Light Oil redistillate, intermediate boiling	648-008-00-9	287-500-4	85536-19-2	J
Naphtha (coal), distn. Residues; Light Oil redistillate, high boiling (The residue remaining from the distillation of recovered naphtha. Composed primarily of naphthalene and condensation products of indene and styrene.)	648-009-00-4	292-636-2	90641-12-6	J
Aromatic hydrocarbons, C ₈ ; Light Oil redistillate, high boiling	648-010-00-X	292-694-9	90989-38-1	J
Aromatic hydrocarbons, C_{8-10} ; Light Oil redistillate, high boiling	648-011-00-5	292-695-4	90989-39-2	J
Aromatic hydrocarbons, C ₈	648-012-00-0	295-281-1	91995-20-9	J

Substances	Index number	EC number	CAS number	Notes
_9; hydrocarbon				
resin polymn. by-				
product; Light				
Oil Redistillate, high boiling				
(A complex				
combination of				
hydrocarbons				
obtained from				
the evaporation				
of solvent under				
vacuum from				
polymerized				
hydrocarbon				
resin. It consists				
predominantly				
of aromatic				
hydrocarbons				
having carbon				
numbers				
predominantly in the range of				
C ₈ through C ₉				
and boiling in				
the range of				
appoximately				
120°C to 215°C				
(248°F to				
419°F).)				
Aromatic	648-013-00-6	295-551-9	92062-36-7	J
hydrocarbons,				
C _{9—12} , benzene				
distn.; Light Oil				
redistillate, high				
boiling				
Extract residues	648-014-00-1	295-323-9	91995-61-8	J
(coal), benzole				
fraction alk., acid				
ext.; Light Oil				
Extract Residues,				
low boiling (The				
redistillate from				
the distillate,				
freed of tar				
acids and tar bases, from				
bituminous coal				
high temperature				
tar boiling in				
the approximate				

Substances	Index number	EC number	CAS number	Notes
range of 90°C to 160°C (194°F to 320°F). It consists predominantly of benzene, toluene and xylenes.)				
Extract residues (coal tar), benzole fraction alk., acd ext.; Light Oil extract residues, low boiling (A complex combination of hydrocarbons obtained by the redistillation of the distillate of high temperature coal tar (tar acid and tar base free). It consists predominantly of unsubstituted and substituted mononuclear aromatic hydrocarbons boiling in the range of 85°C-195°C (185°F-383°F).)	648-015-00-7	309-868-8	101316-63-6	J
Extract residues (coal) benzole fraction acid; Light oil extract residues, low boiling (An acid sludge byproduct of the sulphuric acid refining of crude high temperature coal. Composed primarily of sulfuric acid and organic compounds.)	648-016-00-2	298-725-2	93821-38-6	J
Extract residues (coal), light	648-017-00-8	292-625-2	90641-02-4	J

Substances	Index number	EC number	CAS number	Notes
oil alk., distn.				
Overheads;				
Light Oil extract				
residues, low				
boiling (The first				
fraction from				
the distillation				
of aromatic				
hydrocarbons,				
coumarone,				
naphthalene				
and indene rich				
prefactionator				
bottoms or				
washed carbolic				
oil boiling				
substantially				
below 145°C				
(293°F).				
Composed				
primarily of C7				
and C ₈ aliphatic and aromatic				
hydrocarbons.)				
Extract residues	648-018-00-3	309-867-2	101316-62-5	J
(coal), light				
oil alk., acid				
ext., indene				
fraction; Light Oil				
Extract Residues,				
intermediate				
boiling				
Extract residues	648-019-00-9	292-626-8	90641-03-5	J
(coal), light				
oil alk., indene				
naphtha fraction;				
Light Oil Extract				
Residues,				
high boiling				
(The distillate				
from aromatic				
hydrocarbons,				
coumarone,				
naphthalene				
and indene rich				
prefractionator				
bottoms or				
washed carbolic				
oils, having an				
approximate				
boiling range of		23		
		/ 1		

Substances	Index number	EC number	CAS number	Notes
155°C to 180°C (311°F to 356°F). Composed primarily of indene, indan and trimethylbenzenes.)			
Solvent naphtha (coal); Light Oil extract residues, high boiling (The distillate from either high temperature coal tar, coke oven light oil, or coal tar oil alkaline extract residue having an approximate distillation range of 130°C to 210°C (266°F to 410°F) Composed primarily of indene and other polycyclic ring systems containing a single aromatic ring. May contain phenolic compounds and aromatic nitrogen bases.)	648-020-00-4	266-013-0	65996-79-4	J
Distillates (coal tar), light oils, neutral fraction; Light Oil extract residues, high boiling (A Distillate from the fractional distillation of high temperature coal tar. Composed primarily of alkyl-substituted one ring aromatic hydrocarbons boiling in	648-021-00-X	309-971-8	101794-90-5	J

Substances	Index number	EC number	CAS number	Notes
the range of approximately 135°C to 210°C (275°F to 410°F). May also include unsaturated hydrocarbons such as indene and coumarone.)				
Distillates (coal tar), light oils, acid exts.; Light oil extract residues, high boiling (This oil is a complex mixture of aromatic hydrocarbons, primarily indene, naphthalene, coumarone, phenol and o-, m-and p-cresol and boiling in the range of 140°C to 215°C (284°F to 419°F).)	648-022-00-5	292-609-5	90640-87-2	J
Distillates (coal tar), light oils; Carbolic Oil (A complex combination of hydrocarbons obtained by distillation of coal tar. It consists of aromatic and other hydrocarbons, phenolic compounds and aromatic nitrogen compounds and distills at the approximate range of 150°C to 210°C (302°F to 410°F).)	648-023-00-0	283-483-2	84650-03-3	J

Substances	Index number	EC number	CAS number	Notes
Tar oils, coal; Carbolic Oil (The distillate from high temperature coal tar having an approximate distillation range of 130°C to 250°C (266°F to 410°F). Composed primarily of naphthalene, alkylnaphthalenes, phenolic compounds, and aromatic nitrogen bases.)	648-024-00-6	266-016-7	65996-82-9	J
Tar, brown-coal; Carbolic Oil (An oil distilled from brown-coal tar. Composed primarily of aliphatic, naphthenic and one-to three-ring aromatic hydrocarbons, their alkyl derivatives, heteroaromatics and one-and two-ring phenols boiling in the range of approximately 150°C to 360°C (302°F to 680°F).)	648-025-00-1	309-885-0	101316-83-0	J
Extract residues (coal), light oil alk., acid ext.; Carbolic Oil extract residue (The oil resulting from the acid washing of alkali-washed carbolic oil to	648-026-00-7	292-624-7	90641-01-3	J

Substances	Index number	EC number	CAS number	Notes
remove the minor amounts of basic compounds (tar bases). Composed primarily of indene, indan and alkylbenzenes.)				
Extract residues (coal), tar oil alk.; Carbolic Oil extract residue (The residue obtained from coal tar oil by an alkaline wash such as aqueous sodium hydroxide after the removal of crude coal tar acids. Composed primarily of naphthalenes and aromatic nitrogen bases.)	648-027-00-2	266-021-4	65996-87-4	J
Extract oils (coal), light oil; Acid extract (The aqueous extract produced by an acidic wash of alkaliwashed carbolic oil. Composed primarily of acid salts of various aromatic nitrogen bases including pyridine, quinoline and their alkyl derivatives.)	648-028-00-8	292-622-6	90640-99-6	l
Pyridine, alkyl derivs.; Crude tar bases (The complex combination of polyalkylated pyridines derived from coal tar distillation	648-029-00-3	269-929-9	68391-11-7	J

Substances	Index number	EC number	CAS number	Notes
or as high-boiling distillates approximately above 150°C (302°F) from the reaction of ammonia with acetaldehyde, formaldehyde or paraformaldehyde	.)			
Tar bases, coal, picoline fraction; Distillate bases (Pyridine bases boiling in the range of approximately 125°C to 160°C (257°F to 320°F) obtained by distillation of neutralized acid extract of the base-containing tar fraction obtained by the distillation of bituminous coal tars. Composed chiefly of lutidines and picolines.)	648-030-00-9	295-548-2	92062-33-4	J
Tar bases, coal, lutidine fraction; Distillate Bases	648-031-00-4	293-766-2	91082-52-9	J
Extract oils (coal), tar base, collidine fraction; Distillate Bases (The extract produced by the acid extraction of bases from crude coal tar aromatic oils, neutralization, and distillation of the bases. Composed primarily of	648-032-00-X	273-077-3	68937-63-3	J

Substances	Index number	EC number	CAS number	Notes
collidines, aniline, toluidines, lutidines, xylidines.)				
Tar bases, coal, collidine fraction; Distillate bases (The distillation fraction boiling in the range of approximately 181°C to 186°C (356°F to 367°F) from the crude bases obtained from the neutralized, acid-extracted base-containing tar fractions obtained by the distillation of bituminous coal tar. It contains chiefly aniline and collidines.)	648-033-00-5	295-543-5	92062-28-7	J
Tar bases, coal, aniline fraction; Distillate bases (The distillation fraction boiling in the range of approximately 180°C to 200°C (356°F to 392°F) from the crude bases obtained by dephenolating and debasing the carbolated oil from the distillation of coal tar. It contains chiefly aniline, collidines, lutidines and toluidines.)	648-034-00-0	295-541-4	92062-27-6	J

Substances	Index number	EC number	CAS number	Notes
Tar bases, coal, toluidine fraction; Distillate bases	648-035-00-6	293-767-8	91082-53-0	J
Distillates (petroleum), alkene-alkyene manuf. pyrolysis oil, mixed with hightemp. coal tar, indene fraction; Redistillates (A complex combination of hydrocarbons obtained as a redistillate from the fractional distillation of bituminous coal high temperature tar and residual oils that are obtained by the pyrolytic production of alkenes and alkenes from petroleum products or natural gas. It consists predominantly of indene and boils in a range of approximately 160°C to 190°C (320°F to 374°F).)	648-036-00-1	295-292-1	91995-31-2	J
Distillates (coal), coal tar-residual pyrolysis oils, napthalene oils, Redistillates (The redistillate obtained from the fractional distillation of bituminous coal high temperature	648-037-00-7	295-295-8	91995-35-6	J

Substances	Index number	EC number	CAS number	Notes
tar and pyrolysis residual oils and boiling in the range of approximately 190°C to 270°C (374°F to 518°F). Composed primarily of substituted dinuclear aromatics.)				
Extract oils (coal), coal tarresidual pyrolysis oils, naphthalene oil, redistillate; Redistillates (The redistillate from the fractional distillation of dephenolated and debased methylnaphthalene oil obtained from bituminous coal high temperature tar and pyrolysis residual oils boiling in the approximate range of 220°C to 230°C (428°F to 446°F). It consists predominantly of unsubstituted and substituted dinuclear aromatic hydrocarbons.)	648-038-00-2	295-329-1	91995-66-3	J
Extract oils (coal), coal tarresidual pyrolysis oils, naphthalene oils; Redistillates (A neutral oil obtained by debasing and dephenolating the oil obtained from the distillation of	648-039-00-8	310-170-0	122070-79-5	J

Substances	Index number	EC number	CAS number	Notes
high temperature tar and pyrolysis residual oils which has a boiling range of 225°C to 255°C (437°F to 491°F). Composed primarily of substituted dinuclear aromatic hydrocarbons.)				
Extract oils (coal), coal tar-residual pyrolysis oils, naphthalene oil, distn. residues; Redistillates (Residue from the distillation of dephenolated and debased methylnaphthalene oil (from bituminous coal tar and pyrolysis residual oils) with a boiling range of 240°C to 260°C (464°F to 500°F). Composed primarily of substituted dinuclear aromatic and heterocyclic hydrocarbons.)	648-040-00-3	310-171-6	122070-80-8	J
Absorption oils, bicyclo arom. and heterocyclic hydrocarbon fraction; Wash oil redistillate (A complex combination of hydrocarbons obtained as a redistillate from the distillation	648-041-00-9	309-851-5	101316-45-4	M

Substances	Index number	EC number	CAS number	Notes
of wash oil. It consists predominantly of 2-ringed aromatic and heterocyclic hydrocarbons boiling in the range of approximately 260°C to 290°C (500°F to 554°F).)				
Distillates (coal tar), upper, fluorene- rich; Wash oil redistillate (A complex combination of hydrocarbons obtained by the crystallization of tar oil. It consists of aromatic and polycyclic hydrocarbons primarily fluorene and some acenaphthene.)	648-042-00-4	284-900-0	84989-11-7	M
Creosote oil, acenaphthene fraction, acenaphthene-free; Wash oil redistillate (The oil remaining after removal by a crystallization process of acenaphthene from acenaphthene oil from coal tar. Composed primarily of naphthalene and alkylnaphthalenes.	648-043-00-X	292-606-9	90640-85-0	M
Distillates (coal tar), heavy oils; Heavy	648-044-00-5	292-607-4	90640-86-1	

Substances	Index number	EC number	CAS number	Notes
anthracene oil (Distillate from the fractional distillation of coal tar of bituminous coal, with boiling range of 240°C to 400°C (464°F to 752°F). Composed primarily of triand polynuclear hydrocarbons and heterocyclic compounds.)				
Anthracene oil, acid ext.; Anthracene oil extract residue (A complex combination of hydrocarbons from the base-freed fraction obtained from the distillation of coal tar and boiling in the range of approximately 325°C to 365°C (617°F to 689°F). It contains predominantly anthracene and phenanthrene and their alkyl derivatives.)	648-046-00-6	295-274-3	91995-14-1	M
Distillates (coal tar); Heavy anthracene oil (The distillate from coal tar having an approximate distillation range of 100°C to 450°C (212°F to 842°F). Composed primarily of two to four membered	648-047-00-1	266-027-7	65996-92-1	M

Substances	Index number	EC number	CAS number	Notes
condensed ring aromatic hydrocarbons, phenolic compounds, and aromatic nitrogen bases.)				
Distillates (coal tar), pitch, heavy oils; Heavy anthracene oil (The distillate from the distillation of the pitch obtained from bituminous high temperature tar. Composed primarily of triand polynuclear aromatic hydrocarbons and boiling in the range of approximately 300°C to 470°C (572°F to 878°F). The product may also contain heteroatoms.)	648-048-00-7	295-312-9	91995-51-6	M
Distillates (coal tar), pitch; Heavy anthracene oil (The oil obtained from condensation of the vapors from the heat treatment of pitch. Composed primarily of two-to fourring aromatic compounds boiling in the range of 200°C to greater than 400°C (392°F to greater than 752°F).)	648-049-00-2	309-855-7	101316-49-8	M

Substances	Index number	EC number	CAS number	Notes
Distillates (coal tar), heavy oils, pyrene fraction; Heavy anthracene oil redistillate (The redistillate obtained from the fractional distillation of pitch distillate boiling in the range of approximately 350°C to 400°C (662°F to 752°F). Consists predominantly of tri-and polynuclear aromatic and heterocyclic hydrocarbons.)	648-050-00-8	295-304-5	91995-42-5	M
Distillates (coal tar), pitch, pyrene fraction; Heavy anthracene oil redistillate (The redistillate obtained from the fractional distillation of pitch distillate and boiling in the range of approximately 380°C to 410°C (716°F to 770°F). Composed primarily of triand polynuclear aromatic hydrocarbons and heterocyclic compounds.)	648-051-00-3	295-313-4	91995-52-7	M
Paraffin waxes (coal), brown-coal high-temp. tar, carbon-treated; Coal tar extract	648-052-00-9	308-296-6	97926-76-6	M

Substances	Index number	EC number	CAS number	Notes
(A complex combination of hydrocarbons obtained by the treatment of lignite carbonization tar with activated carbon for removal of trace constituents and impurities. It consists predominantly of saturated straight and branched chain hydrocarbons having carbon numbers predominantly greater than C ₁ 2.)				
Paraffin waxes (coal), brown-coal high-temp. tar, carbon-treated; Coal tar extract (A complex combination of hydrocarbons obtained by the treatment of lignite carbonization tar with bentonite for removal of trace constituents and impurities. It consists predominantly of saturated straight and branched chain hydrocarbons having carbon numbers predominantly greater than C ₁₂ .)	648-053-00-4	308-297-1	97926-77-7	M
Pitch; Pitch	648-054-00-X	236-072-4	61789-60-4	M

Substances	Index number	EC number	CAS number	Notes
Pitch, coal tar, high temp.; Pitch (The residue from the distillation of high temperature coal tar. A black solid with an approximate softening point from 30°C to 180°C (86°F to 356°F). Composed primarily of a complex mixture of three or more membered condensed ring aromatic hydrocarbons.)	648-055-00-5	266-028-2	65996-93-2	
Pitch, coal tar, high temp.; heat-treated; Pitch (The heat treated residue from the distillation of high temperature coal tar. A black solid with an approximate softening point from 80°C to 180°C (176°F to 356°F). Composed primarily of a complex mixture of three or more membered condensed ring aromatic hydrocarbons.)	648-056-00-0	310-162-7	121575-60-8	M
Pitch, coal tar, high temp., secondary; Pitch redistillate (The residue obtained during the distillation of high boiling	648-057-00-6	302-650-3	94114-13-3	M

Substances	Index number	EC number	CAS number	Notes
fractions from bituminous coal high temperature tar and/or pitch coke oil, with a softening point of 140°C to 170°C (284°F to 392°F) according to DIN 52025. Composed primarily of triand polynuclear aromatic compounds which also contain heteroatoms.)				
Residues (coal tar), pitch distn.; Pitch redistillate (Residue from the fractional distillation of pitch distillate boiling in the range of approximately 400°C to 470°C (752°F to 846°F). Composed primarily of polynuclear aromatic hydrocarbons, and heterocyclic compounds.)	648-058-00-1	295-507-9	92061-94-4	M
Tar, coal, high-temp., distn. and storage residues; Coal tar solids residue (Coke-and ash-containing solid residues that separate on distillation and thermal treatment of bituminous coal high temperature tar in distillation installations	648-059-00-7	295-535-1	92062-20-9	M

Substances	Index number	EC number	CAS number	Notes
and storage vessels. Consists predominantly of carbon and contains a small quantity of hero compounds as well as ash components.)				
Tar, coal, storage residues; Coal tar solids residue (The deposit removed from crude coal tar storages. Composed primarily of coal tar and carbonaceous particulate matter.)	648-060-00-2	293-764-1	91082-50-7	M
Tar, coal, high-temp., residues; Coal tar solids residue (Solids formed during the coking of bituminous coal to produce crude bituminous coal high temperature tar. Composed primarily of coke and coal particles, highly aromatized compounds and mineral substances.)	648-061-00-8	309-726-5	100684-51-3	M
Tar, coal, high-temp., high-solids; Coal tar solids residue (The condensation product obtained by cooling, to approximately ambient temperature, the	648-062-00-3	273-615-7	68990-61-4	M

Substances	Index number	EC number	CAS number	Notes
gas evolved in the high temperature (greater than 700°C (1292°F)) destructive distillation of coal. Composed primarily of a complex mixture of condensed ring aromatic hydrocarbons with a high solid content of coaltype materials.)				
Waste solids, coal-tar pitch coking; Coal tar solids residue (The combination of wastes formed by the coking of bituminous coal tar pitch. It consists predominantly of carbon.)	648-063-00-9	295-549-8	92062-34-5	M
Extract residues (coal), brown; Coal tar extract (The residue from extraction of dried coal.)	648-064-00-4	294-285-0	91697-23-3	M
Paraffin waxes (coal), brown-coal-high-temp. tar; Coal tar extract (A complex combination of hydrocarbons obtained from lignite carbonization tar by solvent crystallization (solvent deoiling), by sweating or an adducting process.	648-065-00-X	295-454-1	92045-71-1	M

Substances	Index number	EC number	CAS number	Notes
It consists predominantly of straight and branched chain saturated hydrocarbons having carbon numbers predominantly greater than C ₁₂ .)				
Paraffin waxes (coal), brown-coal-high-temp. tar, hydrotreated; Coal tar extract (A complex combination of hydrocarbons obtained from lignite carbonization tar by solvent crystallization (solvent deoiling), by sweating or an adducting process treated with hydrogen in the presence of a catalyst. It consists predominantly of straight and branched chain saturated hydrocarbons having carbon numbers predominantly greater than C ₁₂ .)	648-066-00-5	295-455-7	92045-72-2	M
Paraffin waxes (coal), brown-coal-high-temp tar, silicic acid-treated; Coal tar extract (A complex combination of hydrocarbons obtained by the treatment	648-067-00-0	308-298-7	97926-78-8	M

Substances	Index number	EC number	CAS number	Notes
of lignite carbonization tar with silicic acid for removal of trace constituents and impurities. It consists predominantly of saturated straight and branched chain hydrocarbons having carbon numbers predominantly greater than C ₁₂ .)				
Tar, coal, low-temp., distn. residues; Tar oil, intermediate boiling (Residues from fractional distillation of low temperature coal tar to remove oils that boil in a range up to approximately 300°C (572°F). Composed primarily of aromatic compounds.	648-068-00-6	309-887-1	101316-85-2	M
Pitch, coal tar, low-temp., Pitch residue (A complex black solid or semi-solid obtained from the distillation of a low temperature coal tar. It has a softening point within the approximate range of 40°C to 180°C (104°F to 356°F). Composed primarily of a	648-069-00-1	292-651-4	90669-57-1	M

Substances	Index number	EC number	CAS number	Notes
complex mixture of hydrocarbons.)				
Pitch, coal tar, low-temp., oxidized; Pitch residue, oxidised (The product obtained by air-blowing, at elevated temperature, low-temperature coal tar pitch. It has a softening-point within the approximate range of 70°C to 180°C (158°F to 356°F). Composed primarily of a complex mixture of hydrocarbons.)	648-070-00-7	292-654-0	90669-59-3	M
Pitch, coal tar, low-temp., heat-treated; Pitch residue, oxidised; Pitch residue, heat-treated (A complex black solid obtained by the heat treatment of low temperature coal tar pitch. It has a softening point within the approximate range of 50°C to 140°C (122°F to 284°F). Composed primarily of a complex mixture of aromatic compounds.)	648-071-00-2	292-653-5	90669-58-2	M
Distillates (coal- petroleum), condensed-ring arom; Distillates	648-072-00-8	269-159-3	68188-48-7	M

Substances	Index number	EC number	CAS number	Notes
(The distillate from a mixture of coal and tar and aromatic petroleum streams having an approximate distillation range of 220°C to 450°C (428°F to 842°F). Composed primarily of 3-to 4-membered condensed ring aromatic hydrocarbons.)				
Aromatic hydrocarbons, C ₂₀ — ₂₈ , polycyclic, mixed coaltar pitch-polyethylene-polypropylene pyrolysis-derived; Pyrolysis products (A complex combination of hydrocarbons obtained from mixed coal tar pitch-polyethylene-polypropylene pyrolysis. Composed primarily of polycyclic aromatic hydrocarbons having carbon numbers predominantly in the range of C ₂₀ through C ₂₈ and having a softening point of 100°C to 220°C (212°F to 428°F)	648-073-00-3	309-956-6	101794-74-5	M

Substances	Index number	EC number	CAS number	Notes
according to DIN 52025.)				
Aromatic hydrocarbons, C ₂₀ —28, polycyclic, mixed coaltar pitch-polyethylene pyrolysis-derived; Pyrolysis products (A complex combination of hydrocarbons obtained from mixed coal tar pitch-polyethylene pyrolysis. Composed primarily of polycyclic aromatic hydrocarbons having carbon numbers predominantly in the range of C ₂₀ through C ₂₈ and having a softening point of 100°C to 220°C (212°F to 428°F) according to DIN 52025.)	648-074-00-9	309-957-1	101794-75-6	M
Aromatic hydrocarbons, C_{20} —28, polycyclic, mixed coal-tar pitch-polystyrene pyrolysis-derived; Pyrolysis products (A complex combination of hydrocarbons obtained from mixed coal tar pitch-polystyrene pyrolysis.	648-075-00-4	309-958-7	101794-76-7	M

Substances	Index number	EC number	CAS number	Notes
Composed primarily of polycyclic aromatic hydrocarbons having carbon numbers predominantly in the range of C ₂₀ through C ₂₈ and having a softening point of 100°C to 220°C (212°F to 428°F) according to DIN 52025.)				
Pitch, coal tarpetroleum; Pitch residues (The residue from the distillation of a mixture of coal tar and aromatic petroleum streams. A solid with a softening point from 40°C to 180°C (140°F to 356°F). Composed primarily of a complex combination of three or more membered condensed ring aromatic hydrocarbons.)	648-076-00-X	269-109-0	68187-57-5	M
Phenanthrene, distn. residues; Heavy anthracene oil redistillate (Residue from the distillation of crude phenanthrene boiling in the approximate range of 340°C to 420°C (644°F to 788°F). It consists	648-077-00-5	310-169-5	122070-78-4	M

Substances	Index number	EC number	CAS number	Notes
predominantly of phenanthrene, anthracene and carbazole.)				
Distillates (coal tar), upper, fluorene-free; Wash oil redistillate (A complex combination of hydrocarbons obtained by the crystallization of tar oil. It consists of aromatic polycyclic hydrocarbons, primarily diphenyl, dibenzofuran and acenaphthene.)	648-078-00-0	284-899-7	84989-10-6	M
Residues (coal tar), creosote oil distn.; Wash oil redistillate (The residue from the fractional distillation of wash oil boiling in the approximate range of 270°C to 330°C (518°F to 626°F). It consists predominantly of dinuclear aromatic and heterocyclic hydrocarbons.)	648-080-00-1	295-506-3	92061-93-3	M
Distillates (coal), coke-oven light oil, naphthalene cut; Naphthalene oil (The complex combination of hydrocarbons obtained from prefractionation (continuous	648-084-00-3	285-076-5	85029-51-2	J,M

Substances	Index number	EC number	CAS number	Notes
distillation of coke oven light oil. It consists predominantly of naphthalene, coumarone and indene and boils above 148°C (298°F).)				
Distillates (coal tar), naphthalene oils, naphthalene oils, naphthalene oil redistillate (A complex combination of hydrocarbons obtained by crystallization of naphthalene oil. Composed primarily of naphthalene, alkyl naphthalenes and phenolic compounds.)	648-086-00-4	284-898-1	84989-09-3	J,M
Distillates (coal tar), napthalene oil crystn. mother liquor; Naphthalene oil redistillate (A complex combination of organic compounds obtained as a filtrate from the crystallization of the naphthalene fraction from coal tar and boiling in the range of approximately 200°C to 230°C (392°F to 446F). Contains chiefly naphthalene, thionaphthene	648-087-00-X	295-310-8	91995-49-2	J,M

Substances	Index number	EC number	CAS number	Notes
and alkylnaphthalenes.	.)			
Extract residues (coal), naphthalene oil, alk.; Naphthalene oil extract residue (A complex combination of hydrocarbons obtained from the alkali washing of naphthalene oil to remove phenolic compounds (tar acids). It is composed of naphthalene and alkyl naphthalenes.)	648-088-00-5	310-166-9	121620-47-1	J,M
Extract residues (coal), naphthalene oil, alk., naphthalene- low; Naphthalene oil extract residue (A complex combination of hydrocarbons remaining after the removal of naphthalene from alkali-washed naphthalene oil by a crystallization process. It is composed primarily of naphthalene and alkyl naphthalenes.)	648-089-00-0	310-167-4	121620-48-2	J,M
Distillates (coal tar), naphthalene oils, naphthalene free, alk. exts.; Naphthalene oil extract residue (The oil remaining	648-090-00-6	292-612-1	90640-90-7	J,M

Substances	Index number	EC number	CAS number	Notes
after the removal of phenolic compounds (tar acids) from drained naphthalene oil by an alkali wash. Composed primarily of naphthalene and alkyl naphthalenes.)				
Extract residues (coal), naphthalene oil alk., distn. overheads; Naphthalene oil extract residue (The distillation from alkali-washed naphthalene oil having an approximate distillation range of 180°C to 220°C (356°F to 428°F). Composed primarily of naphthalene, alkylbenzenes, indene and indan.)	648-091-00-1	292-627-3	90641-04-6	J,M
Distillates (coal tar), naphthalene oils, methylnaphthalene fraction; Methylnaphthalene oil (A distillate from the fractional distillation of high temperature coal tar. Composed primarily of substituted two ring aromatic		309-985-4	101896-27-9	J,M

Substances	Index number	EC number	CAS number	Notes
hydrocarbons and aromatic nitrogen bases boiling in the range of approximately 225°C to 255°C (437°F to 491°F).)				
Distillates (coal tar), naphthalene oils, indolemethylnaphthalene fraction; Methylnaphthalene oil (A distillate from the fractional distillation of high temperature coal tar. Composed primarily of indole and methylnaphthalene boiling in the range of approximately 235°C to 255°C (455°F to 491°F).)	e	309-972-3	101794-91-6	J,M
Distillates (coal tar), naphthalene oils, acid exts.; Methylnaphthalene oil extract residue (A complex combination of hydrocarbons obtained by debasing the methylnaphthalene fraction obtained by the distillation of coal tar and boiling in the range of approximately 230°C to 255°C (446°F to 491°F). Contains chiefly 1(2)-		295-309-2	91995-48-1	J,M

Substances	Index number	EC number	CAS number	Notes
methylnaphthalene naphthalene, dimethylnaphthale and biphenyl.)				
Extract residues (coal), naphthalene oil alk., distn. residues; Methylnapthalene oil extract residue (The residue from the distillation of alkali-washed naphthalene oil having an approximate distillation range of 220°C to 300°C (428°F to 572°F). Composed primarily of naphthalene, alkylnaphthalenes and aromatic nitrogen bases.)	648-095-00-3	292-628-9	90641-05-7	J,M
Extract oils (coal), acidic, tar-base free; Methylnaphthalene oil extract residue (The extract oil boiling in the range of approximately 220°C to 265°C (428°F to 509°F) from coal tar alkaline extract residue produced by an acidic wash such as aqueous sulfuric acid after distillation to remove tar bases. Composed primarily of alkylnaphthalenes.		284-901-6	84989-12-8	J,M

Substances	Index number	EC number	CAS number	Notes
Distillates (coal tar), benzole fraction, distn. residues; Wash oil (A complex combination of hydrocarbons obtained from the distillation of crude benzole (high temperature coal tar). It may be a liquid with the approximate distillation range of 150°C to 300°C (302°F to 572°F) or a semisolid or solid with a melting point up to 70°C (158°F). It is composed primarily of naphthalene and alkyl naphthalenes.)	648-097-00-4	310-165-3	121620-46-0	J,M
Creosote oil, high-boiling distillate; Wash oil (The high-boiling distillation fraction obtained from the high temperature carbonization of bituminous coal which is further refined to remove excess crystalline salts. It consists primarily of creosote oil with some of the normal polynuclear aromatic salts, which are components of coal tar distillates, removed. It is	648-100-00-9	274-565-9	70321-79-8	J,M

Substances	Index number	EC number	CAS number	Notes
crystal free at approximately 5°C (41°F).)				
Extract residues (coal), creosote oil acid; Wash oil extract residue (A complex combination of hydrocarbons from the base-freed fraction from the distillation of coal tar, boiling in the range of approximately 250°C to 280°C (482°F to 536°F). It consists predominantly of biphenyl and isomeric diphenylnaphthale	648-102-00-X	310-189-4	122384-77-4	J,M
Anthracene oil, anthracene paste; Anthracence oil fraction (The anthracene-rich solid obtained by the crystallization and centrifuging of anthracene oil. It is composed primarily of anthracene, carbazole and phenanthrene.)	648-103-00-5	292-603-2	90640-81-6	J,M
Anthracene oil, anthracene-low; Anthracene oil fraction (The oil remaining after the removal, by a crystallization process, of an anthracene-rich solid (anthracene paste) from anthracene oil.	648-104-00-0	292-604-8	90640-82-7	J,M

Substances	Index number	EC number	CAS number	Notes
It is composed primarily of two, three and four membered aromatic compounds.)				
Residues (coal tar), anthracene oil distn.; Anthracene oil fraction (The residue from the fraction distillation of crude anthracene boiling in the approximate range of 340°C to 400°C (644°F to 752°F). It consists predominantly of tri-and polynuclear aromatic and heterocyclic hydrocarbons.)	648-105-00-6	295-505-8	92061-92-2	J,M
Anthracene oil, anthracene paste, anthracene fraction; Anthracene oil fraction (A complex combination of hydrocarbons from the distillation of anthracene obtained by the crystallization of anthracene oil from bituminous high temperature tar and boiling in the range of 330°C to 350°C (626°F to 662°F). It contains chiefly anthracene,	648-106-00-1	295-275-9	91995-15-2	J,M

Substances	Inday number	EC number	CAS number	Notes
Substances carbazole and	Index number	EC number	CAS number	Notes
phenanthrene.				
Anthracene oil, anthracene paste, carbazole fraction; Anthracene oil fraction (A complex combination of hydrocarbons from the distillation of anthracene obtained by crystallization of anthracene oil from bituminous coal high temperature tar and boiling in the approximate range of 350°C to 360°C (662°F to 680°F). It contains chiefly anthracene, carbazole and phenanthrene.)	648-107-00-7	295-276-4	91995-16-3	J,M
Anthracene oil, anthracene paste, distn. lights; Anthracene oil fraction (A complex combination of hydrocarbons from the distillation of anthracene obtained by crystallization of anthracene oil from bituminous light temperature tar and boiling in the range of approximately 290°C to 340°C (554°F to 644°F). It contains	648-108-00-2	295-278-5	91995-17-4	J,M
		57		

Substances	Index number	EC number	CAS number	Notes
chiefly trinuclear aromatics and their dihydro derivatives.)				
Tar oils, coal, low-temp.; Tar oil, high boiling (A distillate from low-temperature coal tar. Composed primarily of hydrocarbons, phenolic compounds and aromatic nitrogen bases boiling in the range of approximately 160°C to 340°C (320°F to 644°F).)	648-109-00-8	309-889-2	101316-87-4	J,M
Phenols, ammonia liquor ext.; Alkaline extract (The combination of phenols extracted, using isobutyl acetate, from the ammonia liquor condensed from the gas evolved in low-temperature (less than 700°C (1292°F)) destructive distillation of coal. It consists predominantly of a mixture of monohydric and dihydric phenols.)	648-111-00-9	284-881-9	84988-93-2	J,M
Distillates (coal tar), light oils, alk. exts.; Alkaline extract (The aqueous extract from carbolic oil	648-112-00-4	292-610-0	90640-88-3	J,M

Substances	Index number	EC number	CAS number	Notes
produced by an alkaline wash such as aqueous sodium hydroxide. Composed primarily of the alkali salts of various phenolic compounds.)				
Extracts, coal tar oil alk.; Alkaline extract (The extract from coal tar oil produced by an alkaline wash such as aqueous sodium hydroxide. Composed primarily of the alkali salts of various phenolic compounds.)	648-113-00-X	266-017-2	65996-83-0	J,M
Distillates (coal tar), naphthalene oils, alk. exts.; Alkaline extract (The aqueous extract from naphthalene oil produced by an alkaline wash such as aqueous sodium hydroxide. Composed primarily of the alkali salts of various phenolic compounds.)	648-114-00-5	292-611-6	90640-89-4	J,M
Extract residues (coal), tar oil alk., carbonated, limed; Crude phenols (The product obtained by treatment of coal tar oil alkaline extract	648-115-00-0	292-629-4	90641-06-8	J,M

Substances	Index number	EC number	CAS number	Notes
with CO ₂ and CaO. Composed primarily CaCO ₃ , Ca(OH) ₂ , Na ₂ CO ₃ and other organic and inorganic impurities.)				
Tar acids, brown-coal, crude; Crude phenols (An acidified alkaline extract of brown coal tar distillate. Composed primarily of phenol and phenol homologs.)	648-117-00-1	309-888-7	101316-86-3	J,M
Tar acids, brown-coal, gasification; Crude phenols (A complex combination of organic compounds obtained from brown coal gasification. Composed primarily of C ₆ —10 hydroxy aromatic phenols and their homologs.)	648-118-00-7	295-536-7	92062-22-1	J,M
Tar acids, distn. residues; Distillate phenols (A residue from the distillation of crude phenol from coal. It consists predominantly of phenols having carbon numbers in the range of C ₈ through C ₁₀ with a softening point of 60°C to	648-119-00-2	306-251-5	96690-55-0	J,M

Substances	Index number	EC number	CAS number	Notes
80°C (140°F to 176°F).)				
Tar acids, methylphenol fraction; Distillate phenols (The fraction of tar acid rich in 3-and 4-methylphenol, recovered by distillation of low-temperature coal tar crude tar acids.)	648-120-00-8	284-892-9	84989-04-8	J,M
Tar acids, polyalkylphenol fraction; Distillate phenols (The fraction of tar acids, recovered by distillation of low-temperature coal tar crude tar acids, having an approximate boiling range of 225°C to 320°C (437°F to 608°F). Composed primarily of polyalkylphenols.)	648-121-00-3	284-893-4	84989-05-9	J,M
Tar acids, xylenol fraction; Distillate phenols (The fraction of tar acids, rich in 2,4-and 2,5-dimethylphenol, recovered by distillation of low-temperature coal tar crude tar acids.)	648-122-00-9	284-895-5	84989-06-0	J,M
Tar acids, ethylphenol fraction; Distillate phenols (The fraction of tar acids, rich in 3-and 4-	648-123-00-4	284-891-3	84989-03-7	J,M

Substances	Index number	EC number	CAS number	Notes
ethylphenol, recovered by distillation of low-temperature coal tar crude tar acids.)				
Tar acids, 3,5-xylenol fraction; Distillate phenols (The fraction of tar acids, rich in 3,5- dimethylphenol, recovered by distillation of low-temperature coal tar acids.)	648-124-00-X	284-896-0	84989-07-1	J,M
Tar acids, residues, distillates, first-cut; Distillate phenols (The residue from the distillation in the range of 235°C to 355°C (481°F to 697°F) of light carbolic oil.)	648-125-00-5	270-713-1	68477-23-6	J,M
Tar acids, cresylic, residues; Distillate phenols (The residue from crude coal tar acids after removal of phenol, cresols, xylenols and any higher boiling phenols. A black solid with a melting point approximately 80°C (176°F). Composed primarily of polyalkyphenols, resin gums, and inorganic salts.)	648-126-00-0	271-418-0	68555-24-8	J,M

Substances	Index number	EC number	CAS number	Notes
Phenols, C _{9—11} Distillate phenols	648-127-00-6	293-435-2	91079-47-9	J,M
Tar acids, cresylic; Distillate phenols (A complex combination of organic compounds obtained from brown coal and boiling in the range of approximately 200°C to 230°C (392°F to 446°F). It contains chiefly phenols and pyridine bases.)	648-128-00-1	295-540-9	92062-26-5	J,M
Tar acids, brown-coal, C ₂ -alkylphenol fraction; Distillate phenols (The distillate from the acidification of alkaline washed lignite tar distillate boiling in the range of approximately 200°C to 230°C (392°F to 446°F). Composed primarily of mand p-ethylphenol as well as cresols and xylenols.)	648-129-00-7	302-662-9	94114-29-1	J,M
Extract oils (coal), naphthalene oils; Acid extract (The aqueous extract produced by an acidic wash of alkali-washed naphthalene oil. Composed primarily of acid salts of various	648-130-00-2	292-623-1	90641-00-2	J,M
		62		

Substances	Index number	EC number	CAS number	Notes
aromatic nitrogen bases including pyridine, quinoline and their alkyl derivatives.)				
Tar bases, quinoline derivs.; Distillate bases	648-131-00-8	271-020-7	68513-87-1	J,M
Tar bases, coal, quinoline derivs. fraction; Distillate bases	648-132-00-3	274-560-1	70321-67-4	J,M
Tar bases, coal, distn. residues; Distillate bases (The distillation residue remaining after the distillation of the neutralized, acid-extracted base-containing tar fractions obtained by the distillation of coal tars. It contains chiefly aniline, collidines, quinoline and quinoline derivatives and toluidines.)	648-132-00-9	274-544-0	92062-29-8	J,M
Hydrocarbon oils, arom., mixed with polyethylene and polypropylene, pyrolyzed, light oil fraction; Heat treatment products (The oil obtained from the heat treatment of a polyethylene/polypropylene mixture with coal tar pitch or aromatic oils. It consists predominantly	648-134-00-4	309-745-9	100801-63-6	J,M

Substances	Index number	EC number	CAS number	Notes
of benzene and its homologs boiling in a range of approximately 70°C to 120°C (158°F to 248°F).)				
Hydrocarbon oils, arom., mixed with polyethylene, pyrolyzed, light oil fraction; Heat treatment products (The oil obtained from the heat treatment of polyethylene with coal tar pitch or aromatic oils. It consists predominantly of benzene and its homologs boiling in a range of 70°C to 120°C (158°F to 248°F).)	648-135-00-X	309-748-5	100801-65-8	J,M
Hydrocarbon oils, arom., mixed with polystyrene, pyrolyzed, light oil fraction; Heat treatment products (The oil obtained from the heat treatment of polystyrene with coal tar pitch or aromatic oils. It consists predominantly of benzene and its homologs boiling in a range of approximately 70°C to 210°C (158°F to 410°F).)	648-136-00-5	309-749-0	100801-66-9	J,M
Extract residues (coal), tar oil alk., naphthalene	648-137-00-0	277-567-8	736665-18-6	J,M

Substances	Index number	EC number	CAS number	Notes
distn. residues; Naphthalene oil extract residue (The residue obtained from chemical oil extracted after the removal of naphthalene by distillation composed primarily of two to four membered condensed ring aromatic hydrocarbons and aromatic nitrogen bases.)				
Creosote oil, low-boiling distillate; Wash oil (The low-boiling distillation fraction obtained from the high temperature carbonization of bituminous coal, which is further refined to remove excess crystalline salts. It consists primarily of creosote oil with some of the normal polynuclear aromatic salts, which are components of coal tar distillate, removed. It is crystal free at approximately 38°C (100°F).)		274-566-4	70321-80-1	J,M
Tar acids, cresylic, sodium salts, caustic solns.; Alkaline extract	648-139-00-1	272-361-4	68815-21-4	J,M

Substances	Index number	EC number	CAS number	Notes
Extract oils (coal), tar base; Acid extract (The extract from coal tar oil alkaline extract residue produced by an acidic wash such as aqueous sulfuric acid after distillation to remove naphthalene. Composed primarily of the acid salts of various aromatic nitrogen bases including pyridine, quinoline, and their alkyl derivatives.)	648-140-00-7	266-020-9	65996-86-3	J,M
Tar bases, coal, crude; Crude tar bases (The reaction product obtained by neutralizing coal tar base extract oil with an alkaline solution, such as aqueous sodium hydroxide, to obtain the free bases. Composed primarily of such organic bases as acridine, phenanthridine, pryridine, quinoline and their alkyl derivatives.)	648-141-00-2	266-018-8	65996-84-1	J,M
Residues (coal), liq. solvent extn.; (A cohesive powder composed of coal mineral	648-142-00-8	302-681-2	94114-46-2	M

Substances	Index number	EC number	CAS number	Notes
matter and undissolved coal remaining after extraction of coal by a liquid solvent.)				
Coal liquids, liq. solvent extn. soln.; (The product obtained by filtration of coal mineral matter and undissolved coal from coal extract solution produced by digesting coal in a liquid solvent. A black, viscous, highly complex liquid combination composed primarily of aromatic and partly hydrogenated aromatic hydrocarbons, aromatic nitrogen compounds, aromatic sulfur compounds, phenolic and other aromatic oxygen compounds and their alkyl derivatives.)	648-143-00-3	302-682-8	94114-47-3	M
Coal liquids, liq. solvent extn.; (The substantially solvent-free product obtained by the distillation of the solvent from filtered coal extract solution produced by digesting coal in a liquid solvent.	648-144-00-9	302-683-3	94114-48-4	M
		69		

Substances	Index number	EC number	CAS number	Notes
A black semi- solid, composed primarily of a complex combination of condensed- ring aromatic hydrocarbons, aromatic nitrogen compounds, aromatic sulfur compounds phenolic compounds and other aromatic oxygen compounds, and their alkyl derivatives.)				
Light oil (coal), coke-oven; Crude benzole (The volatile organic liquid extracted from the gas evolved in the high temperature (greater than 700°C (1292°F)) destructive distillation of coal. Composed primarily of benzene, toluene, and xylenes. May contain other minor hydrocarbon constituents.)	648-147-00-5	255-012-5	65996-78-3	J
Distillates (coal), liq. solvent extn., primary; (The liquid product of condensation of vapors emitted during the digestion of coal in a liquid solvent and boiling in the range of approximately	648-148-00-0	302-688-0	94114-52-0	J

Substances	Index number	EC number	CAS number	Notes
30°C to 300°C (86°F to 572°F). Composed primarily of partly hydrogenated condensed-ring aromatic hydrocarbons, aromatic compounds containing nitrogen, oxygen and sulfur, and their alkyl derivatives having carbon numbers predominantly in the range of C ₄ through C ₁₄ .)				
Distillates (coal), solvent extn., hydrocracked; (Distillate obtained by hydrocracking of coal extract or solution produced by the liquid solvent extraction or supercritical gas extraction process and boiling in the range of approximately 30°C to 300°C (86°F to 572°F). Composed primarily of aromatic, hydrogenated aromatic and naphthenic compounds, their alkyl derivatives and alkanes with carbon numbers predominantly in the range of	648-149-00-6	302-689-6	94114-53-1	J

Substances	Index number	EC number	CAS number	Notes
C ₄ through C ₁₄ . Nitrogen, sulfur and oxygen- containing aromatic and hydrogenated aromatic compounds are also present.)				
Naphtha (coal), solvent extn., hydrocracked; (Fraction of the distillate obtained by hydrocracking of coal extract or solution produced by the liquid solvent extraction or supercritical gas extraction processes and boiling in the range of approximately 30°C to 180°C (86°F to 356°F). Composed primarily of aromatic, hydrogenated aromatic and naphthenic compounds, their alkyl derivatives and alkanes with carbon numbers predominantly in the range of C ₄ to C ₉ . Nitrogen, sulfur and oxygencontaining aromatic and hydrogenated aromatic compounds are also present.) Gasoline, coal	648-151-00-7	302-690-1	94114-54-2	J
solvent extn., hydrocracked	070-131-00-/	304-071- <i> </i>	/ 1117- JJ-J	J
,		71		

Substances	Index number	EC number	CAS number	Notes
naphtha; (Motor fuel produced by the reforming of the refined naphtha fraction of the products of hydrocracking of coal extract or solution produced by the liquid solvent extraction or supercritical gas extraction processes and boiling in the range of approximately 30°C to 180°C (86°F to 356°F). Composed primarily of aromatic and naphthenic hydrocarbons, their alkyl derivatives and alkyl hydrocarbons having carbon numbers in the range of C4 through C9.)				
Distillates (coal), solvent extn., hydrocracked middle; (Distillate obtained from the hydrocracking of coal extract or solution produced by the liquid solvent extraction or supercritical gas extraction processes and boiling in the range of approximately 180°C to 300°C (356°F to 572°F). Composed primarily of two-	648-152-00-2	302-692-2	94114-56-4	J

Substances	Index number	EC number	CAS number	Notes
ring aromatic, hydrogenated aromatic and naphthenic compounds, their alkyl derivatives and alkanes having carbon numbers predominantly in the range of C ₉ through C ₁₄ . Nitrogen, sulfur and oxygencontaining compounds are also present.)				
Distillates (coal), solvent extn., hydrocracked hydrogenated middle; (Distillate from the hydrogenation of hydrocracked middle distillate from coal extract or solution produced by the liquid solvent extraction or supercritical gas extraction processes and boiling in the range of approximately 180°C to 280°C (356°F to 536°F). Composed primarily of hydrogenated two-ring carbon compounds and their alkyl derivatives having carbon numbers predominantly in the range of C9 through C14.)	648-153-00-8	302-693-8	94114-57-5	J

Substances	Index number	EC number	CAS number	Notes
Light oil (coal), semi-coking process; Fresh oil (The volatile organic liquid condensed from the gas evolved in the low temperature (less than 700°C (1292°F)) destructive distillation of coal. Composed primarily of C ₆ —10 hydrocarbons.)	648-156-00-4	292-635-7	90641-11-5	J
Extracts (petroleum), light naphthenic distillate solvent	649-001-00-3	265-102-1	64742-03-6	
Extracts (petroleum), heavy paraffinic distillate solvent	649-002-00-9	265-103-7	64742-04-7	
Extracts (petroleum), light paraffinic distillate solvent	649-003-00-4	265-104-2	6472-05-8	
Extracts (petroleum), heavy naphthenic distillate solvent	649-004-00-X	265-111-0	64742-11-6	
Extracts (petroleum), light vacuum gas oil solvent	649-005-00-5	295-341-7	91995-78-7	
Hydrocarbons C ₂₆ _ ₅₅ , aromrich	649-006-00-0	307-753-7	97722-04-8	
Residues (petroleum), atm. tower; Heavy fuel oil (A complex residuum from the atmospheric distillation of crude oil. It consists of hydrocarbons	649-008-00-1	265-045-2	64741-45-3	

Substances	Index number	EC number	CAS number	Notes
having carbon numbers predominantly greater than C ₂₀ and boiling above approximately 350°C (662°F). This stream is likely to contain 5 wt. % or more of 4-to 6-membered condensed ring aromatic hydrocarbons.)				
Gas oils (petroleum), heavy vacuum; Heavy fuel oil (A complex combination of hydrocarbons produced by the vacuum distillation of the residuum from atmospheric distillation of crude oil. It consists of hydrocarbons having carbon numbers predominantly in the range of C ₂₀ through C ₅₀ and boiling in the range of approximately 350°C to 600°C (662°F to 1112°F). This stream is likely to contain 5 wt. % more of 4-to 6-membered condensed ring aromatic hydrocarbons.)	649-010-00-2	265-058-3	64741-61-3	
(petroleum), heavy catalytic	U49-U1U-UU- <i>2</i>	∠03-U03-U	04/41-01-3	
5 5		75		

Substances	Index number	EC number	CAS number	Notes
cracked;				
Heavy fuel oil				
(A complex				
combination of				
hydrocarbons				
produced by				
the distillation				
of products				
from a catalytic				
cracking process.				
It consists of				
hydrocarbons				
having carbon				
numbers				
predominantly				
in the range of				
C_{15} through C_{35}				
and boiling in				
the range of				
approximately				
260°C to 500°C				
(500°F to 932°F).				
This stream is				
likely to contain 5 wt. % or more of				
4-to 6-membered				
condensed				
ring aromatic				
hydrocarbons.)				
-	(40.011.00.0	265.064.6	(4741 (2) 4	
Clarified oils	649-011-00-8	265-064-6	64741-62-4	
(petroleum),				
catalytic cracked;				
Heavy fuel oil				
(A complex combination of				
hydrocarbons produced as the				
residual fraction				
from distillation				
of the products				
from a catalytic				
cracking process.				
It consists of				
hydrocarbons				
having carbon				
numbers				
predominantly				
greater than C_{20}				
and boiling above				
approximately				
350°C (662°F).				
-50 5 (50 2 1).				

Substances	Index number	EC number	CAS number	Notes
This stream is likely to contain 5 wt. % or more of 4-to 6-membered condensed ring aromatic hydrocarbons.)				
Residues (petroleum), hydrocracked; Heavy fuel oil (A complex combination of hydrocarbons produced as the residual fraction from distillation of the products of a hydrocracking process. It consists of hydrocarbons having carbon numbers predominantly greater than C ₂₀ and boiling above approximately 350°C (662°F).)	649-012-00-3	265-076-1	64741-75-9	
Residues (petroleum), thermal cracked; Heavy fuel oil (A complex combination of hydrocarbons produced as the residual fraction from distillation of the product from a thermal cracking process. It consists predominantly of unsaturated hydrocarbons having carbon numbers predominantly greater than C ₂₀ and boiling above	649-013-00-9	265-081-9	64741-80-6	

Substances	Index number	EC number	CAS number	Notes
approximately 350°C (662°F). This stream is likely to contain 5 wt. % or more of 4-to 6-membered condensed ring aromatic hydrocarbons.)				
Distillates (petroleum), heavy thermal cracked; Heavy fuel oil (A complex combination of hydrocarbons from the distillation of the products from a thermal cracking process. It consists predominantly of unsaturated hydrocarbons having carbon numbers predominantly in the range of C ₁₅ through C ₃₆ and boiling in the range of approximately 260°C to 480°C (500°F to 896°F). This stream is likely to contain 5 wt.% or more of 4-to 6-membered condensed ring aromatic hydrocarbons.)	649-014-00-4	265-082-4	64741-81-7	
Gas oils (petroleum), hydrotreated vacuum; Heavy fuel oil (A complex combination of hydrocarbons	649-015-00-X	265-162-9	64742-59-2	

Substances	Index number	EC number	CAS number	Notes
obtained by				
treating a				
petroleum				
fraction with				
hydrogen in				
the presence				
of a catalyst.				
It consists of				
hydrocarbons				
having carbon				
numbers				
predominantly				
in the range of				
C_{13} through C_{50}				
and boiling in				
the range of approximately				
230°C to 600°C				
(446°F to				
1112°F). This				
stream is likely				
to contain 5 wt.				
% or more of 4-				
to 6-membered				
condensed				
ring aromatic				
hydrocarbons.)				
Residues	649-016-00-5	265-181-2	64742-78-5	
(petroleum)	047 010 00 3	203 101 2	04742 70 5	
hydrodesulfurized				
atmospheric				
tower; Heavy fuel				
oil (A complex				
combination of				
hydrocarbons				
obtained by				
treating an				
atmospheric				
tower residuum				
with hydrogen				
in the presence				
of a catalyst				
under conditions				
primarily				
to remove				
organic sulfur				
compounds.				
It consists of				
hydrocarbons				
having carbon numbers				
namoers				
		70		

Substances	Index number	EC number	CAS number	Notes
predominantly				
greater than C_{20}				
and boiling above				
approximately 350°C (662°F).				
This steam is				
likely to contain 5				
wt.% or more of				
4-to 6-membered				
condensed				
ring aromatic hydrocarbons.)				
,	640 01 7 00 0	265 100 6	64 5 40 06 5	
Gas oils (petroleum),	649-017-00-0	265-189-6	64742-86-5	
hydrodesulfurized				
heavy vacuum;				
Heavy fuel oil				
(A complex				
combination of				
hydrocarbons				
obtained from a catalytic				
hydrodesulfurization	on			
process. It	O-1-			
consists of				
hydrocarbons				
having carbon				
numbers predominantly				
in the range of				
C_{20} through C_{50}				
and boiling in				
the range of				
approximately				
350°C to 600°C				
(662°F to 1112°F). This				
stream is likely				
to contain 5 wt.				
% or more of 4-				
to 6-membered				
condensed				
ring aromatic				
hydrocarbons.)	640.040.00.6	265 105 3	6.1 7.10 .66.1	
Residues (netroloum)	649-018-00-6	265-193-8	64742-90-1	
(petroleum), steam-cracked;				
Heavy fuel oil				
(A complex				
combination of				
hydrocarbons		80		
		XU		

Substances	Index number	EC number	CAS number	Notes
obtained as				
the residual				
fraction from				
the distillation				
of the products				
of a steam				
cracking process				
(including				
steam cracking				
to produce ethylene).				
It consists				
predominantly				
of unsaturated				
hydrocarbons				
having carbon				
numbers				
predominantly				
greater than C_{14}				
and boiling above				
approximately				
260°C (500°F).				
This stream is				
likely to contain 5				
wt.% or more of				
4-to 6-membered				
condensed				
ring aromatic				
hydrocarbons.)				
Residues	649-019-00-1	269-777-3	68333-22-2	
(petroleum),				
armospheric;				
Heavy fuel oil				
(A complex				
residuum from				
atmospheric				
distillation				
of crude oil.				
It consists of				
hydrocarbons				
having carbon				
numbers				
predominantly				
greater than C ₁₁				
and boiling above				
approximately				
200°C (392°F).				
This stream is				
likely to contain 5				
wt.% or more of 4-to 6-membered				
4-10 0-membered				

Substances	Index number	EC number	CAS number	Notes
condensed ring aromatic hydrocarbons.)				
Clarified oils (petroleum), hydrodesulfurized catalytic cracked; Heavy fuel oil (A complex combination of hydrocarbons obtained by treating catalytic cracked clarified oil with hydrogen to convert organic sulfur to hydrogen sulfide which is removed. It consists of hydrocarbons having carbon numbers predominantly greater than C ₂₀ and boiling above approximately 350°C (662°F). This stream is likely to contain 5 wt. % or more of 4-to 6-membered condensed ring aromatic hydrocarbons.)	649-020-00-7	269-782-0	68333-26-6	
Distillates (petroleum), hydrodesulfurized intermediate catalytic cracked; Heavy fuel oil (A complex combination of hydrocarbons obtained by treating intermediate catalytic cracked distillates with hydrogen	649-021-00-2	269-783-6	68333-27-7	

Substances	Index number	EC number	CAS number	Notes
to convert organic sulfur to hydrogen sulfide which is removed. It consists of hydrocarbons having carbon numbers predominantly in the range of C ₁₁ through C ₃₀ and boiling in the range of approximately 205°C to 450°C (401°F to 842°F). It contains a relatively large proportion of tricyclic aromatic hydrocarbons.)				
Distillates (petroleum), hydrodesulfurized heavy cataytic cracked; Heavy fuel oil (A complex combination of hydrocarbons obtained by treatment of heavy catalytic cracked distillates with hydrogen to convert organic sulfur to hydrogen sulfide which is removed. It consists of hydrocarbons having carbon numbers predominantly in the range of C ₁₅ through C ₃₅ and boiling in the range of approximately	649-022-00-8	269-784-1	68333-28-8	

Substances	Index number	EC number	CAS number	Notes
260°C to 500°C (500°F to 932°F). This stream is likely to contain 5 wt. % or more of 4-to 6-membered condensed ring aromatic hydrocarbons.)				
Fuel oil, residues- straight-run gas oils, high-sulfur; Heavy fuel oil	649-023-00-3	270-674-0	68476-32-4	
Fuel oil, residual; Heavy fuel oil (The liquid product from various refinery streams, usually residues. The composition is complex and varies with the source of the crude oil.)	649-024-00-9	270-675-6	68476-33-5	
Residues (petroleum), catalytic reformer fractionator residue distn; Heavy fuel oil (A complex residuum from the distillation of catalytic reformer fractionator residue. It boils above approximately 399°C (750°F).)	649-025-00-4	270-792-2	68478-13-7	
Residues (petroleum), heavy coker gas oil and vacuum gas oil; Heavy fuel oil (A complex combination of hydrocarbons produced as	649-026-00-X	270-796-4	68478-17-1	

Substances	Index number	EC number	CAS number	Notes
the residual fraction from the distillation of heavy coker gas oil and vacuum gas oil. It predominantly consists of hydrocarbons having carbon numbers predominantly greater than C ₁₃ and boiling above approximately 230°C (446°F).)				Notes
Residues (petroleum), heavy coker and light vacuum; Heavy fuel oil (A complex combination of hydrocarbons produced as the residual fraction from the distillation of heavy coker gas oil and light vacuum gas oil. It consists predominantly of hydrocarbons having carbon numbers predominantly greater than C ₁₃ and boiling above approximately 230°C (446°F).)	649-027-00-5	270-983-0	68512-61-8	
Residues (petroleum), light vacuum; Heavy fuel oil (A complex residuum from the vacuum distillation of the residuum from the atmospheric	649-028-00-0	270-984-6	68512-62-9	
		85		

Substances	Index number	EC number	CAS number	Notes
distillation of crude oil. It consists of hydrocarbons having carbon numbers predominantly greater than C ₁₃ and boiling above approximately 230°C (446°F).)				
Residues (petroleum), steam-cracked light; Heavy fuel oil (A complex residuum from the distillation of the products from a steam-cracking process. It consists predominantly of aromatic and unsaturated hydrocarbons having carbon numbers greater than C ₇ and boiling in the range of approximately 101°C to 555°C (214°F to 1030°F).)	649-029-00-6	271-013-9	68513-69-9	
Fuel oil, No 6; Heavy fuel oil (A distillate oil having a minimum viscosity of 900 SUS at 37,7°C (100°F) to a maximum of 9000 SUS at 37,7°C (100°F).)	649-030-00-1	271-384-7	68553-00-4	
Residues (petroleum), topping plant, low-sulfur; Heavy	649-031-00-7	271-763-7	68607-30-7	

Substances	Index number	EC number	CAS number	Notes
fuel oil (A low-sulfur complex combination of hydrocarbons produced as the residual fraction from the topping plant distillation of crude oil. It is the residuum after the straightrun gasoline cut, kerosene cut and gas oil cut have been removed.)				
Gas oils (petroleum), heavy atmospheric; Heavy fuel oil (A complex combination of hydrocarbons obtained by the distillation of crude oil. It consists of hydrocarbons having carbon numbers predominantly in the range of C ₇ through C ₃₅ and boiling in the range of approximately 121°C to 510°C (250°F to 950°F).)	649-032-00-2	272-184-2	68783-08-4	
Residues (petroleum), coker scrubber, Condensed-ring- aromcontg.; Heavy fuel oil (A very complex combination of hydrocarbons produced as the residual fraction from the	649-033-00-8	272-187-9	68783-13-1	
		87		

Substances	Index number	EC number	CAS number	Notes
distillation of				
vacuum residuum and the products				
from a thermal				
cracking process.				
It consists				
predominantly				
of hydrocarbons				
having carbon				
numbers				
predominantly greater than				
C ₂ sub0; and				
boiling above				
approximately				
350°C (662°F).				
This stream is				
likely to contain 5				
wt. % or more of				
4-to 6-membered condensed				
ring aromatic				
hydrocarbons.)				
Distillates	649-034-00-3	273-263-4	68955-27-1	
(petroleum),	049-034-00-3	273-203-4	00933-27-1	
petroleum				
residues vacuum;				
Heavy fuel oil				
(A complex				
combination of				
hydrocarbons produced by				
the vacuum				
distillation of the				
residuum from				
the atmospheric				
distillation of				
crude oil.)				
Residues	649-035-00-9	273-272-3	68955-36-2	
(petroleum),				
steam-cracked,				
resinous; Heavy fuel oil				
(A complex				
residuum from				
the distillation of				
steam-cracked				
petroleum				
residues.)				

Substances	Index number	EC number	CAS number	Notes
Distillates (petroleum), intermediate vacuum; Heavy fuel oil (A complex combination of hydrocarbons produced by the vacuum distillation of the residuum from atmospheric distillation of crude oil. It consists of hydrocarbons having carbon numbers predominantly in the range of C ₁₄ through C ₄₂ and boiling in the range of approximately 250°C to 545°C (482°F to 1013°F). This stream is likely to contain 5 wt. % or more of 4-to 6-membered condensed ring aromatic hydrocarbons.)	649-036-00-4	274-683-0	70592-76-6	
Distillates (petroleum), light vacuum; Heavy fuel oil (A complex combination of hydrocarbons produced by the vacuum distillation of the residuum from atmospheric distillaton of crude oil. It consists of hydrocarbons	649-037-00-X	247-684-6	70592-77-7	
		89		

Substances	Index number	EC number	CAS number	Notes
having carbon numbers predominantly in the range of C ₁₁ through C ₃₅ and boiling in the range of approximately 250°C to 545°C (482°F to 1013°F).)				
Distillates (petroleum), vacuum; Heavy fuel oil (A complex combination of hydrocarbons produced by the vacuum distillation of the residuum from atmospheric distillation of crude oil. It consists of hydrocarbons having numbers predominantly in the range of C ₁₅ through C ₅₀ and boiling in the range of approximately 270°C to 600°C (518°F to 1112°F). This stream is likely to contain 5 wt. % or more of 4-to 6-membered condensed ring aromatic hydrocarbons.)	649-038-00-5	274-685-1	70592-78-8	
Gas oils (petroleum), hydrodesulfurized coker heavy vacuum; Heavy fuel oil (A complex	649-039-00-0	285-555-9	85117-03-9	
(- 1 tompion		90		

Substances	Index number	EC number	CAS number	Notes
combination of				
hydrocarbons				
obtained by				
hydrodesulfurization	on			
of heavy coker				
distillate stocks.				
It consists				
predominantly				
of hydrocarbons				
having carbon				
numbers				
predominantly in				
the range C_{18} to				
C ₄₄ and boiling				
in the range of				
approximately				
304°C to 548°C				
(579°F to				
1018°F). Likely				
to contain 5%				
or more of 4-				
to 6-members				
condensed				
ring aromatic				
hydrocarbons.)				
Residues	649-040-00-6	292-657-7	90669-75-3	
(petroleum),				
steam-cracked,				
distillates;				
Heavy fuel oil				
(A complex				
combination of				
hydrocarbons				
obtained during				
the production				
of refined				
petroleum tar by the distillation				
of steam cracked				
tar. It consists				
predominantly				
of aromatic				
and other				
hydrocarbons and				
organic sulfur				
compounds.)				
-	(40,041,00,1	202 (50.2	00660 76 4	
Residues	649-041-00-1	292-658-2	90669-76-4	
(petroleum), vacuum, light;				
Heavy fuel oil				
(A complex				
(21 complex		91		

Substances	Index number	EC number	CAS number	Notes
residuum from the vacuum distillation of the residuum from atmospheric distillation of crude oil. It consists predominantly of hydrocarbons having carbon numbers predominantly greater than C ₂₄ and boiling above approximatley 390°C (734°F).)				
Fuel oil, heavy, high-sulphur; Heavy fuel oil (A complex combination of hydrocarbons obtained by the distillation of crude petroleum. It consists predominantly of aliphatic, aromatic and cycloaliphatic hydrocarbons having carbon numbers predominantly higher than C ₂₅ and boiling above approximately 400°C (752°F).)	649-042-00-7	295-396-7	92045-14-2	
Residues (petroleum), catalytic cracking; Heavy fuel oil (A complex combination of hydrocarbons produced as the residual fraction from the distillation	649-043-00-2	295-511-0	92061-97-7	

Substances	Index number	EC number	CAS number	Notes
of the products from a catalytic cracking process. It consists predominantly of hydrocarbons having carbon numbers predominantly greater than C ₁₁ and boiling above approximately 200°C (392°F).)				
Distillates (petroleum), intermediate catalytic cracked, thermally degraded; Heavy fuel oil (A complex combination of hydrocarbons produced by the distillation of products from a catalytic cracking process which has been used as a heat transfer fluid. It consists predominantly of hydrocarbons boiling in the range of approximately 220°C to 450°C (428°F to 842°F). This stream is likely to contain organic sulfur compounds.)	649-044-00-8	295-990-6	92201-59-7	
Residual oils (petroleum); Heavy fuel oil (A complex combination of hydrocarbons, sulfur compounds and metal-containing	649-045-00-3	298-754-0	93821-66-0	
2		93		

Substances	Index number	EC number	CAS number	Notes
organic compounds obtained as the residue from refinery fractionation cracking processes. It produces a finished oil with a viscosity above 2 cSt. at 100°C.)				
Residues, steam cracked, thermally treated; Heavy fuel oil (A complex combination of hydrocarbons obtained by the treatment and distillation of raw steam-cracked naphtha. It consists predominantly of unsaturated hydrocarbons boiling in the range above approximately 180°C (356°F).)	649-046-00-9	308-733-0	98219-64-8	
Distillates (petroleum), hydrodesulphurize full-range middle; Heavy fuel oil (A complex combination of hydrocarbons obtained by treating a petroleum stock with hydrogen. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of	649-047-00-4 d	309-863-0	101316-57-8	

Substances	Index number	EC number	CAS number	Notes
C ₉ through C ₂₅ and boiling in the range of	Anuca number	LC number	CAS HUMBU	110103
approximately 150°C to 400°C (302°F to 752°F).)				
Residues (petroleum), catalytic reformer fractionator; Heavy fuel oil (A complex combination of hydrocarbons produced as the residual fraction from distillation of the product from a catalytic reforming process. It consists of predominantly aromatic hydrocarbons having carbon numbers predominantly in the range of C ₁₀ through C ₂₅ and boiling in the range of approximately 160°C to 400°C (320°F to 725°F). This stream is likely to contain 5 wt. % or more of 4-or 6-membered condensed ring aromatic hydrocarbons.)	649-048-00-X	265-069-3	64741-67-9	
Petroleum; Crude oil (A complex combination of hydrocarbons. It consists predominantly of aliphatic, alicyclic and aromatic	649-049-00-5	232-298-5	8002-05-9	
		95		

Substances	Index number	EC number	CAS number	Notes
hydrocarbons. It				
may also contain				
small amounts				
of nitrogen,				
oxygen and sulfur				
compounds.				
This category				
encompasses				
light, medium,				
and heavy				
petroleums,				
as well as the				
oils extended				
from tar sands.				
Hydrocarbonaceou	IS			
materials				
requiring major				
chemical changes				
for their recovery				
or conversion				
to petroleum				
refinery				
feedstocks such				
as crude shale				
oils; upgraded				
shale oils and				
liquid coal fuels				
are not included				
in this definition.)				
Gases	649-062-00-6	270-755-0	68477-73-6	K
(petroleum),				
catalytic				
cracked naphtha				
depropanizer				
overhead, C ₃ -				
rich acid-free;				
Petroleum gas				
(A complex				
combination of				
hydrocarbons				
obtained from				
fractionation of				
catalytic cracked				
hydrocarbons and				
treated to remove				
acidic impurities.				
It consists of				
hydrocarbons				
having carbon				
numbers in the range of				
me range of				

Substances	Index number	EC number	CAS number	Notes
C ₂ through C ₄ , predominantly C ₃ .)				
Gases (petroleum), catalytic cracker; Petroleum gas (A complex combination of hydrocarbons produced by the distillation of the products from a catalytic cracking process. It consists predominantly of aliphatic hydrocarbons having carbon numbers predominantly in the range of C ₁ through C ₆ .)	649-063-00-1	270-756-6	68477-74-7	K
Gases (petroleum), catalytic cracker, C ₁ -5-rich; Petroleum gas (A complex combination of hydrocarbons produced by the distillation of products from a catalytic cracking process. It consists of aliphatic hydrocarbons having carbon numbers in the range of C ₁ through C ₆ , predominantly C ₁ through C ₅ .)	649-064-00-7	270-757-1	68477-75-8	K
Gases (petroleum), catalytic polymd. naphtha stabilizer	649-065-00-2	270-758-7	68477-76-9	K
		97		

Substances	Index number	EC number	CAS number	Notes
overhead, C _{2—4} -rich; Petroleum gas (A complex combination of hydrocarbons obtained from the fractionation stabilization of catalytic polymerized naphtha. It consists of aliphatic hydrocarbons having carbon numbers in the range of C ₂ through C ₆ , predominantly C ₂ through C ₄ .)	649-066-00-8	270-760-8	68477-79-2	K
(petroleum), catalytic reformer, C ₁ -4-rich; Petroleum gas (A complex combination of hydrocarbons produced by distillation of products from a catalytic reforming process. It consists of hydrocarbons having carbon numbers in the range of C ₁ through C ₆ , predominantly C ₁ through C ₄ .)	049-000-00-8	2/0-/00-8	08477-19-2	K
Gases (petroleum), C _{3—5} olefinic-paraffinic alkylation feed; Petroleum gas (A complex combination of olefinic	649-067-00-3	270-765-5	68477-83-8	K

Substances	Index number	EC number	CAS number	Notes
and paraffinic hydrocarbons having carbon numbers in the range of C ₃ through C ₅ which are used as alkylation feed. Ambient temperatures normally exceed the critical temperature of these combinations.)				
Gases (petroleum), C ₄ -rich; Petroleum gas (A complex combination of hydrocarbons produced by distillation of products from a catalytic fractionation process. It consists of aliphatic hydrocarbons having carbon numbers in the range of C ₃ through C ₅ , predominantly C ₄ .)	649-068-00-9	270-767-6	68477-85-0	K
Gases (petroleum), deethanizer overheads; Petroleum gas (A complex combination of hydrocarbons produced from distillation of the gas and gasoline fractions from the catalytic cracking process.	649-069-00-4	270-768-1	68477-86-1	K

Substances	Index number	EC number	CAS number	Notes
It contains predominantly ethane and ethylene.)				
Gases (petroleum), deisobutanizer tower overheads; Petroleum gas (A complex combination of hydrocarbons produced by the atmospheric distillation of a butane-butylene stream. It consists of aliphatic hydrocarbons having carbon numbers predominantly in the range of C ₃ through C ₄ .)	649-070-00-X	270-769-7	68477-87-2	K
Gases (petroleum), depropanizer dry, propene- rich; Petroleum gas (A complex combination of hydrocarbons produced by the distillation of products from the gas and gasoline fractions of a catalytic cracking process. It consists predominantly of propylene with some ethane and propane.	649-071-00-5	270-772-3	68477-90-7	K
Gases (petroleum), depropanizer overheads; Petroleum gas (A complex	649-072-00-0	270-773-9	68477-91-8	K

Substances	Index number	EC number	CAS number	Notes
combination of hydrocarbons produced by distillation of products from the gas and gasoline fractions of a catalytic cracking process. It consists of aliphatic hydrocarbons having carbon numbers predominantly in the range of C ₂ through C ₄ .)	Index number 649-073-00-6	EC number 270-777-0	CAS number 68477-94-1	Notes
(petroleum), gas recovery plant depropanizer overheads; Petroleum gas (A complex combination of hydrocarbons obtained by fractionation of miscellaneous hydrocarbon streams. It consists predominantly of hydrocarbons having carbon numbers in the range of C ₁ through C ₄ , predominantly propane.)				
Gases (petroleum), Girbatol unit feed; Petroleum gas (A complex combination of hydrocarbons that is used as the feed into the Girbatol unit to	649-074-00-1	270-778-6	68477-95-2	K

Substances	Index number	EC number	CAS number	Notes
remove hydrogen sulfide. It consists of aliphatic hydrocarbons having carbon numbers predominantly in the range of C ₂ through C ₄ .)				
Gases (petroleum), isomerized naphtha fractionator, C ₄ -rich, hydrogen sulfide-free; Petroleum gas	649-075-00-7	270-782-8	68477-99-6	K
Tail gas (petroleum), catalytic cracked clarified oil and thermal cracked vacuum residue fractionation reflux drum; Petroleum gas (A complex combination of hydrocarbons obtained from fractionation of catalytic cracked clarified oil and thermal cracked vacuum residue. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C ₁ through C ₆ .)	649-076-00-2	270-802-5	68478-21-7	K
Tail gas (petroleum), catalytic cracked naphtha stabilization absorber; Petroleum gas	649-077-00-8	270-803-0	68478-22-8	K

Substances	Index number	EC number	CAS number	Notes
(A complex combination of hydrocarbons obtained from the stabilization of catalytic cracked naphtha. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C ₁ through C ₆ .)				
Tail gas (petroleum), catalytic cracker, catalytic reformer and hydrodesulfurizer combined fractionator; Petroleum gas (A complex combination of hydrocarbons obtained from the fractionation of products from catalytic cracking, catalytic reforming and hydrodesulfurizing processes treated to remove acidic impurities. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C ₁ through C ₅ .)	649-078-00-3	270-804-6	68478-24-0	K
Tail gas (petroleum), catalytic reformed naphtha fractionation	649-079-00-9	270-806-7	68478-26-2	K

Substances	Index number	EC number	CAS number	Notes
stabilizer; Petroleum gas (A complex combination of hydrocarbons obtained from the fractionation stabilization of catalytic reformed naphtha. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C ₁ through C ₄ .)				
Tail gas (petroleum), saturate gas plant mixed stream, C ₄ -rich; Petroleum gas (A complex combination of hydrocarbons obtained from the fractionation stabilization of straight-run naphtha, distillation tail gas and catalytic reformed naphtha stabilizer tail gas. It consists of hydrocarbons having carbon numbers in the range of C ₃ through C ₆ , predominantly butane and isobutane.)	649-080-00-4	270-813-5	68478-32-0	K
Tail gas (petroleum), saturate gas recovery plant, C_{1-2} -rich; Petroleum gas	649-081-00-X	270-814-0	68478-33-1	K

Substances	Index number	EC number	CAS number	Notes
(A complex combination of hydrocarbons obtained from fractionation of distillate tail gas, straight-run naphtha, catalytic reformed naphtha stabilizer tail gas. it consists predominantly of hydrocarbons having carbon numbers in the range of C ₁ through C ₅ , predominantly methane and ethane.)				
Tail gas (petroleum), vacuum residues thermal cracker; Petroleum gas (A complex combination of hydrocarbons obtained from the thermal cracking of vacuum residues. It consists of hydrocarbons having carbon numbers predominantly in the range of C ₁ through C ₅ .)	649-082-00-5	270-815-6	68478-34-2	K
Hydrocarbons, C_{3-4} -rich, petroleum distillate; Petroleum gas (A complex combination of hydrocarbons produced by distillation and condensation	649-083-00-0	270-990-9	68512-91-4	K

Substances	Index number	EC number	CAS number	Notes
of crude oil. It consists of hydrocarbons having carbon numbers in the range of C ₃ through C ₅ , predominantly C ₃ through C ₄ .)				
Gases (petroleum), full-range straight-run naphtha dehexanizer off; Petroleum gas (A complex combination of hydrocarbons obtained by the fractionation of the full-range straight-run naphtha. It consists of hydrocarbons having carbon numbers predominantly in the range of C ₂ through C ₆ .)	649-084-00-6	271-000-8	68513-15-5	K
Gases (petroleum), hydrocracking depropanizer off, hydrocarbon- rich; Petroleum gas (A complex combination of hydrocarbon produced by the distillation of products from a hydrocracking process. It consists predominantly of hydrocarbons having carbon numbers predominantly	649-085-00-1	271-001-3	68513-16-6	K

Substances	Index number	EC number	CAS number	Notes
in the range of C ₁ through C ₄ . It may also contain small amounts of hydrogen and hydrogen sulfide.)				
Gases (petroleum), light straight-run naphtha stabilizer off; Petroleum gas (A complex combination of hydrocarbons obtained by the stabilization of light straight-run naphtha. It consists of saturated aliphatic hydrocarbons having carbon numbers predominantly in the range of C ₂ through C ₆ .)	649-086-00-7	271-002-9	68513-17-7	K
Residues (petroleum), alkylation splitter, C ₄ -rich; Petroleum gas (A complex residuum from the distillation of streams from various refinery operations. It consists of hydrocarbons having carbon numbers in the range of C ₄ through C ₅ , predominantly butane, and boiling in the range of approximately—11, 7°C to 27.8°C (11°F to 82°F).)	649-087-00-2	271-010-2	68513-66-6	K

Substances	Index number	EC number	CAS number	Notes
Hydrocarbons, C ₁ —4, sweetened; Petroleum gas (A complex combination of hydrocarbons obtained by subjecting hydrocarbon gases to a sweetening process to convert mercaptans or to remove acidic impurities. It consists of hydrocarbons having carbon numbers predominantly in the range of C ₁ through C ₄ and boiling in the range of approximately 164°C to — 0.5°C (—263°F to 31°F.)	649-089-00-3	271-038-5	68514-36-3	K
Hydrocarbons, C _{1—3} Petroleum gas (A complex combination of hydrocarbons having carbon numbers predominantly in the range of C ₁ through C ₃ and boiling in the range of approximately — 164°C to —42°C (—263°F to —44°F).)	649-090-00-9	271-259-7	68527-16-2	K
Hydrocarbons, C ₁ 4, debutanizer fraction; Petroleum gas	649-091-00-4	271-261-8	68527-19-5	K

Substances	Index number	EC number	CAS number	Notes
Gases (petroleum), C _{1—5} , wet; Petroleum gas (A complex combination of hydrocarbons produced by the distillation of crude oil and/or the cracking of tower gas oil. It consists of hydrocarbons having carbon numbers predominantly in the range of C ₁ through C ₅ .)	649-092-00-X	271-624-0	68602-83-5	K
Hydrocarbons, C ₂ 4; Petroleum gas	649-093-00-5	271-734-9	68606-25-7	K
Hydrocarbons, C ₃ ; Petroleum gas	649-094-00-0	271-735-4	68606-26-8	K
Gases (petroleum), alkylation feed; Petroleum gas (A complex combination of hydrocarbons produced by the catalytic cracking of gas oil. It consists of hydrocarbons having carbon numbers predominantly in the range of C ₃ through C ₄ .)	649-095-00-6	271-737-5	68606-27-9	K
Gases (petroleum), depropanizer bottoms fractionation off; Petroleum gas (A complex combination of hydrocarbons obtained from	649-096-00-1	271-742-2	68606-34-8	K
		100		

Substances	Index number	EC number	CAS number	Notes
the fractionation of depropanizer bottoms. It consists predominantly of butane, isobutane and butadiene.)				
Gases (petroleum), refinery blend; Petroleum gas (A complex combination obtained from various processes. It consists of hydrogen, hydrogen sulfide and hydrocarbons having carbon numbers predominantly in the range of C ₁ through C ₅ .)	649-097-00-7	272-183-7	68783-07-3	K
Gases (petroleum), catalytic cracking; Petroleum gas (A complex combination of hydrocarbons produced by the distillation of the products from a catalytic cracking process. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C ₃ through C ₅ .)	649-098-00-2	272-203-4	68783-64-2	K
Gases (petroleum), C ₂ 4, sweetened; Petroleum gas (A complex	649-099-00-8	272-205-5	68783-65-3	K
. 1		110		

Substances	Index number	EC number	CAS number	Notes
combination of				
hydrocarbons				
obtained by				
subjecting a				
peteroleum				
distillate to a				
sweetening				
process to convert				
mercaptans				
or to remove				
acidic impurities.				
It consists				
predominantly				
of saturated				
and unsaturated				
hydrocarbone				
having carbon				
numbers				
predominantly				
in the range of				
C_2 through C_4				
and boiling in				
the range of				
approximately —				
51°C to —34°C				
(—60°F to —				
30°F).)				
Gases	649-100-00-1	272-871-7	68918-99-0	K
(petroleum),				
crude oil				
fractionation				
off; Petroleum				
gas (A complex				
combination of				
hydrocarbons				
produced by				
the fractination				
of crude oil.				
It consists of				
saturated aliphatic				
hydrocarbons				
having carbon				
numbers				
predominantly in				
the range of C_3				
through C ₅ .)				
Gases	649-101-00-7	272-872-2	68919-00-6	K
(petroleum),	U-77-101-00-/	212-012 - 2	00/1/-00-0	IX
dehexanizer				
off; Petroleum				
on, i onoioum				

Substances	Index number	EC number	CAS number	Notes
gas (A complex combination of hydrocarbons obtained by the fractionation of combined naphtha streams. It consists of saturated aliphatic hydrocarbons having carbon numbers predominantly in the range of C_1 through C_5 .)				
Gases (petroleum), light straight run gasoline fractionation stabilizer off; Petroleum gas (A complex combination of hydrocarbons obtained by the fractionation of light straight-run gasoline. It consists of saturated aliphatic hydrocarbons having carbon numbers predominantly in the range of C ₁ through C ₅ .)	649-102-00-2	272-878-5	68919-05-1	K
Gases (petroleum), naphtha unifiner desulfurization stripper off; Petroleum gas (A complex combination of hydrocarbons produced by a naphtha unifiner desulfurization process and	649-103-00-8	272-879-0	68919-06-2	K

Substances	Index number	EC number	CAS number	Notes
stripped from the naphtha product. It consists of saturated aliphatic hydrocarbons having carbon numbers predominantly in the range of C ₁ through C ₄ .)				
Gases (petroleum), straight-run naphtha catalytic reforming off; Petroleum gas (A complex combination of hydrocarbons obtained by the catalytic reforming of straight-run naphtha and fractionation of the total effluent. It consists of methane, ethane, and propane.)	649-104-00-3	272-882-7	68919-09-5	K
Gases (petroleum), fluidized catalytic cracker splitter overheads; Petroleum gas (A complex combination of hydrocarbons produced by the fractionation of the charge to the C ₃ –C ₄ splitter. It consists predominantly of C ₃ hydrocarbons.)	649-105-00-9	272-893-7	68919-20-0	K
Gases (petroleum), straight-run stabilizer off; Petroleum gas	649-106-00-4	272-883-2	68919-10-8	K

Substances	Index number	EC number	CAS number	Notes
(A complex combination of hydrocarbons obtained from the fractionation of the liquid from the first tower used in the distillation of crude oil. It consists of saturated aliphatic hydrocarbons having carbon numbers predominantly in the range of C ₁ through C ₄ .)	(40.107.00 V	272.160.2		
Gases (petroleum), catalytic cracked naphtha debutanizer; Petroleum gas (A complex combination of hydrocarbons obtained from fractionation of catalytic cracked naphtha. It consists of hydrocarbons having carbon numbers predominantly in the range of C ₁ through C ₄ .)	649-107-00-X	273-169-3	68952-76-1	K
Tail gas (petroleum), catalytic cracked distillate and naphtha stabilizer; Petroleum gas (A complex combination of hydrocarbons obtained by the fractionation	649-108-00-5	273-170-9	68952-77-2	K

Substances	Index number	EC number	CAS number	Notes
of catalytic cracked naphtha and distillate. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C_1 through C_4 .)				
Tail gas (petroleum), thermal-cracked distillate, gas oil and naphtha absorber; Petroleum gas (A complex combination of hydrocarbons obtained from the separation of thermal-cracked distillates, naphtha and gas oil. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C ₁ through C ₆ .)	649-109-00-0	273-175-6	68952-81-8	K
Tail gas (petroleum), thermal cracked hydrocarbon fractionation stabilizer, petroleum coking; Petroleum gas (A complex combination of hydrocarbons obtained from the fractionation stabilization of thermal cracked hydrocarbons	649-110-00-6	273-176-1	68952-82-9	K

Substances	Index number	EC number	CAS number	Notes
from a petroleum coking process. It consists of hydrocarbons having carbon numbers predominantly in the range of C_1 through C_6 .)				
Gases (petroleum, light steam-cracked, butadiene conc.; Petroleum gas (A complex combination of hydrocarbons produced by the distillation of products from a thermal cracking process. It consists of hydrocarbons having a carbon number predominantly of C ₄ .)	649-111-00-1	273-265-5	68955-28-2	K
Gases (petroleum), straight-run naphtha catalytic reformer stabilizer overhead; Petroleum gas (A complex combination of hydrocarbons obtained by the catalytic reforming of straight-run naphtha and the fractionation of the total effluent. It consists of saturated aliphatic hydrocarbons having carbon	649-112-00-7	273-270-2	68955-34-0	K

Substances	Index number	EC number	CAS number	Notes
numbers predominantly in the range of C ₂ through C ₄ .)				
Hydrocarbons, C ₄ ; Petroleum gas	649-113-00-2	289-339-5	87741-01-3	K
Alkanes, C ₁ _4, C ₃ -rich; Petroleum gas	649-114-00-8	292-456-4	90622-55-2	K
Gases (petroleum), steam-cracker C ₃ -rich; Petroleum gas (A complex combination of hydrocarbons produced by the distillation of products from a steam cracking process. It consists predominantly of propylene with some propane and boils in the range of approximately — 70°C to 0°C (— 94°F to 32°F).)	649-115-00-3	295-404-9	92045-22-2	K
Hydrocarbons, C ₄ , steam-cracker distillate; Petroleum gas (A complex combination of hydrocarbons produced by the distillation of the products of a steam cracking process. It consists predominantly of hydrocarbons having a carbon number of C ₄ , predominantly 1-butene and	649-116-00-9	295-405-4	92045-23-3	K

Substances	Index number	EC number	CAS number	Notes
2-butene, containing also butane and isobutene and boiling in the range of approximately — 12°C to 5°C (10.4°F to 41°F).)				
Petroleum gases, liquefied, sweetened, C ₄ , fraction; Petroleum gas (A complex combination of hydrocarbons obtained by subjecting a liquified petroleum gas mix to a sweetening process to oxidize mercaptans or to remove acidic impurities. It consists predominantly of C ₄ saturated and unsaturated hydrocarbons.)	649-117-00-4	295-463-0	92045-80-2	K
Hydrocarbons, C ₄ , 1,3-butadiene- and isobutene- free; Petroleum gas	649-118-00-X	306-004-1	95465-89-7	K
Raffinates (petroleum), steam-cracked C ₄ fraction cuprous ammonium acetate extn., C ₃₋₅ and C ₃ 5 unsatd., butadiene-free; Petroleum gas	649-199-00-5	307-769-4	97722-19-5	K
Gases (petroleum),	649-120-00-0	270-746-1	68477-65-6	K

Substances	Index number	EC number	CAS number	Notes
amine system feed; Refinery gas (The feed gas to the amine system for removal of hydrogen sulphide. It consists primarily of hydrogen. Carbon monoxide, carbon dioxide, hydrogen sulphide and aliphatic hydrocarbons having carbon numbers predominantly in the range of C ₁ through C ₅ may also be present.)				
Gases (petroleum), benzene unit hydrodesulphurizer off; Refinery gas (Off gases produced by the benzene unit. It consists primarily of hydrogen. Carbon monoxide and hydrocarbons having carbon numbers predominantly in the range of C ₁ through C ₆ , including benzene, may also be present.)	649-121-00-6	270-747-7	68477-66-7	K
Gases (petroleum), benzene unit recycle, hydrogen-rich; Refinery gas (A complex combination of hydrocarbons	649-122-00-1	270-748-2	68477-67-8	K

Substances	Index number	EC number	CAS number	Notes
obtained by recycling the gases of the benzene unit. It consists primarily of hydrogen with various small amounts of carbon monoxide and hydrocarbons having carbon numbers in the range of C_1 through C_6 .)				
Gases (petroleum), blend oil, hydrogen-nitrogen-rich; Refinery gas (A complex combination of hydrocarbons obtained by distillation of a blend oil. It consists primarily of hydrogen and nitrogen with various small amounts of carbon monoxide, carbon dioxide, and aliphatic hydrocarbons having carbon numbers predominantly in the range of C ₁ through C ₅ .)	649-123-00-7	270-749-8	68477-68-9	K
Gases (petroleum), catalytic reformed naphtha stripper overheads; Refinery gas (A complex combination of hydrocarbons obtained from	649-124-00-2	270-759-2	68477-77-0	K

Substances	Index number	EC number	CAS number	Notes
stabilization of catalytic reformed naphtha. It consists of hydrogen and saturated hydrocarbons having carbon numbers predominantly in the range of C_1 through C_4 .)				
Gases (petroleum), C _{6—8} catalytic reformer recycle; Refinery gas (A complex combination of hydrocarbons produced by distillation of products from catalytic reforming of C ₆ -C ₈ feed and recycled to conserve hydrogen. It consists primarily of hydrogen. It may also contain various small amounts of carbon monoxide, carbon dioxide, nitrogen, and hydrocarbons having carbon numbers predominantly in the range of C ₁ through C ₆ .)	649-125-00-8	270-761-3	68477-80-5	K
Gases (petroleum), C _{6—8} catalytic reformer; Refinery gas (A complex combination of hydrocarbons	649-126-00-3	270-762-9	68477-81-6	K

Substances	Index number	EC number	CAS number	Notes
produced by distillation of products from catalytic reforming of C_6 - C_8 feed. It consists of hydrocarbons having carbon numbers in the range of C_1 through C_5 and hydrogen.)				
Gases (petroleum), C _{6—8} catalytic reformer recycle, hydrogen-rich; Refinery gas	649-127-00-9	270-763-4	68477-82-7	K
Gases (petroleum), C2-return stream; Refinery gas (A complex combination of hydrocarbons obtained by the extraction of hydrogen from a gas stream which consists primarily of hydrogen with small amounts of nitrogen, carbon monoxide, methane, ethane, and ehtylene. It contains predomintly hydrocarbons such as methane, ethane, ethane, and ethylene with small amounts of hydrogen, nitrogen and carbon monoxide.)	649-128-00-4	270-766-0	68477-84-9	K
Gases (petroleum), dry	649-129-00-X	270-774-4	68477-92-9	K
(1), J		122		

Substances	Index number	EC number	CAS number	Notes
sour, gas-concn- unit-off; Refinery gas (A complex combination of dry gases from a gas concentration unit. It consists of hydrogen, hydrogen sulphide and hydrocarbons having carbon numbers predominantly in the range of C ₁ through C ₃ .)				
Gases (petroleum) gas concn. re absorber distn.; Refinery gas (A complex combination of hydrocarbons produced by distillation of products from combined gas streams in a gas concentration reabsorber. It consists predominantly of hydrogen, carbon monoxide, carbon dioxide, nitrogen, hydrogen sulphide and hydrocarbons having carbon numbers in the range of C1 through C3.)	649-130-00-5	270-776-5	68477-93-0	K
Gases (petroleum), hydrogen absorber off; Refinery gas (A complex combination	649-131-00-0	270-779-1	68477-96-3	K

Substances	Index number	EC number	CAS number	Notes
obtained by absorbing hydrogen from a hydrogen rich stream. It consists of hydrogen, carbon monoxide, nitrogen, and methane with small amounts of C ₂ hydrocarbons.)				
Gases (petroleum), hydrogen-rich; Refinery gas (A complex combination separated as a gas from hydrocarbon gases by chilling. It consists primarily of hydrogen with various small amounts of carbon monoxide, nitrogen, methane and C ₂ hydrocarbons.)	649-132-00-6	270-780-7	68477-97-4	K
Gases (petroleum), hydrotreater blend oil recycle, hydrogen- nitrogen-rich; Refinery gas (A complex combination obtained from recycled hydrotreated blend oil. It consists primarily of hydrogen and nitrogen with various small amounts of carbon monoxide, carbon dioxide and hydrocarbons having carbon	649-133-00-1	270-781-2	68477-98-5	K

Substances	Index number	EC number	CAS number	Notes
numbers predominantly in the range of C ₁ through C ₅ .)	Index number	EC number	CAS HUMBEL	110115
Gases (petroleum), recycle, hydrogen-rich; Refinery gas (A complex combination obtained from recycled reactor gases. It consists primarily of hydrogen with various small amounts of carbon monoxide, carbon dioxide, nitrogen, hydrogen sulphide, and saturated aliphatic hydrocarbons having carbon numbers in the range of C ₁ through C ₅ .)	649-134-00-7	270-783-3	68478-00-2	K
Gases (petroleum), reformer make-up, hydrogen-rich; Refinery gas (A complex combination obtained from the reformers. It consists primarily of hydrogen with various small amounts of carbon monoxide and aliphatic hydrocarbons having carbon numbers predominantly in the range of C ₁ through C ₅ .)	649-135-00-2	270-784-9	68478-01-3	K

Substances	Index number	EC number	CAS number	Notes
Gases	649-136-00-8	270-785-4	68478-02-4	K
(petroleum),	0.7 150 00 0		00170 02 1	
reforming				
hydrotreater;				
Refinery gas;				
(A complex				
combination				
obtained from				
the reforming				
hydrotreating				
process. It				
consists primarily of hydrogen,				
methane, and				
ethane with				
various small				
amounts of				
hydrogen				
sulphide and				
aliphatic				
hydrocarbons				
having carbon				
numbers				
predominantly				
in the range C_3				
through C_{5} .)				
Gases	649-137-00-3	270-787-5	68478-03-5	K
(petroleum),				
reforming				
hydrotreater,				
hydrogen-				
methane-rich;				
Refinery gas (A complex				
combination				
obtained from				
the reforming				
hydrotreating				
process. It				
consists primarily				
of hydrogen				
and methane				
with various				
small amounts of				
carbon monoxide,				
carbon dioxide,				
nitrogen and saturated aliphatic				
hydrocarbons				
having carbon				
numbers				
		126		

Substances	Index number	EC number	CAS number	Notes
predominantly in the range of C ₂ through C ₅ .)				
Gases (petroleum), reforming hydrotreater make-up, hydrogen-rich; Refinery gas (A complex combination obtained from the reforming hydrotreating process. It consists primarily of hydrogen with various small amounts of carbon monoxide and aliphatic hydrocarbons having carbon numbers predominantly in the range of C ₁ through C ₅ .)	649-138-00-9	270-788-0	68478-04-6	K
Gases (petroleum), thermal cracking distn; Refinery gas (A complex combination produced by distillation of products from a thermal cracking process. It consists of hydrogen, hydrogen sulphide, carbon monoxide, carbon dioxide and hydrocarbons having carbon numbers predominantly in	649-139-00-4	270-789-6	68478-05-7	K

Substances	Index number	EC number	CAS number	Notes
the range of C ₁ through C ₆ .)				
Tail gas (petroleum), catalytic cracker refractionation absorber; Refinery gas (A complex combination of hydrocarbons obtained from refractionation of products from a catalytic cracking process. It consists of hydrogen and hydrocarbons having carbon numbers predominantly in the range of C ₁ through C ₃ .)	649-140-00-X	270-805-1	68478-25-1	K
Tail gas (petroleum), catalytic reformed naphtha separator; Refinery gas (A complex combination of hydrocarbons obtained from the catalytic reforming of straight-run naphtha. It consists of hydrogen and hydrocarbons having carbon numbers predominantly in the range of C ₁ through C ₆ .)	649-141-00-5	270-807-2	68478-27-3	K
Tail gas (petroleum), catalytic reformed naphtha	649-142-00-0	270-808-8	68478-28-4	K
		120		

Substances	Index number	EC number	CAS number	Notes
stabilizer; Refinery gas (A complex combination of hydrocarbons obtained from the stabilization of catalytic reformed naphtha. It consists of hydrogen and hydrocarbons having carbon numbers predominantly in the range of C ₁ through C ₆ .)				
Tail gas (petroleum), cracked distillate hydrotreater separator; Refinery gas (A complex combination of hydrocarbons obtained by treating cracked distillates with hydrogen in the presence of a catalyst. It consists of hydrogen and saturated aliphatic hydrocarbons having carbon numbers predominantly in the range of C ₁ through C ₅ .)	649-143-00-6	270-809-3	68478-29-5	K
Tail gas (petroleum), hydrodesulphurized straight- run naphtha separator; Refinery gas (A complex combination of	649-144-00-1 d	270-810-9	68478-30-8	K

Substances	Index number	EC number	CAS number	Notes
hydrocarbons obtained from hydrodesulphuriza of straight-run naphtha. It consists of hydrogen and saturated aliphatic hydrocarbons having carbon numbers predominantly in the range of C_1 through C_6 .)	tion			
Gases (petroleum), catalytic reformed straight-run naphtha stabilizer overheads; Refinery gas (A complex combination of hydrocarbons obtained from the catalytic reforming of straight- run naphtha followed by fractionation of the total effluent. It consists of hydrogen, methane, ethane and propane.)	649-145-00-7	270-999-8	68513-14-4	K
Gases (petroleum), reformer effluent high-pressure flash drum off; Refinery gas (A complex combination produced by the high-pressure flashing of the effluent from the reforming reactor. It consists primarily of	649-146-00-2	271-003-4	68513-18-8	K

Cubatanasa	Indov rombo-	FC number	CAC rumban	Notas
hydrogen with various small amounts of methane, ethane, and propane.)	Index number	EC number	CAS number	Notes
Gases (petroleum), reformer effluent low-pressure flash drum off; Refinery gas (A complex combination produced by low-pressure flashing of the effluent from the reforming reactor. It consists primarily of hydrogen with various small amounts of methane, ethane, and propane.)	649-147-00-8	271-005-5	68513-19-9	K
Gases (petroleum), oil refinery gas distn. off; Refinery gas (A complex combination separated by distillation of a gas stream containing hydrogen, carbon monoxide, carbon dioxide and hydrocarbons having carbon numbers in the range of C ₁ through C ₆ or obtained by cracking ethane and propane. It consists of hydrocarbons having carbon numbers predominantly	649-148-00-3	271-258-1	68527-15-1	K
-		131		

Substances	Index number	EC number	CAS number	Notes
in the range of C ₁ through C ₂ , hydrogen, nitrogen, and carbon monoxide.)				
Gases (petroleum), benzene unit hydrotreater depentanizer overheads; Refinery gas (A complex combination produced by treating the feed from the benzene unit with hydrogen in the presence of a catalyst followed by depentanizing. It consists primarily of hydrogen, ethane and propane with various small amounts of nitrogen, carbon monoxide, carbon dioxide and hydrocarbons having carbon numbers predominantly in the range of C1 through C6. It may contain trace amounts of benzene.)	649-149-00-9	271-623-5	68602-82-4	K
Gases (petroleum), secondary absorber off, fluidized catalytic cracker overheads fractionator; Refinery gas (A complex	649-150-00-4	271-625-6	68602-84-6	K

Substances	Index number	EC number	CAS number	Notes
combination produced by the fractionation of the overhead products from the catalytic cracking process in the fluidized catalytic cracker. It consists of hydrogen, nitrogen, and hydrocarbons having carbon numbers predominantly in the range of C_1 through C_3 .)				
Petroleum products, refinery gases; Refinery gas (A complex combination which consists primarily of hydrogen with various small amounts of methane, ethane and propane.)	649-151-0-X	271-750-6	68607-11-4	K
Gases (petroleum), hydrocracking low-pressure separator; Refinery gas (A complex combination obtained by the liquid-vapor separation of the hydrocracking process reactor effluent. It consists predominantly of hydrogen and saturated hydrocarbons having carbon numbers	649-152-00-5	272-182-1	68783-06-2	K

Index number	EC number	CAS number	Notes
649-153-00-0	272-338-9	68814-67-5	K
649-154-00-6	272-343-6	68814-90-4	K
649-155-00-1	272-775-5	68911-58-0	K
	649-153-00-0 649-154-00-6	649-153-00-0 272-338-9 649-154-00-6 272-343-6	649-153-00-0 272-338-9 68814-67-5 649-154-00-6 272-343-6 68814-90-4 649-155-00-1 272-775-5 68911-58-0

Substances	Index number	EC number	CAS number	Notes
combination obtained from the depentanizer stabilization of hydrotreated kerosine. It consists primarily of hydrogen, methane, ethane, and propane with various small amounts of nitrogen, hydrogen sulphide, carbon monoxide and hydrocarbons having carbon numbers predominantly in the range of C ₄ through C ₅ .)				
Gases (petroleum), hydrotreated sour kerosine flash drum; Refinery gas (A complex combination obtained from the flash drum of the unit treating sour kerosine with hydrogen in the presence of a catalyst. It consists primarily of hydrogen and methane with various small amounts of nitrogen, carbon monoxide, and hydrocarbons having carbon numbers predominantly in the range of C ₂ through C ₅ .)	649-156-00-7	272-776-0	68911-59-1	K

Substances	Index number	EC number	CAS number	Notes
Gases (petroleum), distillate unifiner desulphurization stripper off; Refinery gas (A complex combination stripped from the liquid product of the unifiner desulphurization process. It consists of hydrogen sulphide, methane, ethane, and propane.)	649-157-00-2	272-873-8	68919-01-7	K
Gases (petroleum), fluidized catalytic cracker fractionation off; Refinery gas (A complex combination produced by the fractionation of the overhead product of the fluidized catalytic cracking process. It consists of hydrogen, hydrogen sulphide, nitrogen, and hydrocarbons having carbon numbers predominantly in the range of C ₁ through C ₅ .)	649-158-00-8	272-874-3	68919-02-8	K
Gases (petroleum), fluidized catalytic cracker scrubbing secondary absorber off; Refinery gas	649-159-00-3	272-875-9	68919-03-9	K

Substances	Index number	EC number	CAS number	Notes
(A complex combination produced by scrubbing the overhead gas from the fluidized catalytic cracker. It consists of hydrogen, nitrogen, methane, ethane and propane.)				
Gases (petroleum), heavy distillate hydrotreater desulphurization stripper off; Refinery gas (A complex combination stripped from the liquid product of the heavy distillate hydrotreater desulphurization process. It consists of hydrogen, hydrogen sulphide, and saturated aliphatic hydrocarbons having carbon numbers predominantly in the range of C ₁ through C ₅ .)	649-160-00-9	272-876-4	68919-04-0	K
Gases (petroleum), platformer stabilizer off, light ends fractionation; Refinery gas (A complex combination obtained by the fractionation of the light ends	649-161-00-4	272-880-6	68919-07-3	K

Substances	Index number	EC number	CAS number	Notes
of the platinum reactors of the platformer unit. It consists of hydrogen, methane, ethane and propane.)	Index number	EC number	CAS number	110113
Gases (petroleum), preflash tower off, crude distn.; Refinery gas (A complex combination produced from the first tower used in the distillation of crude oil. It consists of nitrogen and saturated aliphatic hydrocarbons having carbon numbers predominantly in the range of C ₁ through C ₅ .)	649-162-00-X	272-881-1	68919-08-4	K
Gases (petroleum), tar stripper off; Refinery gas (A complex combination obtained by the fractionation of reduced crude oil. It consists of hydrogen and hydrocarbons having carbon numbers predominantly in the range of C ₁ through C ₄ .)	649-163-00-5	272-884-8	68919-11-9	K
Gases (petroleum), unifiner stripper off; Refinery gas (A combination	649-164-00-0	272-885-3	68919-12-0	K
		120		

Substances	Index number	EC number	CAS number	Notes
of hydrogen and methane obtained by fractionation of the products from the unifiner unit.)				
Tail gas (petroleum), catalytic hydrodesulphurize naphtha separator; Refinery gas (A complex combination of hydrocarbons obtained from the hydrodesulphuriza of naphtha. It consists of hydrogen, methane, ethane, and propane.)		273-173-5	68952-79-4	K
Tail gas (petroleum), straight-run naphtha hydrodesulphurize Refinery gas (A complex combination obtained from the hydrodesulphuriza of straight-run naphtha. It consists of hydrogen and hydrocarbons having carbon numbers predominantly in the range of C ₁ through C ₅ .)		273-174-0	68952-80-7	K
Gases (petroleum), sponge absorber off, fluidized catalytic cracker and gas oil desulphurizer	649-167-00-7	273-269-7	68955-33-9	K

Substances	Index number	EC number	CAS number	Notes
overhead fractionation; Refinery gas (A complex combination obtained by the fractionation of products from the fluidized catalytic cracker and gas oil desulphurizer. It consists of hydrogen and hydrocarbons having carbon numbers predominantly in the range of C ₁ through C ₄ .)				
Gases (petroleum), crude distn. and catalytic cracking; Refinery gas (A complex combination produced by crude distillation and catalytic cracking processes. It consists of hydrogen, hydrogen sulphide, nitrogen, carbon monoxide and paraffinic and olefinic hydrocarbons having carbon numbers predominantly in the range of C ₁ through C ₆ .)	649-168-00-2	273-563-5	68989-88-8	K
Gases (petroleum), gas oil diethanolamine	649-169-00-8	295-397-2	92045-15-3	K

Substances	Index number	EC number	CAS number	Notes
scrubber off; Refinery gas (A complex combination produced by desulphurization of gas oils with diethanolamine. It consists predominantly of hydrogen sulphide, hydrogen and aliphatic hydrocarbons having carbon numbers in the range of C ₁ through C ₅ .)				
Gases (petroleum), gas oil hydrodesulphuriza effluent; Refinery gas (A complex combination obtained by separation of the liquid phase from the effluent from the hydrogenation reaction. It consists predominantly of hydrogen, hydrogen sulphide and aliphatic hydrocarbons having carbon numbers predominantly in the range of C ₁ through C ₃ .)	649-170-00-3	295-398-8	92045-16-4	K
Gases (petroleum), gas oil hydrodesulphuriza purge; Refinery gas (A complex	649-171-00-9 ution	295-399-3	92045-17-5	K

Substances	Index number	EC number	CAS number	Notes
combination of gases obtained from the reformer and from the purges from the hydrogenation reactor. It consists predominantly of hydrogen and aliphatic hydrocarbons having carbon numbers predominantly in the range of C ₁ through C ₄ .)				
Gases (petroleum), hydrogenator effluent flash drum off; Refinery gas (A complex combination of gases obtained from flash of the effluents after the hydrogenation reaction. It consists predominantly of hydrogen and aliphatic hydrocarbons having carbon numbers predominantly in the range of C ₁ through C ₆ .)	649-172-00-4	295-400-7	92045-18-6	K
Gases (petroleum), naphtha steam cracking high- pressure residual; Refinery gas (A complex combination obtained as a mixture of the non-condensable	649-173-00-X	295-401-2	92045-19-7	K

Substances	Index number	EC number	CAS number	Notes
portions from the product of a naphtha steam cracking process as well as residual gases obtained during the preparation of subsequent products. It consists predominantly of hydrogen and paraffinic and olefinic hydrocarbons having carbon numbers predominantly in the range of C ₁ through C ₅ with which natural gas may also be mixed.)				
Gases (petroleum), residue visbaking off; Refinery gas (A complex combination obtained from viscosity reduction of residues in a furnace. It consists predominantly of hydrogen sulphide and paraffinic and olefinic hydrocarbons having carbon numbers predominantly in the range of C ₁ through C ₅ .)	649-174-00-5	295-402-8	92045-20-0	K
Foots oil (petroleum), acid-treated; Foots	649-175-00-0	300-225-7	93924-31-3	L

Substances	Index number	EC number	CAS number	Notes
oil (A complex combination of hydrocarbons obtained by treatment of Foot's oil with sulphuric acid. It consists predominantly of branched-chain hydrocarbons with carbon numbers predominantly in the range of C ₂₀ through C ₅₀ .)				
Foots oil (petroleum), clay-treated; Foots oil (A complex combination of hydrocarbons obtained by treatment of Foot's oil with natural or modified clay in either a contacting or percolation process to remove the trace amounts of polar compounds and impurities present. It consists predominantly of branched chain hydrocarbons with carbon numbers predominantly in the range of C ₂₀ through C ₅₀ .)	649-176-00-6	300-226-2	93924-32-4	L
Gases (petroleum), C ₃ —4 Petroleum gas (A complex combination of	649-177-00-1	268-629-5	68131-75-9	K

Substances	Index number	EC number	CAS number	Notes
hydrocarbons produced by distillation of products from the cracking of crude oil. It consists of hydrocarbons having carbon numbers in the range of C ₃ through C ₄ , predominantly of propane and propylene, and boiling in the range of approximately – 51°C to –1°C (– 60°F to 30°F).)				
Tail gas (petroleum), catalytic cracked distillate and catalytic cracked naphtha fractionation absorber; Petroleum gas (The complex combination of hydrocarbons from the distillation of the products from catalytic cracked distillates and catalytic cracked naphtha. It consists predominantly of hydrocarbons having carbon numbers in the range of C ₁ through C ₄ .)	649-178-00-7	269-617-2	68307-98-2	K
Tail gas (petroleum), catalytic polymn. naphtha fractionation	649-179-00-2	269-618-8	68307-99-3	K

Substances	Index number	EC number	CAS number	Notes
stabilizer; Petroleum gas (A complex combination of hydrocarbons from the fractionation stabilization products from polymerization of naphtha. It consists predominantly of hydrocarbons having carbon numbers in the range of C ₁ through C ₄ .)				
Tail gas (petroleum), catalytic reformed naphtha fractionation stabilizer, hydrogen sulphide-free; Petroleum gas (A complex combination of hydrocarbons obtained from fractionation stabilization of catalytic reformed naphtha and from which hydrogen sulphide has been removed by amine treatment. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C ₁ through C ₄ .)	649-180-00-8	269-619-3	68308-00-9	K
Tail gas (petroleum), cracked distillate	649-181-00-3	269-620-9	68308-01-0	K

Substances	Index number	EC number	CAS number	Notes
hydrotreater stripper; Petroleum gas (A complex combination of hydrocarbons obtained by treating thermal cracked distillates with hydrogen in the presence of a catalyst. It consists predominantly of saturated hydrocarbons having carbon numbers predominantly in the range of C ₁ through C ₆ .)				
Tail gas (petroleum), straight-run distillate hydrodesulphurize hydrogen sulfidefree; Petroleum gas (A complex combination of hydrocarbons obtained from catalytic hydrodesulphuriza of straight run distillates and from which hydrogen sulphide has been removed by amine treatment. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C1 through C4.)		269-630-3	68308-10-1	K

Substances	Index number	EC number	CAS number	Notes
Tail gas (petroleum), gas oil catalytic cracking absorber; Petroleum gas (A complex combination of hydrocarbons obtained from the distillation of products from the catalytic cracking of gas oil. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C ₁ through C ₅ .)	649-183-00-4	269-623-5	68308-03-2	K
Tail gas (petroleum), gas recovery plant; Petroleum gas (A complex combination of hydrocarbons from the distillation of products from miscellaneous hydrocarbon streams. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C ₁ through C ₅ .)	649-184-00-X	269-624-0	68308-04-3	K
Tail gas (petroleum), gas recovery plant deethanizer; Petroleum gas (A complex combination of	649-185-00-5	269-625-6	68308-05-4	K

Substances	Index number	EC number	CAS number	Notes
hydrocarbons from the distillation of products from miscellaneous hydrocarbon streams. It consists of hydrocarbon having carbon numbers predominantly in the range of C ₁ through C ₄ .)				
Tail gas (petroleum), hydrodesulphurized distillate and hydrodesulphurized naphtha fractionator acidfree; Petroleum gas (A complex combination of hydrocarbons obtained from fractionation of hydrodesulphurized naphtha and distillate hydrocarbon streams and treated to remove acidic impurities, It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C ₁ through C ₅ .)	d	269-626-1	68308-06-5	K
Tail gas (petroleum), hydrodesulphurized vacuum gas oil stripper, hydrogen sulphide-free; Petroleum gas (A complex	649-187-00-6 d	269-627-7	68308-07-6	K

Substances	Index number	EC number	CAS number	Notes
combination of				
hydrocarbons				
obtained from				
stripping				
stabilization				
of catalytic				
hydrodesulphurize	ed			
vacuum gas				
oil and from				
which hydrogen				
sulphide has				
been removed by				
amine treatment.				
It consists				
predominantly				
of hydrocarbons				
having carbon				
numbers				
predominantly in				
the range of C_1				
through C ₆ .)				
Tail gas	649-188-00-1	269-629-8	68308-09-8	K
(petroleum),				
light straight-run				
naphtha stabilizer,				
hydrogen				
sulphide-free;				
Petroleum gas				
(A complex				
combination of				
hydrocarbons				
obtained from				
fractionation				
stabilization of				
light straight-run				
naphtha and from				
which hydrogen				
sulphide has				
been removed by				
amine treatment.				
It consists				
predominantly				
of hydrocarbons				
having carbon				
numbers				
predominantly in				
the range of C_1				
through C ₅ .)				
Tail gas	649-189-00-7	269-631-9	68308-11-2	K
(petroleum),	U+7-107-UU-/	207-031-9	00300-11-2	Λ
(penoieum),				

Substances	Index number	EC number	CAS number	Notes
propane- propylene alkylation feed prep deethanizer; Petroleum gas (A complex combination of hydrocarbons obtained from the distillation of the reaction products of propane with propylene. It consists of hydrocarbons having carbon numbers predominantly in the range of C ₁ through C ₄ .)				
Tail gas (petroleum), vacuum gas oil hydrodesulphurize hydrogen sulphide-free; Petroleum gas (A complex combination of hydrocarbons obtained from catalytic hydrodesulphuriza of vacuum gas oil and from which hydrogen sulphide has been removed by amine treatment. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C1 through C6.)		269-632-4	68308-12-3	K
Gases (petroleum), catalytic cracked	649-191-00-8	270-071-2	68409-99-4	K

Substances	Index number	EC number	CAS number	Notes
overheads;				
Petroleum gas				
(A complex				
combination of				
hydrocarbons				
produced by the				
distillation of				
products from				
the catalytic				
cracking process.				
It consists of				
hydrocarbons				
having carbon				
numbers				
predominantly				
in the range of				
C ₃ through C ₅				
and boiling in				
the range of				
approximately —				
48°C to 32°C (—				
54°F to 90°F).)				
Alkanes, C_{1-2} ;	649-193-00-9	270-651-5	68475-57-0	K
Petroleum gas				
Alkanes, C_{2-3} ;	649-194-00-4	270-652-0	68475-58-1	K
Petroleum gas	049-194-00-4	270-032-0	004/3-30-1	K
	(40.105.00.37	250 (52 (60455 50 0	**
Alkanes, C_{3_4}	649-195-00-X	270-653-6	68475-59-2	K
Petroleum gas				
Alkanes, C _{4—5}	649-196-00-5	270-654-1	68475-60-5	K
Petroleum gas				
9				
Fuel gases;	649-197-00-0	270-667-2	68476-26-6	K
Petroleum gas				
(A combination				
of light gases.				
It consists				
predominantly				
of hydrogen				
and/or low				
molecular weight				
hydrocarbons.)				
Fuel gases, crude	649-198-00-6	270-670-9	68476-29-9	K
oil of distillates;	017 170 00 0	270 070 9	00170277	11
Petroleum gas				
(A complex				
combination				
of light gases				
produced by				
distillation of				
aistinution of				

Substances	Index number	EC number	CAS number	Notes
crude oil and by catalytic reforming of naphtha. It consists of hydrogen and hydrocarbons having carbon numbers predominantly in the range of C ₁ through C ₄ and boiling in the range of approximately — 217°C to — 12°C (—423°F to 10°F).)				
Hydrocarbons, C ₃ _4 Petroleum gas	649-199-00-1	270-681-9	68476-40-4	K
Hydrocarbons, C ₄ _5 Petroleum gas	649-200-00-5	270-682-4	68476-42-6	K
Hydrocarbons, C _{2—4} , C ₃ -rich; Petroleum gas	649-201-00-0	270-689-2	68476-49-3	K
Petroleum gases, liquefied; Petroleum gas (A complex combination of hydrocarbons produced by the distillation of crude oil. It consists of hydrocarbons having carbon numbers predominantly in the range of C ₃ through C ₇ and boiling in the range of approximately — 40°C to 80°C (— 40°F to 176°F).)	649-202-00-6	270-704-2	68476-85-7	K
Petroleum gases, liquefied, sweetened;	649-203-00-1	270-705-8	68476-86-8	K

Substances	Index number	EC number	CAS number	Notes
Petroleum gas (A complex combination of hydrocarbons obtained by subjecting liquefied petroleum gas mix to a sweetening process to convert mercaptans or to remove acidic impurities. It consists of hydrocarbons having carbon numbers predominantly in the range of C ₃ through C ₇ and boiling in the range of approximately — 40°C to 80°C (— 40°F to 176°F).)				
Gases (petroleum), C ₃ —4, isobutanerich; Petroleum gas (A complex combination of hydrocarbons from the distillation of saturated and unsaturated hydrocarbons usually ranging in carbon numbers from C ₃ through C ₆ , predominantly butane and isobutane. It consists of saturated and unsaturated hydrocarbons having carbon numbers in	649-204-00-7	270-724-1	68477-33-8	K

Substances	Index number	EC number	CAS number	Notes
the range of C ₃ through C ₄ , predominantly isobutane.)				
Distillates (petroleum), C ₃ 6, piperylenerich; Petroleum gas (A complex combination of hydrocarbons from the distillation of saturated and unsaturated aliphatic hydrocarbons usually ranging in the carbon numbers C ₃ through C ₆ . It consists of saturated and unsaturated hydrocarbons having carbon numbers in the range of C ₃ through C ₆ , predominantly piperylenes.)	649-205-00-2	270-726-2	68477-35-0	K
Gases (petroleum), butane splitter overheads; Petroleum gas (A complex combination of hydrocarbons obtained from the distillation of the butane stream. It consists of aliphatic hydrocarbons having carbon numbers predominantly in the range of C ₃ through C ₄ .)	649-206-00-8	270-750-3	68477-69-0	K

Substances	Index number	EC number	CAS number	Notes
Gases (petroleum), C ₂ _3; Petroleum gas (A complex combination of hydrocarbons produced by the distillation of products from a catalytic fractionation process. It contains predominantly ethane, ethylene, propane, and propylene.)	649-207-00-3	270-751-9	68477-70-3	K
Gases (petroleum), catalytic-cracked gas oil depropanizer bottoms, C ₄ -rich acid-free; Petroleum gas (A complex combination of hydrocarbons obtained from fractionation of catalytic cracked gas oil hydrocarbon stream and treated to remove hydrogen sulphide and other acidic components. It consists of hydrocarbons having carbon numbers in the range of C ₃ through C ₅ , predominantly C ₄ .)	649-208-00-9	270-752-4	68477-71-4	K
Gases (petroleum), catalytic-	649-209-00-4	270-754-5	68477-72-5	K

Substances	Index number	EC number	CAS number	Notes
cracked naphtha debutanizer bottoms, C_{3-5} -rich; Petroleum gas (A complex combination of hydrocarbons obtained from the stabilization of catalytic cracked naphtha. It consists of aliphatic hydrocarbons having carbon numbers predominantly in the range of C_3 through C_5 .)				
Tail gas (petroleum), isomerized naphtha fractionation stabilizer; Petroleum gas (A complex combination of hydrocarbons obtained from the fractionation stabilization products from isomerized naphtha. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C ₁ through C ₄ .)	649-210-00-X	269-628-2	68308-08-7	K
Foots oil (petroleum), carbon-treated; Foot's oil (A complex combination of hydrocarbons	649-211-00-5	308-126-0	97862-76-5	L

Substances	Index number	EC number	CAS number	Notes
obtained by the treatment of Foot's oil with activated carbon for the removal of trace constituents and impurities. It consists predominantly of saturated straight chain hydrocarbons having carbon numbers predominantly greater than C ₁₂ .)				
Distillates (petroleum), sweetened middle; Gas oil —unspecified (A complex combination of hydrocarbons obtained by subjecting a petroleum distillate to a sweetening process to convert mercaptans or to remove acidic impurities. It consists of hydrocarbons having carbon numbers predominantly in the range of C9 through C20 and boiling in the range of approximately 150°C to 345°C (302°F to 653°F).)	649-212-00-0	265-088-7	64741-86-2	N
Gas oils (petroleum), solvent- refined; Gas oil unspecified	649-213-00-6	265-092-9	64741-90-8	N

Substances	Index number	EC number	CAS number	Notes
(A complex combination of hydrocarbons obtained as the raffinate from a solvent extraction process. It consists predominantly of aliphatic hydrocarbons having carbon numbers predominantly in the range of C ₁₁ through C ₂₅ and boiling in the range of approximately 205°C to 400°C (401°F to 752°F).)				
Distillates (petroleum), solvent-refined middle; Gas oil—unspecified (A complex combination of hydrocarbons obtained as the raffinate from a solvent extraction process. It consists predominantly of aliphatic hydrocarbons having carbon numbers predominantly in the range of C ₉ through C ₂₀ and boiling in the range of approximately 150°C to 345°C (302°F to 653°F).)	649-214-00-1	265-093-4	64741-91-9	N
Gas oils (petroleum), acid-	649-215-00-7	265-112-6	64742-12-7	N
(Petroleum), acid-		159		

Substances	Index number	EC number	CAS number	Notes
treated; Gas oil —unspecified (A complex combination of hydrocarbons obtained as a raffinate from a sulphuric acid treating process. It consists of hydrocarbons having carbon numbers predominantly in the range of C ₁₃ through C ₂₅ and boiling in the range of approximately 230°C to 400°C (446°F to 752°F).)				
Distillates (petroleum), acid-treated middle; Gas oil—unspecified (A complex combination of hydrocarbons obtained as a raffinate from a sulphuric acid treating process. It consists of hydrocarbons having carbon numbers predominantly in the range of C ₁₁ through C ₂₀ and boiling in the range of approximately 205°C to 345°C (401°F to 653°F).)	649-216-00-2	265-113-1	64742-13-8	N
Distillates (petroleum), acid- treated light; Gas oil—unspecified	649-217-00-8	265-114-7	64742-14-9	N
on unspecified		160		

Substances	Index number	EC number	CAS number	Notes
(A complex				•
combination of				
hydrocarbons				
obtained as a				
raffinate from a				
sulphuric acid				
treating process.				
It consists of				
hydrocarbons				
having carbon numbers				
predominantly				
in the range of				
C_9 through C_{16}				
and boiling in				
the range of				
approximately				
150°C to 290°C				
(302°F to				
554°F).)				
Gas oils	649-218-00-3	265-129-9	64742-29-6	N
(petroleum),	019 210 00 9	203 127 7	01712270	11
chemically				
neutralized; Gas				
oil—unspecified				
(A complex				
combination of				
hydrocarbons				
produced by a				
treating process to remove acidic				
materials. It				
consists of				
hydrocarbons				
having carbon				
numbers				
predominantly				
in the range of				
C_{13} through C_{25}				
and boiling in				
the range of				
approximately				
230°C to 400°C				
(446°F to				
752°F).)				
Distillates	649-219-00-9	265-130-4	64742-30-9	N
(petroleum),				
chemically				
neutralized				
middle; Gas oil				
—unspecified		161		

Substances	Index number	EC number	CAS number	Notes
(A complex combination of hydrocarbons produced by a treating process to remove acidic materials. It consists of hydrocarbons having carbon numbers predominantly in the range of C ₁₁ through C ₂₀ and boiling in the range of approximately 205°C to 345°C (401°F to 653°F).)				
Distillates (petroleum), clay-treated middle; Gas oil—unspecified (A complex combination of hydrocarbons resulting from treatment of a petroleum fraction with natural or modified clay, usually in a percolation process to remove the trace amounts of polar compounds and impurities present. It consists of hydrocarbons having carbon numbers predominantly in the range of C9 through C20 and boiling in the range of	649-220-00-4	265-139-3	64742-38-7	N

Substances	Index number	EC number	CAS number	Notes
approximately 150°C to 345°C (302°F to 653°F).)				
Distillates (petroleum) hydrotreated middle; Gas oil—unspecified (A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C ₁₁ through C ₂₅ and boiling in the range of approximately 205°C to 400°C (401°F to 752°F).)	649-221-00-X	265-148-2	64742-46-7	N
Gas oils (petroleum), hydrodesulphurize Gas oil— unspecified (A complex combination of hydrocarbons obtained from a petroleum stock by treating with hydrogen to convert organic sulphur to hydrogen sulphide which is removed. It consists predominantly	649-222-00-5 ed;	265-182-8	64742-79-6	N

Substances	Index number	EC number	CAS number	Notes
of hydrocarbons having carbon numbers predominantly in the range of C ₁₃ through C ₂₅ and boiling in the range of approximately 230°C to 400°C (446°F to 752°F).)				
Distillates (petroleum), hydrodesulphurize middle; Gas oil —unspecified (A complex combination of hydrocarbons obtained from a petroleum stock by treating with hydrogen to convert organic sulphur to hydrogen sulphide which is removed. It consists of hydrocarbons having carbon numbers predominantly in the range of C ₁₁ through C ₂₅ and boiling in the range of approximately 205°C to 400°C (401°F to 752°F).)	649-223-00-0 d	265-183-3	64742-80-9	N
Distillates (petroleum), catalytic reformer fractionator residue, high- boiling; Gas oil —unspecified (A complex combination of	649-228-00-8	270-719-4	68477-29-2	N
*-		164		

Substances	Index number	EC number	CAS number	Notes
hydrocarbons from the distillation of catalytic reformer fractionator residue. It boils in the range of approximately 343°C to 399°C (650°F to 750°F).)				
Distillates (petroleum), catalytic reformer fractionator residue, intermediateboiling; Gas oil—unspecified (A complex combination of hydrocarbons from the distillation of catalytic reformer fractionator residue. It boils in the range of approximately 288°C to 371°C (550°F to 700°F).)	649-229-00-3	270-721-5	68477-30-5	N
Distillates (petroleum), catalytic reformer fractionator residue, low-boiling; Gas oil—unspecified (The complex combination of hydrocarbons from the distillation of catalytic reformer fractionator residue. It boils approximately below 288°C (550°F).)	649-230-00-9	270-722-0	68477-31-6	N

Substances	Index number	EC number	CAS number	Notes
Distillates (petroleum), highly refined middle; Gas oil unspecified (A complex combination of hydrocarbons obtained by the subjection of a petroleum fraction to several of the following steps: filtration, centrifugation, atmospheric distillation, vacuum distillation, acidification, neutralization and clay treatment. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C ₁₀ through C ₂₀ .)	649-231-00-4	292-615-8	90640-93-0	N
Distillates (petroleum) catalytic reformer, heavy arom. conc.; Gas oil —unspecified (A complex combination of hydrocarbons obtained from the distillation of a catalytically reformed petroleum cut. It consists predominantly of aromatic hydrocarbons having carbon numbers predominantly	649-232-00-X	295-294-2	91995-34-5	N

Substances	Index number	EC number	CAS number	Notes
in the range of C ₁₀ through C ₁₆ and boiling in the range of approximately 200°C to 300°C (392°F to 572°F).)				
Gas oils, paraffinic; Gas oil— unspecified (A distillate obtained from the redistillation of a complex combination of hydrocarbons obtained by the distillation of the effluents from a severe catalytic hydrotreatment of paraffins. It boils in the range of approximately 190°C to 330°C (374°F to 594°F).)	649-233-00-5	300-227-8	93924-33-5	N
Naphtha (petroleum), solvent-refined hydrodesulphurize heavy; Gas oil— unspecified	649-234-00-0 ed	307-035-3	97488-96-5	N
Hydrocarbons, C _{16—20} , hydrotreated middle distillate, distn. lights; Gas oil—unspecified (A complex combination of hydrocarbons obtained as first runnings from the vacuum distillation of effluents from the treatment of a middle distillate	649-235-00-6	307-659-6	97675-85-9	N

Substances	Index number	EC number	CAS number	Notes
with hydrogen.				
It consists				
predominantly				
of hydrocarbons				
having carbon				
numbers				
predominantly				
in the range of				
C_{16} through C_{20}				
and boiling in				
the range of				
approximately				
290°C to 350°C				
(554°F to 662°F).				
It produces a				
finished oil having a viscosity				
of 2 cSt at 100°C				
(212°F).)				
Hydrocarbons,	649-236-00-1	307-660-1	97675-86-0	N
C_{12-20} ,				
hydrotreated				
paraffinic, distn.				
lights; Gas oil				
—unspecified(A complex				
combination of				
hydrocarbons				
obtained as first				
runnings from				
the vacuum				
distillation of				
effluents from				
the treatment of				
heavy paraffins				
with hydrogen				
in the presence				
of a catalyst. It consists				
predominantly				
of hydrocarbons				
having carbon				
numbers				
predominantly				
in the range of				
C_{12} through C_{20}				
and boiling in				
the range of				
approximately				
230°C to 350°C				
$(446^{\circ}\text{F to }662^{\circ}\text{F}).$				

Substances	Index number	EC number	CAS number	Notes
It produces a finished oil having a viscosity of 2 cSt at 100°C (212°F).)				
Hydrocarbons, C _{11—17} , solvent-extd. light naphthenic; Gas oil—unspecified (A complex combination of hydrocarbons obtained by extraction of the aromatics from a light naphthenic distillate having a visciosity of 2.2 cSt at 40°C (104°F). It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C ₁₁ through C ₁₇ and boiling in the range of approximately 200°C to 300°C (392°F to 572°F).)	649-237-00-7	307-757-9	97722-08-2	N
Gas oils, hydrotreated; Gas oil—unspecified (A complex combination of hydrocarbons obtained from the redistillation of the effluents from the treatment of paraffins with hydrogen in the presence of a catalyst. It consists predominantly	649-238-00-2	308-128-1	97862-78-7	N

Substances	Index number	EC number	CAS number	Notes
of hydrocarbons having carbon numbers predominantly in the range of C ₁₇ through C ₂₇ and boiling in the range of approximately 330°C to 340°C (626°F to 644°F).)				
Distillates (petroleum), carbon-treated light paraffinic; Gas oil—unspecified (A complex combination of hydrocarbons obtained by the treatment of a petroleum oil fraction with activated charcoal for the removal of traces of polar constituents and impurities. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C ₁₂ through C ₂ 8.)	649-239-00-8	309-667-5	100683-97-4	N
Distillates (petroleum), intermediate paraffinic, carbontreated; Gas oil unspecified (A complex combination of hydrocarbons obtained by the treatment	649-240-00-3	309-668-0	100683-98-5	N

Substances	Index number	EC number	CAS number	Notes
of petroleum with activated charcoal for the removal of trace polar constituents and impurities. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C_{16} through C_{36} .)				
Distillates (petroleum), intermediate paraffinic, claytreated; Gas oil—unspecified (A complex combination of hydrocarbons obtained by the treatment of petroleum with bleaching earth for the removal of trace polar constituents and impurities. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C ₁₆ through C ₃₆ .)	649-241-00-9	309-669-6	100683-99-6	N
Alkanes, C ₁₂ — ₂₆ —branched and linear;	649-242-00-4	292-454-3	90622-53-0	N
Lubricating greases; Grease (A complex combination of hydrocarbons having carbon numbers predominantly in	649-243-00-X	278-011-7	74869-21-9	N

Substances	Index number	EC number	CAS number	Notes
the range of C ₁₂ through C ₅₀ . May contain organic salts of alkali metals, alkaline earth metals, and/ or aluminium compounds.)				
Slack wax (petroleum); Slack wax (A complex combination of hydrocarbons obtained from a petroleum fraction by solvent crystallization (solvent dewaxing) or as a distillation fraction from a very waxy crude. It consists predominantly of saturated straight and branched chain hydrocarbons having carbon numbers predominantly greater than C ₂₀ .)	649-244-00-5	265-165-5	64742-61-6	N
Slack wax (petroleum), acid-treated; Slack wax (A complex combination of hydrocarbons obtained as a raffinate by treatment of a petroleum slack wax fraction with sulphuric acid treating process. It consists predominantly of saturated	649-245-00-0	292-659-8	90669-77-5	N

Substances	Index number	EC number	CAS number	Notes
straight and branched chain hydrocarbons having carbon numbers predominantly greater than C ₂₀ .)	ZAMUA HUHIDUI	De number	CASO RUMOVI	.1000
Slack wax (petroleum), clay-treated; Slack wax (A complex combination of hydrocarbons obtained by treatment of a petroleum slack wax fraction with natural or modified clay in either a contacting or percolation process. It consists predominantly of saturated straight and branched hydrocarbons having carbon numbers predominantly greater than C ₂₀ .)	649-246-00-6	292-660-3	90669-78-6	N
Slack was (petroleum), hydrotreated; Slack wax (A complex combination of hydrocarbons obtained by treating slack wax with hydrogen in the presence of a catalyst. It consists predominantly of saturated straight and branched chain hydrocarbons having carbon	649-247-00-1	295-523-6	92062-09-4	N

Substances	Index number	EC number	CAS number	Notes
numbers predominantly greater than C ₂₀ .)				
Slack wax (petroleum), low-melting; Slack wax (A complex combination of hydrocarbons obtained from a petroleum fraction by solvent deparaffination. It consists predominantly of saturated straight and branched, chain hydrocarbons having carbon numbers predominantly greater than C ₁₂ .)	649-248-00-7	295-524-1	92062-10-7	N
Slack wax (petroleum), low-melting, hydrotreated; Slack wax (A complex combination of hydrocarbons obtained by treatment of low-melting petroleum slack wax with hydrogen in the presence of a catalyst. It consists predominantly of saturated straight and branched chain hydrocarbons having carbon numbers predominantly greater than C ₁₂ .)	649-249-00-2	295-525-7	92062-11-8	N

Substances	Index number	EC number	CAS number	Notes
Slack wax (petroleum), low-melting, carbon-treated; Slack wax (A complex combination of hydrocarbons obtained by the treatment of low-melting slack wax with activated carbon for the removal of trace polar constituents and impurities. It consists predominantly of saturated straight and branched chain hydrocarbons having carbon numbers predominantly greater than C ₁₂ .) Slack wax	649-250-00-8 649-251-00-3	308-155-9 308-156-4	97863-04-2 97863-05-3	N
(petroleum), low-melting, clay-treated; Slack wax (A complex combination of hydrocarbons obtained by the treatment of low-melting petroleum slack wax with bentonite for removal of trace polar constituents and impurities. It consists predominantly of saturated straight and branched chain hydrocarbons having carbon numbers predominantly greater than C ₁₂ .)	047-231-00-3	175	<i>y</i> 1003-03-3	

Substances	Index number	EC number	CAS number	Notes
Slack wax	649-252-00-9	308-158-5	97863-06-4	N
(petroleum),				
low-melting,				
silicic acid-				
treated; Slack				
wax (A complex				
combination of				
hydrocarbons				
obtained by				
the treatment				
of low-melting				
petroleum slack				
wax with silicic				
acid for the				
removal of trace				
polar constituents				
and impurities.				
It consists				
predominantly				
of saturated				
straight and				
branched chain				
hydrocarbons				
having carbon				
numbers				
predominantly				
greater than C_{12} .)				
Slack wax	649-253-00-4	309-723-9	100684-49-9	N
(petroleum),				
carbon-treated;				
Slack wax				
(A complex				
combination of				
hydrocarbons				
obtained by				
treatment of				
petroleum				
slack wax with				
activated charcoal				
for the removal				
of trace polar				
constituents and				
impurities.)				
Petrolatum;	649-254-00-X	232-373-2	8009-03-8	N
Petrolatum				
(A complex				
combination of				
hydrocarbons				
obtained as				
a semi-solid				

Substances	Index number	EC number	CAS number	Notes
from dewaxing paraffinic residual oil. It consists predominantly of saturated crystalline and liquid hydrocarbons having carbon numbers predominantly greater than C ₂₅ .)				
Petrolatum (petroleum), oxidized; Petrolatum (A complex combination of organic compounds, predominantly high molecular weight carboxylic acids, obtained by the air oxidation of petrolatum.)	649-255-00-5	265-206-7	64743-01-7	N
Petrolatum (petroleum), alumina-treated; Petrolatum (A complex combination of hydrocarbons obtained when petrolatum is treated A1 ₂ O ₃ to remove polar components and impurities. It consists predominantly of saturated, crystalline, and liquid hydrocarbons having carbon numbers predominantly greater than C ₂₅ .)	649-256-00-0	285-098-5	85029-74-9	N

Substances	Index number	EC number	CAS number	Notes
Petrolatum (petroleum), hydrotreated; Petrolatum (A complex combination of hydrocarbons obtained as a semi-solid from dewaxed paraffinic residual oil treated with hydrogen in the presence of a catalyst. It consists predominantly of saturated, microcrystalline, and liquid hydrocarbons having carbon numbers predominantly greater than C ₂₀ .)	649-257-00-6	295-459-9	92045-77-7	N
Petrolatum (petroleum), carbon-treated; Petrolatum (A complex combination of hydrocarbons obtained by the treatment of petroleum petrolatum with activated carbon for the removal of trace polar constituents and impurities. It consists predominantly of saturated hydrocarbons having carbon numbers predominantly greater than C ₂₀ .)	649-258-00-1	308-149-6	97862-97-0	N

Substances	Index number	EC number	CAS number	Notes
Petrolatum (petroleum), silicic acid-treated; Petrolatum (A complex combination of hydrocarbons obtained by the treatment of petroleum petrolatum with silicic acid for the removal of trace polar constituents and impurities. It consists predominantly of saturated hydrocarbons having carbon numbers predominantly greater than C ₂₀₋)	649-259-00-7	308-150-1	97862-98-1	N
Petrolatum (petroleum), clay-treated; Petrolatum (A complex combination of hydrocarbons obtained by treatment of petrolatum with bleaching earth for the removal of traces of polar constituents and impurities. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of greater than C ₂₅ .) Gasoline, natural;	649-260-00-2 649-261-00-8	309-706-6 232-349-1	100684-33-1 8006-61-9	P
Low boiling point naphtha	0+7-201-00-0	<i>∠J∠</i> -J+7-1	0000-01-7	1

Substances	Index number	EC number	CAS number	Notes
(A complex combination of hydrocarbons separated from natural gas by processes such as refrigeration or absorption. It consists predominantly of saturated aliphatic hydrocarbons having carbon numbers predominantly in the range of C ₄ through C ₈ and boiling in the range of approximately — 20°C to 120°C (—4°F to 248°F).)				
Naphtha; Low boiling point naphtha (Refined, partly refined, or unrefined petroleum products by the distillation of natural gas. It consists of hydrocarbons having carbon numbers predominantly in the range of C ₅ through C ₆ and boiling in the range of approximately 100°C to 200°C (212°F to 392°F).)	649-262-00-3	232-443-2	8030-30-6	P
Ligroine; Low boiling point naphtha (A complex combination of hydrocarbons	649-263-00-9	232-453-7	8032-32-4	P
₹ 		180		

Substances	Index number	EC number	CAS number	Notes
obtained by the fractional distillation of petroleum. This fraction boils in a range of approximately 20°C to 135°C (58°F to 275°F).)				
Naphtha (petroleum), heavy straightrun; Low boiling point naphtha (A complex combination of hydrocarbons produced by distillation of crude oil. It consists of hydrocarbons having carbon numbers predominantly in the range of C ₆ through C ₁₂ and boiling in the range of approximately 65°C to 230°C (149°F to 446°F).)	649-264-00-4	265-041-0	64741-41-9	P
Naphtha (petroleum), full-range straight-run; Low boiling point naphtha (A complex combination of hydrocarbons produced by distillation of crude oil. It consists of hydrocarbons having carbon numbers predominantly in the range of C ₄ through C ₁₁	649-265-00-X	265-042-6	64741-42-0	P

Substances	Index number	EC number	CAS number	Notes
and boiling in the range of approximately — 20°C to 220°C (—4°F to 428°F).)				
Naphtha (petroleum), light straight-run; Low boiling point naphtha (A complex combination of hydrocarbons produced by distillation of crude oil. It consists predominantly of aliphatic hydrocarbons having carbon numbers predominantly in the range of C ₄ through C ₁₀ and boiling in the range of approximately — 20°C to 180°C (—4°F to 356°F).)	649-266-00-5	265-046-8	64741-46-4	P
Solvent naphtha (petroleum), light aliph; Low boiling point naphtha (A complex combination of hydrocarbons obtained from the distillation of crude oil or natural gasoline. It consists predominantly of saturated hydrocarbons having carbon numbers predominantly	649-267-00-0	265-192-2	64742-89-8	P
		182		

Substances	Index number	EC number	CAS number	Notes
in the range of C ₅ through C ₁₀ and boiling in the range of approximately 35°C to 160°C (95°F to 320°F).)				
Distillates (petroleum), straight-run light; Low boiling point naphtha (A complex combination of hydrocarbons produced by the distillation of crude oil. It consists of hydrocarbons having carbon numbers predominantly in the range of C ₂ through C ₇ and boiling in the range of approximately — 88°C to 99°C (— 127°F to 210°F).)	649-268-00-6	270-077-5	68410-05-9	P
Gasoline, vapor-recovery; Low boiling point naphtha (A complex combination of hydrocarbons separated from the gases from vapor recovery systems by cooling. It consists of hydrocarbons having carbon numbers predominantly in the range of C ₄ through C ₁₁ and boiling in	649-269-00-1	271-025-4	68514-15-8	P

Substances	Index number	EC number	CAS number	Notes
the range of approximately — 20°C to 196°C (—4°F to 384°F).)				
Gasoline, straight-run, topping-plant; Low boiling point naphtha (A complex combination of hydrocarbons produced from the topping plant by the distillation of crude oil. It boils in the range of approximately 36,1°C to 193,3°C (97°F to 380°F).)	649-270-00-7	271-727-0	68606-11-1	P
Naphtha (petroleum), unsweetened; Low boiling point naphtha (A complex combination of hydrocarbons produced from the distillation of naphtha streams from various refinery processes. It consists of hydrocarbons having carbon numbers predominantly in the range of C ₅ through C ₁₂ and boiling in the range of approximately 0°C to 230°C (25°F to 446°F).)	649-271-00-2	272-186-3	68783-12-0	P
Distillates (petroleum),	649-272-00-8	272-931-2	68921-08-4	P

Substances	Index number	EC number	CAS number	Notes
light straight- run gasoline fractionation stabilizer overheads; Low boiling point naphtha (A complex combination of hydrocarbons having carbon numbers predominantly in the range of C ₃ through C ₆ .)				
Naphtha (petroleum), heavy straight run, aromcontg.; Low boiling point naphtha (A complex combination of hydrocarbons obtained from a distillation process of crude petroleum. It consists predominantly of hydrocarbons having carbon numbers in the range of C ₈ through C ₁₂ and boiling in the range of approximately 130°C to 210°C (266°F to 410°F).	649-273-00-3	309-945-6	101631-20-3	P
Naphtha (petroleum) full- range alkylate; Low boiling point modified naphtha (A complex combination of hydrocarbons produced by distillation of the	649-274-00-9	265-066-7	64741-64-6	P

Substances	Index number	EC number	CAS number	Notes
reaction products of isobutane with monoolefinic hydrocarbons usually ranging in carbon numbers from C ₃ through C ₅ . It consist of predominantly branched chain saturated hydrocarbons having carbon numbers predominantly in the range of C ₇ through C ₁₂ and boiling in the range of approximately 90°C to 220°C (194°F to 428°F).)				
Naphtha (petroleum), heavy alkylate; Low boiling point modified naphtha (A complex combination of hydrocarbons produced by distillation of the reaction products of isobutane with monoolefinic hydrocarbons usually ranging in carbon numbers from C ₃ to C ₅ . It consists of predominantly branched chain saturated hydrocarbons having carbon numbers predominantly in the range of C ₉ through C ₁₂ and boiling in the range of	649-275-00-4	265-067-2	64741-65-7	P

Substances	Index number	EC number	CAS number	Notes
approximately 150°C to 220°C (302°F to 428°F).)				
Naphtha (petroleum), light alkylate; Low boiling point modified naphtha (A complex combination of hydrocarbons produced by distillation of the reaction products of isobutane with monoolefinic hydrocarbons usually ranging in carbon numbers from C ₃ through C ₅ . It consists of predominantly branched chain saturated hydrocarbons having carbon numbers predominantly in the range of C ₇ through C ₁₀ and boiling in the range of approximately 90°C to 160°C (194°F to 320°F).)	649-276-00-X	265-068-8	64741-66-8	P
Naphtha (petroleum), isomerization; Low boiling point modified naphtha (A complex combination of hydrocarbons obtained from catalytic isomerization of straight chain paraffinic C ₄ through C ₆	649-277-00-5	265-073-5	64741-70-4	P

Substances	Index number	EC number	CAS number	Notes
hydrocarbons. It consists predominantly of saturated hydrocarbons such as isobutane, isopentane, 2,2-dimethylbutane, 2-methylpentane, and 3-methylpentane.)				
Naphtha (petroleum), solvent-refined light; Low boiling point modified naphtha (A complex combination of hydrocarbons obtained as the raffinate from a solvent extraction process. It consists predominantly of aliphatic hydrocarbons having carbon numbers predominantly in the range of C ₅ through C ₁₁ and boiling in the range of approximately 35°C to 190°C (95°F to 374°F).)	649-278-00-0	265-086-6	64741-84-0	P
Naphtha (petroleum), solvent-refined heavy; Low boiling point modified naphtha (A complex combination of hydrocarbons obtained as the raffinate from a solvent extraction process.	649-279-00-6	265-095-5	64741-92-0	P

Substances	Index number	EC number	CAS number	Notes
It consists predominantly of aliphatic hydrocarbons having carbon numbers predominantly in the range of C ₇ through C ₁₂ and boiling in the range of approximately 90°C to 230°C (194°F to 446°F).)				
Raffinates (petroleum), catalytic reformer ethylene glycol-water countercurrent exts.; Low boiling point modified naphtha (A complex combination of hydrocarbons obtained as the raffinate from the UDEX extraction process on the catalytic reformer stream. It consists of saturated hydrocarbons having carbon numbers predominantly in the range of C ₆ through C ₉ .)	649-280-00-1	270-088-5	68410-71-9	P
Raffinates (petroleum), reformer, Lurgi unit-sepd.; Low boiling point modified naphtha (The complex combination of hydrocarbons obtained as a	649-281-00-7	270-349-3	68425-35-4	P

Substances	Index number	EC number	CAS number	Notes
raffinate from a Lurgi separation unit. It consists predominantly of non-aromatic hydrocarbons with various small amounts of aromatic hydrocarbons having carbon numbers predominantly in the range of C ₆ through C ₈).				
Naphtha (petroleum), full-range alkylate, butane-contg.; Low boiling point modified naphtha (A complex combination of hydrocarbons produced by the distillation of the reaction products of isobutane with monoolefinic hydrocarbons usually ranging in carbon numbers from C ₃ through C ₅ . It consists of predominantly branched chain saturated hydrocarbons having carbon numbers predominantly in the range of C ₇ through C ₁₂ with some butanes and boiling in the range of approximately 35°C to 200°C (95°F to 428°F).)	649-282-00-2	271-267-0	68527-27-5	P

Substances	Index number	EC number	CAS number	Notes
Distillates (petroleum), naphtha steam cracking-derived, solvent-refined light hydrotreated; Low boiling point modified naphtha (A complex combination of hydrocarbons obtained as the raffinates from a solvent extraction process of hydrotreated light distillate from steam-cracked naphtha.)	649-283-00-8	295-315-5	91995-53-8	P
Naphtha (petroleum), C ₄ -12 butane-alkylate, isooctane-rich; Low boiling point modified naphtha (A complex combination of hydrocarbons obtained by alkylation of butanes. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C ₄ through C ₁₂ , rich in isooctane, and boiling in the range of approximately 35°C to 210°C (95°F to 410°F).)	649-284-00-3	295-430-0	92045-49-3	P
Hydrocarbons, hydrotreated light naphtha	649-285-00-9	295-436-3	92045-55-1	P

Substances	Index number	EC number	CAS number	Notes
distillates, solvent-refined; Low boiling point modified naphtha (A combination of hydrocarbons obtained from the distillation of hydrotreated naphtha followed by a solvent extraction and distillation process. It consists predominantly of saturated hydrocarbons boiling in the range of approximately 94°C to 99°C (201°F to 210°F).				
Naphtha (petroleum), isomerization, C ₆ -fraction; Low boiling point modified naphtha (A complex combination of hydrocarbons obtained by distillation of a gasoline which has been catalytically isomerized. It consists predominantly of hexane isomers boiling in the range of approximately 60°C to 66°C (140°F to 151°F).)	649-286-00-4	295-440-5	92045-58-4	P
Hydrocarbons, C _{6—7} , naphthacracking, solventrefined; Low	649-287-00-X	295-446-8	90245-64-2	P
		102		

Substances	Index number	EC number	CAS number	Notes
boiling point modified naphtha (A complex combination of hydrocarbons obtained by the sorption of benzene from a catalytically fully hydrogenated benzene-rich hydrocarbon cut that was distillatively obtained from prehydrogenated cracked naphtha. It consists predominantly of paraffinic and naphthenic hydrocarbons having carbon numbers predominantly in the range of C ₆ through C ₇ and boiling in the range of approximately 70°C to 100°C (158°F to 212°F).)				
Hydrocarbons, C ₆ -rich, hydrogenated light naphtha distillates, solvent-refined; Low boiling point modified naphtha (A complex combination of hydrocarbons obtained by distillation of hydrotreated naphtha followed by solvent extraction. It consists	649-288-00-5	309-871-4	101316-67-0	P

Substances	Index number	EC number	CAS number	Notes
predominantly of saturated hydrocarbons and boiling in the range of approximately 65°C to 70°C (149°F to 158°F).)				
Naphtha (petroleum), heavy catalytic cracked; Low boiling point catcracked naphtha (A complex combination of hydrocarbons produced by a distillation of products from a catalytic cracking process. It consists of hydrocarbons having carbon numbers predominantly in the range of C ₆ through C ₁₂ and boiling in the range of approximately 65°C to 230°C (148°F to 446°F). It contains a relatively large proportion of unsaturated hydrocarbons.)	649-289-00-0	265-055-7	64741-54-4	P
Naphtha (petroleum), light catalytic cracked; Low boiling point cat- cracked naphtha (A complex combination of hydrocarbons produced by the distillation	649-290-00-6	265-056-2	64741-55-5	P
		104		

Substances	Index number	EC number	CAS number	Notes
of products from a catalytic cracking process. It consists of hydrocarbons having carbon numbers predominantly in the range of C ₄ through C ₁₁ and boiling in the range of approximately — 20°C to 190°C (—4°F to 374°F). It contains a relatively large proportion of unsaturated hydrocarbons.)				
Hydrocarbons, C _{3—11} , catalytic cracker distillates; Low boiling point catcracked naphtha (A complex combination of hydrocarbons produced by the distillations of products from a catalytic cracking process. It consists of hydrocarbons having carbon numbers predominantly in the range of C ₃ through C ₁₁ and boiling in a range approximately up to 204°C (400°F).)	649-291-00-1	270-686-6	68476-46-0	P
Naphtha (petroleum), catalytic cracked light dist.; Low boiling point cat-	649-292-00-7	272-185-8	68783-09-5	P

Substances	Index number	EC number	CAS number	Notes
cracked naphtha (A complex combination of hydrocarbons produced by the distillation of products from a catalytic cracking process. It consists of hydrocarbons having carbon numbers predominantly in the range of C ₁ through C ₅ .)				
Distillates (petroleum), naphtha steam cracking-derived, hydrotreated light arom.; Low boiling point catcracked naphtha. (A complex combination of hydrocarbons obtained by treating a light distillate from steam-cracked naphtha. It consists predominantly of aromatic hydrocarbons.)	649-293-00-2	295-311-3	91995-50-5	P
Naphtha (petroleum), heavy catalytic cracked, sweetened; Low boiling point catcracked naphtha (A complex combination of hydrocarbons obtained by subjecting a catalytic cracked petroleum distillate to a	649-294-00-8	295-431-6	92045-50-6	P

Substances	Index number	EC number	CAS number	Notes
sweetening			2122 114111001	- 1000
process to convert				
mercaptans				
or to remove				
acidic impurities.				
It consists				
predominantly				
of hydrocarbons				
having carbon				
numbers				
predominantly				
in the range of				
C_6 through C_{12}				
and boiling in				
the range of				
approximately				
60°C to 200°C				
(140°F to				
392°F).)				
Naphtha	649-295-00-3	295-441-0	92045-59-5	P
(petroleum), light				
catalytic cracked				
sweetened; Low				
boiling point cat-				
cracked naphtha				
(A complex				
combination of				
hydrocarbons				
obtained by				
subjecting				
naphtha from a catalytic cracking				
process to a				
sweetening				
process to convert				
mercaptans				
or to remove				
acidic impurities.				
It consists				
predominantly				
of hydrocarbons				
boiling in a range				
of approximately				
35°C to 210°C				
(95°F to 410°F).)				
Hydrocarbons,	649-296-00-9	295-794-0	92128-94-4	P
C_{8-12} , catalytic-				
cracking, chem.				
neutralized; Low				
boiling point cat-				
cracked naphtha				
		197		

Substances	Index number	EC number	CAS number	Notes
(A complex combination of hydrocarbons produced by the distillation of a cut from the catalytic cracking process, having undergone an alkaline washing. It consists predominantly of hydrocarbons having carbon numbers in the range of C ₈ through C ₁₂ and boiling in the range of approximately 130°C to 210°C (266°F to 410°F).)	Index number	EC number	CAS HUMBET	TABLES
Hydrocarbons, C_{8-12} , catalytic cracker distillates; Low boiling point catcracked naphtha (A complex combination of hydrocarbons obtained by distillation of products from a catalytic cracking process. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C_8 through C_{12} and boiling in the range of approximately 140°C to 210°C (284°F to 410°F).)	649-297-00-4	309-974-4	101794-97-2	P

Substances	Index number	EC number	CAS number	Notes
Hydrocarbons, C ₈ -12, catalytic cracking, chem. neutralized, sweetened; Low boiling point cat- cracked naphtha	649-298-00-X	309-987-5	101896-28-0	P
Naphtha (petroleum), light catalytic reformed; Low boiling point catreformed naphtha (A complex combination of hydrocarbons produced from the distillation of products from a catalytic reforming process. It consists of hydrocarbons having carbon numbers predominantly in the range of C ₅ through C ₁₁ and boiling in the range of approximately 35°C to 190°C (95°F to 374°F. It contains a relatively large proportion of aromatic and branched chain hydrocarbons. This stream may contain 10 vol. % or more benzene.)	649-299-00-5	265-065-1	64741-63-5	P
Naphtha (petroleum), heavy catalytic reformed; Low boiling point cat- reformed naphtha (A complex	649-300-00-9	265-070-9	64741-68-0	P

Substances	Index number	EC number	CAS number	Notes
combination of hydrocarbons produced from the distillation of products from a catalytic reforming process. It consists of predominantly aromatic hydrocarbons having numbers predominantly in the range of C ₇ through C ₁₂ and boiling in the range of approximately 90°C to 230°C (194°F to 446°F).)				
Distillates (petroleum), catalytic reformed depentanizer; Low boiling point catreformed naphtha (A complex combination of hydrocarbons from the distillation of products from a catalytic reforming process. It consists predominantly of aliphatic hydrocarbons having carbon numbers predominantly in the range of C ₃ through C ₆ and boiling in the range of approximately -	649-301-00-4	270-660-4	68475-79-6	P

Cubstance	Index number	EC number	CAS number	Notes
Substances 49°C to 63°C (-	ingex number	£C number	CAS number	Notes
57°F to 145°F).)				
Hydrocarbons, C ₂ _6, C ₆ —8 catalytic reformer; Low boiling point catreformed naphtha		270-687-1	68476-47-1	P
Residues (petroleum), C _{6—8} catalytic reformer; Low boiling point catreformed naphtha (A complex residuum from the catalytic reforming of C _{6—8} feed. It consists of hydrocarbons having carbon numbers predominantly in the range of C ₂ through C ₆ .)	649-303-00-5	270-794-3	68478-15-9	P
Naptha (petroleum), light catalytic reformed, aromfree; low boiling point catreformed naphtha (A complex combination of hydrocarbons obtained from distillation of products from a catalytic reforming process. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C ₅ through C ₈ and boiling in the range of	649-304-00-0	270-993-5	68513-03-1	P
		201		

Substances	Index number	EC number	CAS number	Notes
approximately 35°C to 120°C (95°F to 248°F). It contains a relatively large proportion of branched chain hydro-carbons with the aromatic components removed.)				
Distillates (petroleum), catalytic reformed straightrun naphtha overheads; Low boiling point catreformed naphtha (A complex combination of hydrocarbons obtained by the catalytic reforming of straightrun naphtha followed by the fractionation of the total effluent. It consists of saturated aliphatic hydrocarbons having carbon numbers predominantly in the range of C ₂ through C ₆ .)	649-305-00-6	271-008-1	68513-63-3	P
Petroleum products, hydrofiner- powerformer reformates; Low boiling point cat- reformed naphtha (The complex combination of hydrocarbons obtained in a hydro finer- powerformer	649-306-00-1	271-058-4	68514-79-4	P

Substances	Index number	EC number	CAS number	Notes
process and boiling in a range of approximately 27°C to 210°C (80°F to 410°F).)				
Naphtha (petroleum, full-range reformed; Low boiling point catreformed naphtha (A complex combination of hydrocarbons produced by the distillation of the products from a catalytic reforming process. It consists of hydrocarbons having carbon numbers predominantly in the range of C ₅ through C ₁₂ and boiling in the range of approximately 35°C to 230°C (95°F to 446°F).)	649-307-00-7	272-895-8	68919-37-9	P
Naphtha (petroleum), catalytic reformed; Low boiling point catreformed naphtha (A complex combination of hydrocarbons produced by the distillation of products from a catalytic reforming process. It consists of hydrocarbons having carbon numbers	649-308-00-2	273-271-8	68955-35-1	P

Substances	Index number	EC number	CAS number	Notes
predominantly in the range of C ₄ through C ₁₂ and boiling in the range of approximately 30°C to 220°C (90°F to 430°F).) It contains a relatively large proportion of aromatic and branched chain hydro-carbons. This stream may contain 10 vol.% or more benzene.)				
Distillates (petroleum), catalytic reformed hydrotreated light, C_{8-12} arom. fraction; Low boiling point catreformed naphtha (A complex combination of alkylbenzenes obtained by the catalytic reforming of petroleum naphtha. It consists predominantly of alkylbenzenes having carbon numbers predominantly in the range of C_8 through C_{10} and boiling in the range of approximately 160°C to 180°C (320°F to 356°F).)	649-309-00-8	285-509-8	85116-58-1	P
Aromatic hydrocarbons, C ₈ , catalytic	649-310-00-3	295-279-0	91995-18-5	P

Substances	Index number	EC number	CAS number	Notes
reforming- derived; Low boiling point cat- reformed naphtha.				
Aromatic hydrocarbons, C ₇ —12, C ₈ -rich; Low boiling point catreformed naphtha (A complex combination of hydrocarbons obtained by separation from the platformate-containing fraction. It consists predominantly of aromatic hydrocarbons having carbon numbers predominantly in the range of C ₇ through C ₁₂ (primarily C ₈) and can contain non aromatic hydrocarbons, both boiling in the range of approximately 130°C to 200°C (266°F to 392°F).)	649-311-00-9	297-401-8	93571-75-6	p
Gasoline, C ₅ —11, high- octane stabilized reformed; Low boiling point cat- reformed naphtha (A complex high octane combination of hydrocarbons obtained by the catalytic dehydrogenation of a	649-312-00-4	297-458-9	93572-29-3	P

Substances	Index number	EC number	CAS number	Notes
predominantly naphthenic naphtha. It consists predominantly of aromatics and non-aromatics having carbon numbers predominantly in the range of C ₅ through C ₁₁ and boiling in the range of approximately 45°C to 185°C (113°F to 365°F).)				
Hydrocarbons, C _{7—12} , C ₉ - aromrich, reforming heavy fraction; Low boiling point cat- reformed naphtha (A complex combination of hydrocarbons obtained by separation from the platformate- containing fraction. It consists predominantly of nonaromatic hydrocarbons having carbon numbers predominantly in the range of C ₇ through C ₁₂ and boiling in the range of approximately 120°C to 210°C (248°F to 380°F) and C ₉ and higher aromatic hydrocarbons.)	649-313-00-X	297-465-7	93572-35-1	P

Substances	Index number	EC number	CAS number	Notes
Substances Hydrocarbons, C ₅ —11, nonaroms rich, reforming light fraction; Low boiling point cat- reformed naphtha (A complex combination of hydrocarbons obtained by		EC number 297-466-2	CAS number 93572-36-2	Notes P
separation from the platformate-containing fraction. It consists predominantly of non aromatic hydrocarbons having carbon numbers predominantly in the range of C ₅ to C ₁₁ and boiling in the range of approximately 35°C to 125°C (94°F to 257°F), benzene and toluene.)				
Foots oil (petroleum), silicic acid- treated; Foots oil (A complex combination of hydrocarbons obtained by the treatment of Foots oil with silicic acid for removal of trace constituents and impurities. It consists predominantly of straight chain hydrocarbons having carbon numbers	649-315-00-0	308-127-6	97862-77-6	L

Substances	Index number	EC number	CAS number	Notes
predominantly greater than C_{12} .)	muca number	EC number	CAS HUMBER	110168
Naphtha (petroleum), light thermal cracked; Low boiling point thermally cracked naphtha (A complex combination of hydrocarbons from distillation of products from a thermal cracking process. It consists predominantly of unsaturated hydrocarbons having carbon numbers predominantly in the range of C ₄ through C ₈ and boiling in the range of approximately — 10°C to 130°C (14°F to 226°F).)	649-316-00-6	265-075-6	64741-74-8	P
Naphtha (petroleum), heavy thermal cracked; Low boiling point thermally cracked naphtha (A complex combination of hydrocarbons from distillation of products from a thermal cracking process. It consists predominantly of unsaturated hydrocarbons having carbon numbers predominantly in the range of	649-317-00-1	265-085-0	64741-83-9	P
\mathcal{E}		208		

Substances	Index number	EC number	CAS number	Notes
C ₆ through C ₁₂ and boiling in the range of approximately 65°C to 220°C (148°F to 428°F).)				
Distillates (petroleum), heavy arom.; Low boiling point thermally cracked naphtha (The complex combination of hydrocarbons from the distillation of products from the thermal cracking of ethane and propane. This higher boiling fraction consists predominantly of C ₅ -C ₇ aromatic hydrocarbons with some unsaturated aliphatic hydrocarbons having a carbon number predominantly of C ₅ . This stream may contain benzene.)	649-318-00-7	267-563-4	67891-79-6	P
Distillates (petroleum), light arom.; Low boiling point thermally cracked naphtha (The complex combination of hydrocarbons from the distillation of products from the thermal cracking	649-319-00-2	267-565-5	67891-80-9	P

Substances	Index number	EC number	CAS number	Notes
of ethane and propane. This lower boiling fraction consists predominantly of C ₅ -C ₇ aromatic hydrocarbons with some unsaturated aliphatic hydrocarbons having a carbon number predominantly of C ₅ . This stream may contain benzene.)				
Distillates (petroleum), naphtha-raffinate pyrolyzate-derived, gasoline-blending; Low boiling point thermally cracked naphtha (The complex combination of hydrocarbons obtained by the pyrolysis fractionation at 816°C (1500°F) of naphtha and raffinate. It consists predominantly of hydrocarbons having a carbon number of C9 and boiling at approximately 204°C (400°F.)	649-320-00-8	270-344-6	68425-29-6	P
Aromatic hydrocarbons, C _{6—8} , naphtharaffinate pyrolyzatederived; Low boiling point	649-321-00-3	270-658-3	68475-70-7	P

Substances	Index number	EC number	CAS number	Notes
thermally cracked naphtha (A complex combination of hydrocarbons obtained by the fractionation pyrolysis at 816°C (1500°F) of naphtha and raffinate. It consists predominantly of aromatic hydrocarbons having carbon numbers predominantly in the range of C ₆ through C ₈ , including benezene.)				
Distillates (petroleum), thermal cracked naphtha and gas oil; Low boiling point thermally cracked naphtha (A complex combination of hydrocarbons produced by distillation of thermally cracked naphtha and/or gas oil. It consists predominantly of olefinic hydrocarbons having a carbon number of C ₅ and boiling in the range of approximately 33°C to 60°C (91°F to 140°F).)	649-322-00-9	271-631-9	68603-00-9	P
Distillates (petroleum), thermal cracked	649-323-00-4	271-632-4	68603-01-0	P

Substances	Index number	EC number	CAS number	Notes
naphtha and				
gas oil, C ₅ -				
dimer-contg.;				
Low boiling				
point thermally				
cracked naphtha				
(A complex				
combination of				
hydrocarbons				
produced by				
the extractive				
distillation of				
thermal cracked				
naphtha and/or				
gas oil. It consists				
predominantly				
of hydrocarbons				
having a carbon				
number of				
C ₅ with some				
dimerized C ₅				
olefins and				
boiling in				
the range of				
approximately				
33°C to 184°C				
(91°F to 363°F).)				
Distillates	649-324-00-X	271-634-5	68603-03-2	P
(petroleum),				
thermal cracked				
naphtha and gas				
oil, extractive;				
Low boiling				
point thermally				
cracked naphtha				
(A complex				
combination of hydrocarbons				
•				
produced by the extractive				
distillation of				
thermal cracked				
naphtha and/or				
gas oil. It consists				
of paraffinic				
and olefinic				
hydrocarbons				
predominantly				
isoamylenes such				
as 2-methyl-1-				
butene and 2-				

Substances	Index number	EC number	CAS number	Notes
methyl-2-butene and boiling in the range of approximately 31°C to 40°C (88°F to 104°F).)				
Distillates (petroleum), light thermal cracked, debutanized arom.; Low boiling point thermally cracked naphtha (A complex combination of hydrocarbons produced by the distillation of products from a thermal cracking process. It consists predominantly of aromatic hydrocarbons, primarily benzene.)	649-325-00-5	273-266-0	68955-29-3	P
Naphtha (petroleum), light thermal cracked, sweetened; Low boiling point thermally cracked naphtha (A complex combination of hydrocarbons obtained by subjecting a petroleum distillate from the high temperature thermal cracking of heavy oils fractions to a sweetening process to convert mercaptans. It consists predominantly of	649-326-00-0	295-447-3	92045-65-3	P

Substances	Index number	EC number	CAS number	Notes
aromatics, olefins and saturated hydrocarbons boiling in the range of approximately 20°C to 100°C (68°F to 212°F).)				
Naphtha (petroleum), hydrotreated heavy; Low boiling point hydrogen treated naphtha (A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C ₆ through C ₁₃ and boiling in the range of approximately 65°C to 230°C (149°F to 446°F).)	649-327-00-6	265-150-3	64742-48-9	P
Naphtha (petroleum), hydrotreated light; Low boiling point hydrogen treated naphtha (A complex combination of hydrocarbons obtained by treating a petroleum fraction with	649-328-00-1	265-151-9	64742-49-0	P

Substances	Index number	EC number	CAS number	Notes
hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C ₄ through C ₁₁ and boiling in the range of —20°C to 190°C (—4°F to 374°F).)				
Naphtha (petroleum), hydrodesulphurize light; Low boiling point hydrogen treated naphtha (A complex combination of hydrocarbons obtained from a catalytic hydrodesulphuriza process. It consists of hydrocarbons having carbon numbers predominantly in the range of C ₄ through C ₁₁ and boiling in the range of approximately — 20°C to 190°C (– 4°F to 374°F).)	tion	265-178-6	64742-73-0	P
Naphtha (petroleum), hydrodesulphurize heavy; Low boiling point hydrogentreated naphtha (A complex combination of hydrocarbons obtained from a catalytic	649-330-00-2 d	265-185-4	64742-82-1	P

Substances	Index number	EC number	CAS number	Notes
hydrodesulphurization process. It consists of hydrocarbons having carbon numbers predominantly in the range of C ₇ through C ₁₂ and boiling in the range of approximately 90°C to 230°C (194°F to 446°F).)				
Distillates (petroleum), hydrotreated middle, intermediate boiling; Low boiling point hydrogen treated naphtha (A complex combination of hydrocarbons obtained by the distillation of products from a middle distillate hydrotreating process. It consists of hydrocarbons having carbon numbers predominantly in the range of C ₅ through C ₁₀ and boiling in the range of approximately 127°C to 188°C (262°F to 370°F).)	649-331-00-8	270-092-7	68410-96-8	P
Distillates (petroleum), light distillate hydrotreating process, low-	649-332-00-3	270-093-2	68410-97-9	P
r,		216		

Substances	Index number	EC number	CAS number	Notes
boiling; Low	maca number	20 number	C. D. Humber	110000
boiling point				
hydrogen				
treated naphtha				
(A complex				
combination of				
hydrocarbons				
obtained by the				
distillation of				
products from				
the light distillate				
hydrotreating				
process. It				
consists of				
hydrocarbons				
having carbon numbers				
predominantly				
in the range of				
C ₆ through C ₉				
and boiling in				
the range of				
approximately				
3°C to 194°C				
(37°F to 382°F).)				
Distillates	649-333-00-9	270-094-8	68410-98-0	P
(petroleum),	049-333-00-9	270-094-0	00410-30-0	1
hydrotreated				
heavy naphtha,				
deisohexanizer				
overheads;				
Low boiling				
point hydrogen				
treated naphtha				
(A complex				
combination of				
hydrocarbons				
obtained by the				
distillation of the				
products from a				
heavy naphtha				
hydrotreating				
process. It				
consists of hydrocarbons				
having carbon				
numbers				
predominantly				
in the range of				
C_3 through C_6				
and boiling in				
and coming in				

Substances	Index number	EC number	CAS number	Notes
the range of approximately — 49°C to 68°C (— 57°F to 155°F).)				
Solvent naphtha (petroleum), light arom., hydrotreated; Low boiling point hydrogen treated naphtha (A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists predominantly of aromatic hydrocarbons having carbon numbers predominantly in the range of C ₈ through C ₁₀ and boiling in the range of approximately 135°C to 210°C (275°F to 410°F).)	649-334-00-4	270-988-8	68512-78-7	P
Naphtha (petroleum), hydrodesulphurize thermal cracked light; Low boiling point hydrogen treated naphtha (A complex combination of hydrocarbons obtained by fractionation of hydrodesulphurize thermal cracker distillate.		285-511-9	85116-60-5	P

Substances	Index number	EC number	CAS number	Notes
It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C ₅ to C ₁₁ and boiling in the range of approximately 23°C to 195°C (73°F to 383°F).)				
Naphtha (petroleum), hydrotreated light, cycloalkane-contg.; Low boiling point hydrogen treated naphtha (A complex combination of hydrocarbons obtained from the distillation of a petroleum fraction. It consists predominantly of alkanes and cycloalkanes boiling in the range of approximately — 20°C to 190°C (—4°F to 374°F).)	649-336-00-5	285-512-4	85116-61-6	P
Naphtha (petroleum), heavy steam- cracked, hydrogenated; Low boiling point hydrogen treated naphtha	649-337-00-0	295-432-1	92045-51-7	P
Naphtha (petroleum) hydrodesulphurize full-range;	649-338-00-6 d	295-433-7	92045-52-8	P

Substances	Index number	EC number	CAS number	Notes
Low boiling				
point hydrogen				
treated naphtha				
(A complex				
combination of				
hydrocarbons				
obtained from				
a catalytic				
hydrodesulphuriza	tion			
process.				
It consists				
predominantly				
of hydrocarbons				
having carbon numbers				
predominantly				
in the range of				
C_4 through C_{11}				
and boiling in				
the range of				
approximately				
30°C to 250°C				
(86°F to 482°F).)				
` , ,	(40, 220, 00, 1	205 420 4	02045 57 2	D
Naphtha	649-339-00-1	295-438-4	92045-57-3	P
(petroleum),				
hydrotreated light steam-cracked;				
Low boiling				
point hydrogen				
treated naphtha				
(A complex				
combination of				
hydrocarbons				
obtained by				
treating a				
petroleum				
fraction, derived				
from a pyrolysis				
process, with				
hydrogen in				
the presence				
of a catalyst.				
It consists				
predominantly				
of unsaturated				
hydrocarbons having carbon				
numbers				
predominantly				
in the range of				
C_5 through C_{11}				
- 3				

Substances	Index number	EC number	CAS number	Notes
and boiling in the range of approximately 35°C to 190°C (95°F to 374°F).)				
Hydrocarbons, C ₄ -12, naphthacracking, hydrotreated; Low boiling point hydrogen treated naphtha (A complex combination of hydrocarbons obtained by distillation from the product of naphtha steam cracking process and subsequent catalytic selective hydrogenation of gum formers. It consists of hydrocarbons having carbon numbers predominantly in the range of C ₄ through C ₁₂ and boiling in the range of approximately 30°C to 230°C (86°F to 446°F).)	649-340-00-7	295-443-1	92045-61-9	P
Solvent naphtha (petroleum), hydrotreated light naphthenic; Low boiling point hydrogen treated naphtha (A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in	649-341-00-2	295-529-9	92062-15-2	P

Substances	Index number	EC number	CAS number	Notes
the presence of a catalyst. It consists predominantly of cycloparaffinic hydrocarbons having carbon numbers predominantly in the range of C ₆ through C ₇ and boiling in the range of approximately 73°C to 85°C (163°F to 185°F).)				
Naphtha (petroleum), light steam-cracked, hydrogenated; Low boiling point hydrogen treated naphtha (A complex combination of hydrocarbons produced from the separation and subsequent hydrogenation of the products of a steam-cracking process to produce ethylene. It consists predominantly of saturated and unsaturated paraffins, cyclic paraffins and cyclic aromatic hydrocarbons having carbon numbers predominantly in the range of C ₄ through C ₁₀ and boiling in the range of approximately	649-342-00-8	296-942-7	93165-55-0	P

Substances	Index number	EC number	CAS number	Notes
50°C to 200°C (122°F to 392°F). The proportion of benzene hydrocarbons may vary up to 30 wt. % and the stream may also contain small amounts of sulphur and oxygenated compounds.)				
Hydrocarbons, C ₆ —11, hydrotreated, dearomatized; Low boiling point hydrogen treated naphtha (A complex combination of hydrocarbons obtained as solvents which have been subjected to hydro treatment in order to convert aromatics to naphthenes by catalytic hydrogenation.)	649-343-00-3	297-852-0	93763-33-8	P
Hydrocarbons, C ₉ _{—12} , hydrotreated, dearomatized, Low boiling point hydrogen treated naphtha (A complex combination of hydrocarbons obtained as solvents which have been subjected to hydrotreatment in order to convert aromatics to naphthenes	649-344-00-9	297-853-6	93763-34-9	P

Substances	Index number	EC number	CAS number	Notes
by catalytic hydrogenation.)				
Stoddard solvent; Low boiling point naphtha—unspecified (A colourless, refined petroleum distillate that is free from rancid or objectionable odours and that boils in a range of approximately 300°F to 400°F.)	649-345-00-4	232-489-3	8052-41-3	P
Natural gas condensates (petroleum); Low boiling point naphtha —unspecified (A complex combination of hydrocarbons separated as a liquid from natural gas in a surface separator by retrograde condensation. It consists mainly of hydrocarbons having carbon numbers predominantly in the range of C ₂ to C ₂₀ . It is a liquid at atmospheric temperature and pressure.)	649-346-00-X	265-047-3	64741-47-5	P
Natural gas (petroleum), raw liq. mix; Low boiling point naphtha —unspecified (A complex combination of hydrocarbons separated	649-347-00-5	265-048-9	64741-48-6	P

Substances	Index number	EC number	CAS number	Notes
as a liquid from natural gas in a gas recycling plant by processes such as refrigeration or absorption. It consists mainly of saturated aliphatic hydrocarbons having carbon numbers in the range of C ₂ through C ₈ .)				
Naphtha (petroleum), light hydrocracked; Low boiling point naphtha —unspecified (A complex combination of hydrocarbons from distillation of the products from a hydrocracking process. It consists predominantly of saturated hydrocarbons having carbon numbers predominantly in the range of C ₄ through C ₁₀ and boiling in the range of approximately — 20°C to 180°C (—4°F to 356°F).)	649-348-00-0	265-071-4	64741-69-1	P
Naphtha (petroleum) heavy hydrocracked; Low boiling point naphtha —unspecified	649-349-00-6	265-079-8	64741-78-2	P

Substances	Index number	EC number	CAS number	Notes
(A complex combination of hydrocarbons from distillation of the products from a hydrocracking process. It consists predominantly of saturated hydrocarbons having carbon numbers predominantly in the range of C ₆ through C ₁₂ , and boiling in the range of approximately 65°C to 230°C (148°F to 446°F).)				
Naphtha (petroleum), sweetened; Low boiling point naphtha —unspecified (A complex combination of hydrocarbons obtained by subjecting a petroleum naphtha to a sweetening process to convert mercaptans or to remove acidic impurities. It consists of hydrocarbons having carbon numbers predominantly in the range of C ₄ through C ₁₂ and boiling in the range of approximately —	649-350-00-1	265-089-2	64741-87-3	P

Substances	Index number	EC number	CAS number	Notes
10°C to 230°C (14°F to 446°F).)	muex number	EC Humber	CAS HUMBER	notes
Naphtha (petroleum), acid-treated; Low boiling point naphtha —unspecified (A complex combination of hydrocarbons obtained as a raffinate from a sulphuric acid treating process. It consists of hydrocarbons having carbon numbers predominantly in the range of C ₇ through C ₁₂ and boiling in the range of approximately 90°C to 230°C (194°F to 446°F).)	649-351-00-7	265-115-2	64742-15-0	P
Naphtha (petroleum), chemically neutralized heavy; Low boiling point naphtha—unspecified (A complex combination of hydrocarbons produced by a treating process to remove acidic materials. It consists of hydrocarbons having carbon numbers predominantly in the range of C ₆ through C ₁₂ and boiling in	649-352-00-2	265-122-0	64742-22-9	P

Substances	Index number	EC number	CAS number	Notes
the range of approximately 65°C to 230°C (149°F to 446°F).)				
Naphtha (petroleum) chemically neutralized light; Low boiling point naphtha —unspecified (A complex combination of hydrocarbons produced by a treating process to remove acidic materials. It consists of hydrocarbons having carbon numbers predominantly in the range of C ₄ through C ₁₁ and boiling in the range of approximately — 20°C to 190°C (—4°F to 374°F).)	649-353-00-8	265-123-6	64742-23-0	P
Naphtha (petroleum), catalytic dewaxed; Low boiling point naphtha unspecified (A complex combination of hydrocarbons obtained from the catalytic de waxing of a petroleum fraction. It consists predominantly of hydrocarbons having carbon	649-354-00-3	265-170-2	64742-66-1	P
		228		

Substances	Index number	EC number	CAS number	Notes
numbers predominantly in the range of C ₅ through C ₁₂ and boiling in the range of approximately 35°C to 230°C (95°F to 446°F).)				
Naphtha (petroleum), light steam-cracked; Low boiling point naphtha —unspecified (A complex combination of hydrocarbons obtained by the distillation of the products from a steam cracking process. It consists predominantly of unsaturated hydrocarbons having carbon numbers predominantly in the range of C ₄ through C ₁₁ and boiling in the range of approximately — 20°C to 190°C (—4°F to 374°F). This stream is likely to contain 10 vol. % or more benzene.)	649-355-00-9	265-187-5	64742-83-2	P
Solvent naphtha (petroleum), light arom.; Low boiling point naphtha —unspecified (A complex combination of hydrocarbons obtained from	649-356-00-4	265-199-0	64742-95-6	P
		229		

Substances	Index number	EC number	CAS number	Notes
distillation of aromatic streams. It consists predominantly of aromatic hydrocarbons having carbon numbers predominantly in the range of C ₈ through C ₁₀ and boiling in the range of approximately 135°C to 210°C (275°F to 410°F).)				
Aromatic hydrocarbons, C ₆ — ₁₀ , acid-treated, neutralized; Low boiling point naphtha unspecified	649-357-00-X	268-618-5	68131-49-7	P
Distillates (petroleum), C ₃ _5, 2-methyl-2- butene-rich; Low boiling point naphtha —unspecified (A complex combination of hydrocarbons from the distillation of hydrocarbons usually ranging in carbon numbers from C ₃ through C ₅ , predominantly isopentane and 3- methyl-1-butene. It consists of saturated and unsaturated hydrocarbons having carbon numbers in	649-358-00-5	270-725-7	68477-34-9	P

Substances	Index number	EC number	CAS number	Notes
the range of C ₃ through C ₅ , predominantly 2-methyl-2-butene.)	Andex number	EC number	CAS number	110113
Distillates (petroleum), polymd. steam-cracked petroleum distillates, C ₅ — ₁₂ fraction; Low boiling point naphtha —unspecified (A complex combination of hydrocarbons obtained from the distillation of polymerized steam-cracked petroleum distillate. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C ₅ through C ₁₂ .)	649-359-00-0	270-735-1	68477-50-9	P
Distillates (petroleum), steam-cracked, C _{5—12} fraction; Low boiling point naphtha —unspecified (A complex combination of organic compounds obtained by the distillation of products from a steam cracking process. It consists of unsaturated hydrocarbons	649-360-00-6	270-736-7	68477-53-2	P

Substances	Index number	EC number	CAS number	Notes
having carbon numbers predominantly in the range of C ₅ through C ₁₂ .)				
Distillates (petroleum), steam-cracked, C_{5-10} fraction, mixed with light steam-cracked petroleum naphtha C_5 fraction; Low boiling point naphtha—unspecified	649-361-00-1	270-738-8	68477-55-4	P
Extracts (petroleum), cold-acid, C ₄ — 6; Low boiling point naphtha —unspecified (A complex combination of organic compounds produced by cold acid unit extraction of saturated and unsaturated aliphatic hydrocarbons usually ranging in carbon numbers from C ₃ through C ₆ , predominantly pentanes and amylenes. It consists predominantly of saturated and unsaturated hydrocarbons having carbon numbers in the range of C ₄ through C ₆ ,	649-362-00-7	270-741-4	68477-61-2	P

Substances	Index number	EC number	CAS number	Notes
predominantly C ₅ .)				
Distillates (petroleum), depentanizer overheads; Low boiling point naphtha —unspecified (A complex combination of hydrocarbons obtained from a catalytic cracked gas stream. It consists of aliphatic hydrocarbons having carbon numbers predominantly in the range of C ₄ through C ₆ .)	649-363-00-2	270-771-8	68477-894-4	P
Residues (petroleum), butane splitter bottoms; Low boiling point naphtha— unspecified (A complex residuum from the distillation of butane stream. It consists of aliphatic hydrocarbons having carbon numbers predominantly in the range of C ₄ through C ₆ .)	649-364-00-8	270-791-7	68478-12-6	P
Residual oils (petroleum), deisobutanizer tower; Low boiling point naphtha— unspecified (A complex	649-365-00-3	270-795-9	68478-16-0	P

Substances	Index number	EC number	CAS number	Notes
residuum from the atmospheric distillation of the butane-butylene stream. It consists of aliphatic hydrocarbons having carbon numbers predominantly in the range of C ₄ through C ₆ .)				
Naphtha (petroleum), full-range coker; Low boiling point naphtha —unspecified (A complex combination of hydrocarbons produced by the distillation of products from a fluid coker. It consists predominantly of unsaturated hydrocarbons having carbon numbers predominantly in the range of C ₄ through C ₁₅ and boiling in the range of approximately 43°C to 250°C (110°F to 500°F).)	649-366-00-9	270-991-4	68513-02-0	P
Naphtha (petroleum), steam-cracked middle arom.; Low boiling point naphtha —unspecified (A complex combination of hydrocarbons	649-367-00-4	271-138-9	68516-20-1	P

Substances	Index number	EC number	CAS number	Notes
produced by the distillation of products from a steam-cracking process. It consists predominantly of aromatic hydrocarbons having carbon numbers predominantly in the range of C ₇ through C ₁₂ and boiling in the range of approximately 130°C to 220°C (226°F to 428°F).)				
Naphtha (petroleum), clay-treated full-range straight-run; Low boiling point naphtha —unspecified (A complex combination of hydrocarbons resulting from treatment of full-range straight-run, naphtha with natural or modified clay, usually in a percolation process to remove the trace amounts of polar compounds and impurities present. It consists of hydrocarbons having carbon numbers predominantly in the range of C4 through C11	649-368-00-X	271-262-3	68527-21-9	P

Substances	Index number	EC number	CAS number	Notes
and boiling in the range of approximately — 20°C to 220°C (—4°F to 429°F).)				
Naphtha (petroleum), clay-treated light straight-run; Low boiling point naphtha —unspecified (A complex combination of hydrocarbons resulting from treatment of light straight-run naphtha with a natural or modified clay, usually in a percolation process to remove the trace amounts of polar compounds and impurities, present. It consists of hydrocarbons having carbon numbers predominantly in the range of C ₇ through C ₁₀ and boiling in the range of approximately 93°C to 180°C (200°F to 356°F).)	649-369-00-5	271-263-9	68527-22-0	P
Naphtha (petroleum), light steam- cracked arom.; Low boiling point naphtha —unspecified (A complex combination of	649-370-00-0	271-264-4	68527-23-1	P
Comomation of		226		

Substances	Index number	EC number	CAS number	Notes
hydrocarbons produced by distillation of products from a steam-cracking process. It consists predominantly of aromatic hydrocarbons having carbon numbers predominantly in the range of C ₇ through C ₉ , and boiling in the range of approximately 110°C to 165°C (230°F to 329°F).)				
Naphtha (petroleum), light steam-cracked, debenzenized; Low boiling point naphtha —unspecified (A complex combination of hydrocarbons produced by distillation of products from a steam-cracking process. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C ₄ through C ₁₂ and boiling in the range of approximately 80°C to 218°C (176°F to 424°F).)	649-371-00-6	271-266-5	68527-26-4	P

Substances	Index number	EC number	CAS number	Notes
Naphtha (petroleum), aromcontg.; Low boiling point naphtha—unspecified	649-372-00-1	271-635-0	68603-08-7	P
Gasoline, pyrolysis, debutanizer bottoms; low boiling point naphtha— unspecified (A complex combination of hydrocarbons obtained from the fractionation of depropanizer bottoms. It consists of hydrocarbons having carbon numbers predominantly greater than C ₅ .)	649-373-00-7	271-726-5	68606-10-0	P
Naphtha (petroleum), light, sweetened; Low boiling point naphtha —unspecified (A complex combination of hydrocarbons obtained by subjecting a petroleum distillate to a sweetening process to convert mercaptans or to remove acidic impurities. It consists predominantly of saturated and unsaturated hydrocarbons having carbon	649-374-00-2	272-206-0	68783-66-4	P

Substances	Index number	EC number	CAS number	Notes
numbers predominantly in the range of C ₃ through C ₆ and boiling in the range of approximately — 20°C to 100°C (—4°F to 212°F).)				
Natural gas condensates; Low boiling point naphtha —unspecified (A complex combination of hydrocarbons separated and/or condensed from natural gas during transportation and collected at the wellhead and/or from the production, gathering, transmission, and distribution pipelines in deeps, scrubbers, etc. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C ₂ through C ₈ .)	649-375-00-8	272-896-3	68919-39-1	J
Distillates (petroleum), naphtha unifiner stripper; Low boiling point naphtha—unspecified (A complex combination of hydrocarbons produced by	649-376-00-3	272-932-8	68921-09-5	P

Substances	Index number	EC number	CAS number	Notes
stripping the products from the naphtha unifiner. It consists of saturated aliphatic hydrocarbons having carbon numbers predominantly in the range of C ₂ through C ₆ .)				
Naphtha (petroleum), catalytic reformed light, aromfree fraction; Low boiling point naphtha—unspecified (A complex combination of hydrocarbons remaining after removal of aromatic compounds from catalytic reformed light naphtha in a selective absorption process. It consists predominantly of paraffinic and cyclic compounds having carbon numbers predominantly in the range of C ₅ to C ₈ and boiling in the range of approximately 66°C to 121°C (151°F to 250°F).)	649-377-00-9	285-510-3	85116-59-2	P
Gasoline; Low boiling point naphtha— unspecified (A complex	649-378-00-4	289-220-8	86290-81-5	P

Substances	Index number	EC number	CAS number	Notes
combination of hydrocarbons consisting primarily of paraffins, cycloparaffins, aromatic and olefinic hydrocarbons having carbon numbers predominantly greater than C ₃ and boiling in the range of 30°C to 260°C (86°F to 500°F).)				
Aromatic hydrocarbons, C ₇ —8, dealkylation products, distn. residues; Low boiling point naphtha— unspecified	649-379-00-X	292-698-0	90989-42-7	P
Hydrocarbons, C ₄ —6, depentanizer lights, arom. hydrotreater; Low boiling point naphtha —unspecified (A complex combination of hydrocarbons obtained as first runnings from the depentanizer column before hydrotreatment of the aromatic charges. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C ₄ through C ₆ ,	649-380-00-5	295-298-4	91995-38-9	P

Substances	Index number	EC number	CAS number	Notes
predominantly pentanes and pentenes, and boiling in the range of approximately 25°C to 40°C (77°F to 104°F).)				
Distillates (petroleum), heat-soaked steam-cracked naphtha, C ₅ rich; Low boiling point naphtha—unspecified (A complex combination of hydrocarbons obtained by distillation of heat-soaked steam-cracked naphtha. It consists predominantly of hydrocarbons having carbon numbers in the range of C ₄ through C ₆ , predominantly C ₅ .	649-381-00-0	295-302-4	91995-41-4	P
Extracts (petroleum), catalytic reformed light naphtha solvent; low boiling point naphtha— unspecified (A complex combination of hydrocarbons obtained as the extract from the solvent extraction of a catalytically reformed petroleum	649-382-00-6	295-331-2	91995-68-5	P

Substances	Index number	EC number	CAS number	Notes
cut. It consists predominantly of aromatic hydrocarbons having carbon numbers predominantly in the range of C ₇ through C ₈ and boiling in the range of approximately 100°C to 200°C (212°F to 392°F).)				
Naphtha (petroleum), hydrodesulphurized light, dearomatized; low boiling point naphtha—unspecified (A complex combination of hydrocarbons obtained by distillation of hydrodesulphurized and dearomatized light petroleum fractions. It consists predominantly of C ₇ paraffins and cycloparaffins boiling in a range of approximately 90°C to 100°C (194°F to 212°F).)	d	295-434-2	92045-53-9	P
Naphtha (petroleum), light, C ₅ -rich, sweetened; low boiling point naphtha —unspecified (A complex combination of	649-384-00-7	295-442-6	92045-60-8	P

Substances	Index number	EC number	CAS number	Notes
hydrocarbons				
obtained by				
subjecting a petroleum				
naphtha to a				
sweetening				
process to convert				
mercaptans				
or to remove				
acidic impurities.				
It consists of				
hydrocarbons				
having carbon				
numbers predominantly				
in the range of				
C_4 through C_5 ,				
predominantly				
C ₅ , and boiling				
in the range of				
approximately —				
10°C to 35°C				
(14°F to 95°F).)				
Hydrocarbons,	649-385-00-2	295-444-7	92045-62-0	P
C_{8-11} ;, naphtha-				
cracking, toluene				
cut; low boiling point naphtha				
—unspecified				
(A complex				
combination of				
hydrocarbons				
obtained by				
distillation from				
prehydrogenated				
cracked naphtha. It consists				
predominantly				
of hydrocarbons				
having carbon				
numbers				
predominantly				
in the range of				
C_8 through C_{11}				
and boiling in				
the range of approximately				
130°C to 205°C				
(266°F to				
401°F).)				

Substances	Index number	EC number	CAS number	Notes
Hydrocarbons, C _{4—11} , naphthacracking; arom-free; low boiling point naphtha—unspecified (A complex combination of hydrocarbons obtained from prehydrogenated cracked naphtha after distillative separation of benzeneand toluenecontaining hydrocarbon cuts and a higher boiling fraction. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C ₄ through C ₁₁ and boiling in the range of approximately 30°C to 205°C (86°F to 401°F).)	649-386-00-8	295-445-2	92045-63-1	P
Naphtha (petroleum), light heat-soaked, steam-cracked; low boiling point naphtha —unspecified (A complex combination of hydrocarbons obtained by the fractionation of steam cracked naphtha after recovery from a heat soaking process. It consists	649-387-00-3	296-028-8	92201-97-3	P

Substances	Index number	EC number	CAS number	Notes
predominantly of hydrocarbons having carbon numbers predominantly in the range of C ₄ through C ₆ and boiling in the range of approximately 0°C to 80°C (32°F to 176°F).)				
Distillates (petroleum), C ₆ -rich low boiling point naphtha—unspecified (A complex combination of hydrocarbons obtained from the distillation of a petroleum feedstock. It consists predominantly of hydrocarbons having carbon numbers of C ₅ through C ₇ , rich in C ₆ , and boiling in the range of approximately 60°C to 70°C (140°F to 158°F).)	649-388-00-9	296-903-4	93165-19-6	P
Gasoline, pyrolysis, hydrogenated; low boiling point naphtha —unspecified (A distillation fraction from the hydrogenation of pyrolysis gasoline boiling in the range of approximately	649-389-00-4	302-639-3	94114-03-1	P

Substances	Index number	EC number	CAS number	Notes
20°C to 200°C (68°F to 392°F).)				
Distillates (petroleum), steam-cracked, C_{8-12} fraction, polymd., distn. lights; low boiling point naphtha—unspecified (A complex combination of hydrocarbons obtained by distillation of the polymerized C_8 through C_{12} fraction from steam-cracked petroleum distillates. It consists predominantly of aromatic hydrocarbons having carbon numbers predominantly in the range of C_8 through C_{12} .)	649-390-00-X	308-261-5	95009-23-7	P
Extracts (petroleum); heavy naphtha solvent, clay- treated; low boiling point naphtha— unspecified (A complex combination of hydrocarbons obtained by the treatment of heavy naphthic solvent petroleum extract with bleaching earth. It consists predominantly of hydrocarbons	649-391-00-5	308-261-5	97926-43-7	P

Substances	Index number	EC number	CAS number	Notes
having carbon numbers predominantly in the range of C ₆ through C ₁₈ , and boiling in the range of approximately 80°C to 180°C (175°F to 356°F).)				
Naphtha (petroleum), light steam-cracked, debenzenized, thermally treated; low boiling point naphtha —unspecified (A complex combination of hydrocarbons obtained by the treatment and distillation of debenzenized light steam-cracked petroleum naphtha. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C ₇ through C ₁₂ and boiling in the range of approximately 95°C to 200°C (203°F to 392°F).)	649-392-00-0	308-713-1	98219-46-6	P
Naphtha (petroleum), light steam-cracked, thermally treated; low boiling point naphtha —unspecified	649-393-00-6	308-714-7	98219-47-7	P
•		248		

Substances	Index number	EC number	CAS number	Notes
(A complex combination of hydrocarbons obtained by the treatment and distillation of light steam-cracked petroleum naphtha. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C ₅ through C ₆ and boiling in the range of approximately 35°C to 80°C (95°F to 176°F).)	640 204 00 1	200 962 5	101216 56 7	D
Distillates (petroleum), C _{7—9} , C ₈ -rich, hydrodesulphurized dearomatized; low boiling point naphtha—unspecified (A complex combination of hydrocarbons obtained by the distillation of petroleum light fraction, hydrodesulphurize and dearomatized. It consists predominantly of hydrocarbons having carbon numbers in the range of C ₇ through C ₉ , predominantly C ₈ paraffins and cycloparaffins, boiling in	d	309-862-5	101316-56-7	P

Substances	Index number	EC number	CAS number	Notes
the range of approximately 120°C to 130°C (248°F to 266°F).)				
Hydrocarbons, C ₆ —8, hydrogenated sorption-dearomatized, toluene raffination; low boiling point naphtha —unspecified (A complex combination of hydrocarbons obtained during the sorption of toluene from a hydrocarbon fraction from cracked gasoline treated with hydrogen in the presence of a catalyst. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C ₆ through C ₈ and boiling in the range of approximately 80°C to 135°C (176°F to 275°F).)		309-870-9	101316-66-9	P
Naphtha (petroleum), hydrodesulphurize full-range coker; low boiling point naphtha —unspecified (A complex combination of	649-396-00-2 d	309-879-8	101316-76-1	P

Substances	Index number	EC number	CAS number	Notes
hydrocarbons				
obtained by				
fractionation from				
hydrodesulphurize	d			
coker distillate.				
It consists				
predominantly				
of hydrocarbons				
having carbon				
numbers				
predominantly in				
the range of C_5 to				
C ₁₁ and boiling				
in the range of				
approximately				
23°C to 196°C				
(73°F to 385°F).)				
Naphtha	649-397-00-8	309-976-5	101795-01-1	P
(petroleum),				
sweetened light;				
low boiling				
point naphtha				
—unspecified				
(A complex				
combination of				
hydrocarbons				
obtained by subjecting				
a petroleum				
naphtha to a				
sweetening				
process to convert				
mercaptans				
or to remove				
acidic impurities.				
It consists				
predominantly				
of hydrocarbons				
having carbon				
numbers				
predominantly				
in the range of				
C ₅ through c8				
and boiling in the range of				
approximately				
20°C to 130°C				
(68°F to 266°F)				
	(40.200.00.2	210.012.0	100110 11 7	D.
Hydrocarbons,	649-398-00-3	310-012-0	102110-14-5	P
C_{3-6} , C_5 -rich,				

Substances	Index number	EC number	CAS number	Notes
steam-cracked naphtha; low boiling point naphtha— unspecified (A complex combination of hydrocarbons obtained by distillation of steam-cracked naphtha. It consists predominantly of hydrocarbons having carbon numbers in the range of C ₃ through C ₆ , predominantly C ₅ .)				
Hydrocarbons, C ₅ -rich, dicyclopentadiene-contg.; low boiling point naphtha— unspecified (A complex combination of hydrocarbons obtained by distillation of the products from a steam-cracking process. It consists predominantly of hydrocarbons having carbon numbers of C ₅ and dicyclopentadiene and boiling in the range of approximately 30°C to 170°C (86°F to 338°F).)	649-399-00-9	310-013-6	102110-15-6	P
Residues (petroleum),	649-400-00-2	310-057-6	102110-55-4	P

Substances	Index number	EC number	CAS number	Notes
steam-cracked				
light, arom.; low boiling				
point naphtha				
—unspecified				
(A complex				
combination of				
hydrocarbons				
obtained by the				
distillation of				
the products of				
steam cracking or				
similar processes				
after taking off				
the very light				
products resulting in a residue				
starting with				
hydrocarbons				
having carbon				
numbers				
greater than				
C ₅ . It consists				
predominantly				
of aromatic				
hydrocarbons				
having carbon				
numbers				
greater than				
C ₅ and boiling point above				
approximately				
40°C (104°F)				
				_
Hydrocarbons,	649-401-00-8	270-690-8	68476-50-6	P
C_5 , C_5 _6-rich;				
low boiling				
point naphtha— unspecified				
•				
Hydrocarbons,	649-402-00-3	270-695-5	68476-55-1	P
C_{5_6} -rich; low				
boiling point				
naphtha—				
unspecified				
Aromatic	649-403-00-9	292-695-4	90989-39-2	P
hydrocarbons,				
C _{8—10} Light Oil				
redistillate, high				
boiling				

Substances	Index number	EC number	CAS number	Notes
Distillates (petroleum), light catalytic cracked; Cracked gas oil (A complex combination of hydrocarbons produced by the distillation of products from a catalytic cracking process. It consists of hydrocarbons having carbon numbers predominantly in the range of C ₉ through C ₂₅ and boiling in the range of approximately 150°C to 400°C (302°F to 752°F). It contains a relatively large proportion of bicyclic aromatic hydrocarbons.)	649-435-00-3	265-060-4	64741-59-9	
Distillates (petroleum), intermediate catalytic cracked; Cracked gas oil (A complex combination of hydrocarbons produced by the distillation of products from a catalytic cracking process. It consists of hydrocarbons having carbon numbers predominantly in the range of C ₁₁ through C ₃₀ and boiling in the range of	649-436-00-9	265-062-5	64741-60-2	

Substances	Index number	EC number	CAS number	Notes
approximately 205°C to 450°C (401°F to 842°F). It contains a relatively large proportion of tricyclic aromatic hydrocarbons.)				110103
Distillates (petroleum), light thermal cracked; Cracked gas oil (A complex combination of hydrocarbons from the distillation of the products from a thermal cracking process. It consists predominantly of unsaturated hydrocarbons having carbon numbers predominantly in the range of C ₁₀ through C ₂₂ and boiling in the range of approximately 160°C to 370°C (320°F to 698°F).)	649-438-00-X	265-084-5	64741-82-8	
Distillates (petroleum), hydrodesulphurize light catalytic cracked; Cracked gas oil (A complex combination of hydrocarbons obtained by treating light catalytic cracked distillates with hydrogen to convert organic sulphur	649-439-00-5 ed	269-781-5	68333-25-5	

Substances	Index number	EC number	CAS number	Notes
to hydrogen sulphide which is removed. It consists of hydrocarbons having carbon numbers predominantly in the range of C ₉ through C ₂₅ and boiling in the range of approximately 150°C to 400°C (302°F to 752°F). It contains a relatively large proportion of bicyclic aromatic hydrocarbons.)				
Distillates (petroleum), light steam-cracked naphtha; Cracked gas oil (A complex combination of hydrocarbons from the multiple distillation of products from a steam cracking process. It consists of hydrocarbons having carbon numbers predominantly in the range of C ₁₀ through C ₁₈ .)	649-440-00-0	270-662-5	68475-80-9	
Distillates (petroleum), cracked steam-cracked petroleum distillates; Cracked gas oil (A complex combination of hydrocarbons	649-441-00-6	270-727-8	68477-38-3	

Substances	Index number	EC number	CAS number	Notes
produced by distilling cracked steam cracked distillate and/or its fractionation products. It consists of hydrocarbons having carbon numbers predominantly in the range of C ₁₀ to low molecular weight polymers.)				
Gas oils (petroleum), steam-cracked; Cracked gas oil (A complex combination of hydrocarbons produced by distillation of the products from a steam cracking process. It consists of hydrocarbons having carbon numbers predominantly greater than C ₉ and boiling in the range of from approximately 205°C to 400°C (400°F to 752°F).)	649-442-00-1	271-260-2	68527-18-4	
Distillates (petroleum), hydrodesulphurize thermal cracked middle; Cracked gas oil (A complex combination of hydrocarbons obtained by fractionation from hydrodesulphurize thermal cracker		285-505-6	85116-53-6	

Substances	Index number	EC number	CAS number	Notes
distillate stocks. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C ₁₁ to C ₂₅ and boiling in the range of from approximately 205°C to 400°C (401°F to 752°F).)				
Gas oils (petroleum), thermal-cracked, hydrodesulphurize Cracked gas oil	649-444-00-2 d;	295-411-7	92045-29-9	
Residues (petroleum), hydrogenated steam-cracked naphtha; Cracked gas oil (A complex combination of hydrocarbons obtained as a residual fraction from the distillation of hydrotreated steam-cracked naphtha. It consists predominantly of hydrocarbons boiling in the range of approximately 200°C to 350°C (32°F to 662°F).)	649-445-00-8	295-514-7	92062-00-5	
Residues (petroleum), steam-cracked naphtha distn.; Cracked gas oil (A complex	649-446-00-3	295-517-3	92062-04-9	

Substances	Index number	EC number	CAS number	Notes
combination of hydrocarbons obtained as a column bottom from the separation of effluents from steam cracking naphtha at a high temperature. It boils in the range of approximately 147°C to 300°C (297°F to 572°F) and produces a finished oil having a viscosity of 18 cSt at 50°C.)				
Distillates (petroleum), light catalytic cracked, thermally degraded; Cracked gas oil (A complex combination of hydrocarbons produced by the distillation of products from a catalytic cracking process which has been used as a heat transfer fluid. It consists predominantly of hydrocarbons boiling in the range of approximately 190°C to 340°C (374°F to 644°F). This steam is likely to contain organic sulphur compounds.) Residues	649-448-00-4	297-905-8	92201-60-0	
(petroleum), steam-cracked, heat-soaked				
		250		

Substances	Index number	EC number	CAS number	Notes
naphtha; Cracked gas oil (A complex combination of hydrocarbons obtained as residue from the distillation of steam-cracked heat-soaked naphtha and boiling in the range of approximately 150°C to 350°C (302°F to 662°F).)				
Gas oils (petroleum), light vacuum, thermal-cracked, hydrodesulphurized Cracked gas oil (A complex combination of hydrocarbons obtained by catalytic dehydrosulphurized of thermal-cracked light vacuum petroleum. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C ₁₄ through C ₂₀ and boiling in the range of approximately 270°C to 370°C (518°F to 698°F).)	ation	308-278-8	97926-59-5	
Distillates (petroleum), hydrodesulphurize middle coker;	649-451-00-0 ed	309-865-1	101316-59-0	
madic coker,		260		

Substances	Index number	EC number	CAS number	Notes
Cracked gas				
oil (A complex				
combination of				
hydrocarbons by				
fractionation from				
hydrodesulphurize	d			
coker distillate				
stocks. It consists				
of hydrocarbons				
having carbon numbers				
predominantly in				
the range of C_{12}				
to C_{21} and boiling				
in the range of				
approximately				
200°C to 360°C				
(392°F to				
680°F).)				
	(40, 450, 00, 6	200.020.2	101601 11 5	
Distillates	649-452-00-6	309-939-3	101631-14-5	
(petroleum),				
heavy steam-				
cracked; Cracked gas				
oil (A complex				
combination of				
hydrocarbons				
obtained by				
distillation of				
steam cracking				
heavy residues.				
It consists				
predominantly of				
highly alkylated				
heavy aromatic				
hydrocarbons				
boiling in				
the range of				
approximately				
250°C to 400°C				
(482°F to 752°F).)				
Distillates	649-453-00-1	265-077-7	64741-76-0	L
(petroleum),				
heavy				
hydrocracked;				
Base oil—				
unspecified				
(A complex combination of				
hydrocarbons				
nyurocarbons		261		

Substances	Index number	EC number	CAS number	Notes
from the distillation of the products from a hydro cracking process. It consists predominantly of saturated hydrocarbons having carbon numbers in the range of C ₁₅ to C ₃₉ and boiling in the range of approximately 260°C to 600°C (500°F to 1112°F).)				
Distillates (petroleum), solvent-refined heavy paraffinic; Base oil—unspecified (A complex combination of hydrocarbons obtained as the raffinate from a solvent extraction process. It consists predominantly of saturated hydrocarbons having carbon numbers predominantly in the range of C ₂₀ through C ₅₀ and produces a finished oil with a viscosity of at least 100 SUS at 100°F (19 cSt at 40°C).)	649-454-00-7	265-090-8	64741-88-4	L
Distillates (petroleum), solvent-refined light parafinnic;	649-455-00-2	265-091-3	64741-89-5	L

Substances	Index number	EC number	CAS number	Notes
Base oil—				
unspecified				
(A complex				
combination of				
hydrocarbons				
obtained as the				
raffinate from a				
solvent extraction				
process.				
It consists				
predominantly				
of saturated				
hydrocarbons				
having carbon				
numbers				
predominantly				
in the range of				
C ₁₅ through C ₃₀				
and produces				
a finished oil				
having a viscosity				
of less than 100				
SUS at 100°F (19				
cSt at 40°C).)				
Residual oils	649-456-00-8	265-096-0	64741-95-3	L
(petroleum),				
solvent				
deasphalted; Base				
oil—unspecified				
(A complex				
combination of				
hydrocarbons				
obtained as the				
solvent soluble				
fraction from				
C ₃ –C ₄ solvent				
de asphalting				
of a residuum.				
It consists of				
hydrocarbons				
having carbon				
numbers				
predominantly				
higher than C ₂₅				
and boiling above				
approximately				
400°C (752°F).)				
Distillates	649-457-00-3	265-097-6	64741-96-4	L
(petroleum),				
solvent-refined				

Substances	Index number	EC number	CAS number	Notes
heavy naphthenic;				
Base oil—				
unspecified				
(A complex				
combination of				
hydrocarbons				
obtained as the				
raffinate from a				
solvent extraction				
process. It				
consists of				
hydrocarbons				
having carbon				
numbers				
predominantly				
in the range of				
C_{20} through C_{50} and produces a				
finished oil with				
a viscosity of at				
least 100 SUS at				
100°F (19 cSt at				
40°C.) It contains				
relatively few				
normal paraffins.)				
-	640, 450, 00, 0	265,000,1	(4541 05 5	T
Distillates	649-458-00-9	265-098-1	64741-97-5	L
(petroleum), solvent-refined				
light naphthenic;				
Base oil—				
unspecified				
(A complex				
combination of				
hydrocarbons				
obtained as the				
raffinate from a				
solvent extraction				
process. It				
consists of				
hydrocarbons				
having carbon				
numbers				
predominantly				
in the range of				
C_{15} through C_{30}				
and produces a				
finished oil with				
a viscosity of less				
than 100 SUS at				
100°F (19 cSt at				
40°C). It contains				

Substances	Index number	EC number	CAS number	Notes
relatively few normal paraffins.)				
Residual oils (petroleum), solvent-refined; Base oil— unspecified (A complex combination of hydrocarbons obtained as the solvent insoluble fraction from solvent refining of a residuum using a polar organic solvent such a phenol or furfural. It consists of hydrocarbons having carbon numbers predominantly greater than C ₂₅ and boiling above approximately 400°C (752°F).)	649-459-00-4	265-101-6	64742-01-4	L
Distillates (petroleum) clay-treated paraffinic; Base oil—unspecified (A complex combination of hydrocarbons resulting from treatment of a petroleum fraction with natural or modified clay in either a contacting or percolation process to remove the trace amounts of polar compounds and impurities present. It	649-460-00-X	265-137-2	64742-36-5	L

Substances	Index number	EC number	CAS number	Notes
consists of				
hydrocarbons				
having carbon				
numbers				
predominantly				
in the range of				
C_{20} through C_{50}				
and produces a				
finished oil with				
a viscosity of at				
least 100 SUS at				
100°F (19 cSt at				
40°C). It contains				
a relatively large proportion				
of saturated				
hydrocarbons.)				
-				
Distillates	649-461-00-5	265-138-8	64742-37-6	L
(petroleum),				
clay-treated light				
paraffinic; Base				
oil—unspecified				
(A complex				
combination of				
hydrocarbons				
resulting from treatment of				
a petroleum				
fraction with				
natural or				
modified clay				
in either a				
contacting or				
percolation				
process to				
remove the trace				
amounts of polar				
compounds				
and impurities				
present. It				
consists of				
hydrocarbons				
having carbon				
numbers predominantly				
in the range of				
C_{15} through C_{30}				
and produces a				
finished oil with				
a viscosity of less				
than 100 SUS at				
·= - ·= · **				

100°F (19 cSt at		EC number		
40°C). It contains a relatively large proportion of saturated hydrocarbons.)				
Residual oils (petroleum), clay-treated; Base oil—unspecified (A complex combination of hydrocarbons obtained by the treatment of a residual oil with a natural or modified clay in either a contacting or percolation process to remove the trace amounts of polar compounds and impurities present. It consists of hydrocarbons having carbon numbers predominantly greater than C ₂₅ and boiling above approximately 400°C (752°F).)		265-143-5	64742-41-2	L
Distillates (petroleum), clay-treated heavy naphthenic; Base oil—unspecified (A complex combination of hydrocarbons resulting from treatment of a petroleum fraction with a natural or modified clay in either a	649-463-00-6	265-146-1	64742-44-5	L

Substances	Index number	EC number	CAS number	Notes
contacting or				
percolation				
process to				
remove the trace				
amounts of polar				
compounds				
and impurities				
present. It				
consists of				
hydrocarbons				
having carbon				
numbers				
predominantly				
in the range of				
C_{20} through C_{50}				
and produces a				
finished oil with				
a viscosity of at				
least 100 SUS at				
100°F (19 cSt at				
40°C). It contains				
relatively few				
normal paraffins.)				
Distillates	649-464-00-1	265-147-7	64742-45-6	L
(petroleum),	049-404-00-1	203-147-7	04/42-43-0	L
clay-treated light				
naphthenic; Base				
oil—unspecified				
(A complex				
combination of				
hydrocarbons				
resulting from				
treatment of				
a petroleum				
fraction with				
natural or				
modified clay				
in either a				
contacting or				
percolation				
process to				
remove the trace				
amounts of polar				
compounds				
and impurities				
present. It				
consists of				
hydrocarbons				
having carbon				
numbers				
predominantly				

Substances	Index number	EC number	CAS number	Notes
in the range of C_{15} through C_{30} and produces a finished oil with a viscosity of less than 100 SUS at 100°F (19 cSt at 40°C). It contains relatively few normal paraffins.)				
Distillates (petroleum), hydrotreated heavy naphthenic; Base oil—unspecified (A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C ₂₀ through C ₅₀ and produces a finished oil with a viscosity of at least 100 SUS at 100°F (19 cSt at 40°C). It contains relatively few normal paraffins.)	649-465-00-7	265-155-0	64742-52-5	L
Distillates (petroleum), hydrotreated light naphthenic; Base oil—unspecified (A complex combination of hydrocarbons obtained by treating a	649-466-00-2	265-156-6	64742-53-6	L
~		269		

Substances	Index number	EC number	CAS number	Notes
petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C ₁₅ through C ₃₀ and produces a finished oil with a viscosity of less than 100 SUS at 100°F (19 cSt at 40°C). It contains relatively few normal paraffins.)				
Distillates (petroleum), hydrotreated heavy paraffinic; Base oil—unspecified (A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C ₂₀ through C ₅₀ and produces a finished oil of at least 100 SUS at 100°F (19 cSt at 40°C). It contains a relatively large proportion	649-467-00-8	265-157-1	64742-54-7	L

Substances	Index number	EC number	CAS number	Notes
of saturated hydrocarbons.)	inuex number	EC number	CAS number	INOTES
Distillates (petroleum), hydrotreated light paraffinic; Base oil—unspecified (A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C ₁₅ through C ₃₀ and produces a finished oil with a viscosity of less than 100 SUS at 100°F (19 cSt at 40°C). It contains a relatively large proportion of saturated hydrocarbons.)	649-468-00-3	265-158-7	64742-55-8	L
Distillates (petroleum), solvent-dewaxed light paraffinic; Base oil—unspecified (A complex combination of hydrocarbons obtained by removal of normal paraffins from a petroleum fraction by solvent crystallization. It consists	649-469-00-9	265-159-2	64742-56-9	L

Substances	Index number	EC number	CAS number	Notes
predominantly of hydrocarbons having carbon numbers predominantly in the range of C ₁₅ through C ₃₀ and produces a finished oil with a viscosity of less than 100 SUS at 100°F (19 cSt at 40°C).)				
Residual oils (petroleum), hydrotreated; Base oil—unspecified (A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly greater than C ₂₅ and boiling above approximately 400°C (752°F).)	649-470-00-4	265-160-8	64742-57-0	L
Residual oils (petroleum), solvent-dewaxed; Base oil— unspecified (A complex combination of hydrocarbons obtained by removal of long, branched chain hydrocarbons from a residual oil by solvent	649-471-00-X	265-166-0	64742-62-7	L

Substances	Index number	EC number	CAS number	Notes
crystallization. It consists of hydrocarbons having carbon numbers predominantly greater than C ₂₅ and boiling above approximately 400°C (752°F).)				
Distillates (petroleum), solvent-dewaxed heavy naphthenic; Base oil—specified (A complex combination of hydrocarbons obtained by removal of normal paraffins from a petroleum fraction by solvent crystallization. It consists of hydrocarbons having carbon numbers predominantly in the range of C ₂₀ through C ₅₀ and produces a finished oil of not less than 100 SUS at 100°F (19 cSt at 40°C). It contains relatively few normal paraffins.)	649-472-00-5	265-167-6	64742-63-8	L
Distillates (petroleum), solvent-dewaxed light naphthenic; Base oil— unspecified (A complex combination of hydrocarbons obtained by	649-473-00-0	265-168-1	64742-64-9	L
		273		

Substances	Index number	EC number	CAS number	Notes
removal of normal paraffins from a petroleum fraction by solvent crystallization. It consists of hydrocarbons having carbon numbers predominantly in the range of C ₁₅ through C ₃₀ and produces a finished oil with a viscosity of less than 100 SUS at 100°F (19 cSt at 40°C). It contains relatively few normal paraffins.)				
Distillates (petroleum), solvent-dewaxed heavy paraffinic; Base oil—unspecified (A complex combination of hydrocarbons obtained by removal of normal paraffins from a petroleum fraction by solvent crystallization. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C ₂₀ through C ₅₀ and produces a finished oil with a viscosity of not less than 100 SUS at 100°F (19 cST at 40°C).)	649-474-00-6	265-169-7	64742-65-0	L

Substances	Index number	EC number	CAS number	Notes
Naphthenic oils (petroleum), catalytic dewaxed heavy; Base oil unspecified (A complex combination of hydrocarbons obtained from a catalytic dewaxing process. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C ₂₀ through C ₅₀ and produces a finished oil with a viscosity of at least 100 SUS at 100°F (19 cSt at 40°C). It contains relatively few normal paraffins.)	649-475-00-1	265-172-3	64742-68-3	L
Naphthenic oils (petroleum), catalytic dewaxed light; Base oil unspecified (A complex combination of hydrocarbons obtained from a catalytic dewaxing process. It consists of hydrocarbons having carbon numbers predominantly in the range of C ₁₅ through C ₃₀ and produces a finished oil with a viscosity of less than 100 SUS at	649-476-00-7	265-173-9	64742-69-4	L

				Notes
100°F (19 cSt at 40°C). It contains relatively few normal paraffins.)				
Paraffin oils (petroleum), catalytic dewaxed heavy; Base oil—unspecified (A complex combination of hydrocarbons obtained from a catalytic dewaxing process. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C ₂₀ through C ₅₀ and produces a finished oil with a viscosity of at least 100 SUS at 100°F (19 cSt at 40°C).)	649-477-00-2	265-174-4	64742-70-7	L
Paraffin oils (petroleum), catalytic dewaxed light; Base oil —unspecified (A complex combination of hydrocarbons obtained from a catalytic dewaxing process. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C ₁₅ through C ₃₀ and produces a	649-478-00-8	265-176-5	64742-71-8	L

Substances	Index number	EC number	CAS number	Notes
finished oil with a viscosity of less than 100 SUS at 100°F (19 cSt at 40°C).)	Andra numbel	EC number	CAS number	TIVILS
Naphthenic oils (petroleum), complex dewaxed heavy; Base oil unspecified (A complex combination of hydrocarbons obtained by removing straight chain paraffin hydrocarbons as a solid by treatment with an agent such as urea. It consists of hydrocarbons having carbon numbers predominantly in the range of C ₂₀ through C ₅₀ and produces a finished oil with a viscosity of at least 100 SUS at 100°F (19 cSt at 40°C). It contains relatively few normal paraffins.)	649-479-00-3	265-179-1	64742-75-2	L
Naphthenic oils (petroleum), complex dewaxed light; Base oil unspecified (A complex combination of hydrocarbons obtained from a catalytic dewaxing process. It consists of hydrocarbons having carbon numbers	649-480-00-9	265-180-7	64742-76-3	L
		277		

Substances	Index number	EC number	CAS number	Notes
predominantly				
in the range of				
C_{15} through C_{30}				
and produces				
a finished oil				
having a viscosity				
less than 100				
SUS at 100°F				
(19 cSt at 40°C).				
It contains				
relatively few				
normal paraffins.)				
Lubricating oils	649-481-00-4	276-736-3	72623-85-9	L
(petroleum), C_{20}				
50, hydrotreated				
neutral oil-				
based high-				
viscosity; Base				
oil unspecified				
(A complex combination of				
hydrocarbons				
obtained by				
treating light				
vacuum gas				
oil; heavy				
vacuum gas				
oil, and solvent				
deasphalted				
residual oil with				
hydrogen in the				
presence of a				
catalyst in a two				
stage process				
with dewaxing being carried out				
between the two				
stages. It consists				
predominantly				
of hydrocarbons				
having carbon				
numbers				
predominantly				
in the range of				
C_{20} through C_{50}				
and produces				
a finished oil				
having a viscosity				
of approximately				
112 cSt at 40°C. It contains a				
n comains a				

Substances	Index number	EC number	CAS number	Notes
relatively large proportion of saturated hydrocarbons.)				
Lubricating oils (petroleum), C ₁₅ –30, hydrotreated neutral oilbased; Base oil—unspecified (A complex combination of hydrocarbons obtained by treating light vacuum gas oil and heavy vacuum gas oil with hydrogen in the presence of a catalyst in a two stage process with dewaxing being carried out between the two stages. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C ₁₅ through C ₃₀ and produces a finished oil having a viscosity of approximately 15 cSt at 40°C. It contains a relatively large proportion of saturated hydrocarbons.)	649-482-00-X	276-737-9	72623-86-0	L
Lubricating oils (petroleum), C ₂₀ –50, hydrotreated neutral oilbased; Base oil—unspecified (A complex	649-483-00-5	276-738-4	72623-87-1	L

Substances	Index number	EC number	CAS number	Notes
combination of				
hydrocarbons				
obtained by				
treating light				
vacuum gas				
oil, heavy				
vacuum gas				
oil and solvent				
deasphalted				
residual oil with				
hydrogen in the				
presence of a				
catalyst in a two				
stage process				
with dewaxing				
being carried out				
between the two				
stages. It consists				
predominantly				
of hydrocarbons				
having carbon				
numbers				
predominantly				
in the range of				
C ₂₀ through C ₅₀				
and produces a				
finished oil with				
a viscosity of				
approximately				
32 cSt at 40°C.				
It contains a				
relatively large				
proportion				
of saturated				
hydrocarbons.)				
Lubricating	649-484-00-0	278-012-2	74869-22-0	L
oils; Base oil		_,,,,,		_
—unspecified				
(A complex				
combination of				
hydrocarbons				
obtained from				
solvent extraction				
and dewaxing				
processes.				
It consists				
predominantly				
of saturated				
hydrocarbons				
having carbon				
numbers in the				

Substances	Index number	EC number	CAS number	Notes
range of C ₁₅ through C ₅₀ .)				
Distillates (petroleum), complex dewaxed heavy paraffinic; Base oil— unspecified (A complex combination of hydrocarbons obtained by dewaxing heavy paraffinic distillate. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C ₂₀ through C ₅₀ and produces a finished oil with a viscosity of equal to or greater than 100 SUS at 100°F (19 cSt at 40°C). It contains relatively few normal paraffins.)	649-485-00-6	292-613-7	90640-91-8	L
Distillates (petroleum), complex dewaxed light paraffinic; Base oil— unspecified (A complex combination of hydrocarbons obtained by dewaxing light paraffinic distillate. It consists predominantly of hydrocarbons having carbon numbers	649-486-00-1	292-614-2	90640-92-9	L

Substances	Index number	EC number	CAS number	Notes
predominantly in the range of C ₁₂ through C ₃₀ and produces a finished oil with a viscosity of less than 100 SUS at 100°F (19 cSt at 40°C). It contains relatively few normal paraffins.)				
Distillates (petroleum), solvent-dewaxed heavy paraffinic, clay-treated; Base oil—unspecified (A complex combination of hydrocarbons obtained by treating dewaxed heavy paraffinic distillate with neutral or modified clay in either a contacting or percolation process. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C ₂₀ through C ₅₀ .)	649-487-00-7	292-616-3	90640-94-1	L
Hydrocarbons, C _{20—50} , solvent-dewaxed heavy paraffinic, hydrotreated; Base oil— unspecified (A complex combination of hydrocarbons produced by treating dewaxed	649-488-00-2	292-617-9	90640-95-2	L

Substances	Index number	EC number	CAS number	Notes
heavy paraffinic distillate with hydrogen in the presence of a catalyst. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C_{20} through C_{50} .				
Distillates (petroleum), solvent-dewaxed light paraffinic clay-treated; Base oil—unspecified (A complex combination of hydrocarbons resulting from treatment of dewaxed light paraffinic distillate with natural or modified clay in either a contacting or percolation process. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C ₁₅ through C ₃₀ .	649-489-00-8	292-618-4	90640-96-3	L
Distillates (petroleum), solvent-dewaxed light paraffinic, hydro treated; Base oil—unspecified (A complex combination of	649-490-00-3	292-620-5	90640-97-4	L

Substances	Index number	EC number	CAS number	Notes
hydrocarbons produced by treating a dewaxed light paraffinic distillate with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C ₁₅ through C ₃₀ .)				
Residual oils (petroleum), hydrotreated solvent dewaxed; Base oil— unspecified	649-491-00-9	292-656-1	90669-74-2	L
Residual oils (petroleum), catalytic dewaxed; Base oil —unspecified	649-492-00-4	294-843-3	91770-57-9	L
Distillates (petroleum), dewaxed heavy paraffinic, hydrotreated; Base oil— unspecified (A complex combination of hydrocarbons obtained from an intensive treatment of dewaxed distillate by hydrogenation in the presence of a catalyst. It consists predominantly of saturated hydrocarbons having carbon numbers in the	649-493-00-X	295-300-3	91995-39-0	L

Substances	Index number	EC number	CAS number	Notes
range of C ₂₅ through C ₃₉ and produces a finished oil with a viscosity of approximately 44 cSt at 50°C.)				
Distillates (petroleum), dewaxed light paraffinic, hydrotreated; Base oil—unspecified (A complex combination of hydrocarbons obtained from an intensive treatment of dewaxed distillate by hydrogenation in the presence of a catalyst. It consists predominantly of saturated hydrocarbons having carbon numbers in the range of C ₂₁ through C ₂₉ and produces a finished oil with a viscosity of approximately 13 cSt at 50°C.)	649-494-00-5	295-301-9	91995-40-3	L
Distillates (petroleum), hydrocracked solvent-refined, dewaxed; base oil—unspecified (A complex combination of liquid hydrocarbons obtained by re- crystallization of dewaxed	649-495-00-0	295-306-6	91995-45-8	L

Substances	Index number	EC number	CAS number	Notes
hydrocracked solvent-refined petroleum distillates)				
Distillates (petroleum), solvent-refined light naphthenic, hydrotreated; Base oil— unspecified (A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst and removing the aromatic hydrocarbons by solvent extraction. It consists predominantly of naphthenic hydrocarbons having carbon numbers predominantly in the range of C ₁₅ through C ₃₀ and produces a finished oil with a viscosity of between 13–15 cSt at 40°C.)	649-496-00-6 649-497-00-1	295-316-0 295-423-2	91995-54-9 92045-42-6	L
(petroleum) C ₁₇ —35, solvent- extd., dewaxed, hydrotreated; Base oil— unspecified	047-47/-00-1	<u> </u>	72043-42-0	L
Lubricating oils (petroleum), hydrocracked	649-498-00-7	295-424-8	92045-43-7	L

Substances	Index number	EC number	CAS number	Notes
nonarom. solvent- deparaffined; Base oil— unspecified				
Residual oils (petroleum), hydrocracked acid-treated solvent-dewaxed; Base oil—unspecified (A complex combination of hydrocarbons produced by solvent removal of paraffins from the residue of the distillation of acid-treated, hydrocracked heavy paraffins and boiling approximately above 380°C (716°F).)	649-499-00-2	295-499-7	92061-86-4	L
Paraffin oils (petroleum), solvent-refined dewaxed heavy; Base oil—unspecified (A complex combination of hydrocarbons obtained from sulphur-containing paraffinic crude oil. It consists predominantly of a solvent refined deparaffinated lubricating oil with a viscosity of 65 cSt at 50°C.)	649-500-00-6	295-810-6	92129-09-4	L
Lubricating oils (petroleum), base oils, paraffinic;	649-501-00-1	297-474-6	93572-43-1	L

Substances	Index number	EC number	CAS number	Notes
Base oil— unspecified				
(A complex				
combination of				
hydrocarbons				
obtained by				
refining crude oil. It consists				
predominantly				
of aromatics,				
naphthenics				
and paraffinics				
and produces a				
finished oil with a viscosity of 120				
SUS at 100°F (23				
cSt at 40°C).)				
Hydrocarbons,	649-502-00-7	297-857-8	93763-38-3	L
hydrocracked	047-302-00-7	271-031-0	73703-36-3	L
paraffinic distn.				
residues, solvent-				
dewaxed; Base oil				
—unspecified				
Hydrocarbons,	649-503-00-2	300-257-1	93924-61-9	L
C_{20-50} , residual				
oil hydrogenation vacuum distillate;				
Base oil—				
unspecified				
Distillates	649-504-00-8	305-588-5	94733-08-1	L
(petroleum),				
solvent-refined				
hydrotreated				
heavy; hydrogenated;				
Base oil-				
unspecified				
Distillates	649-505-00-3	305-589-0	94733-09-2	L
(petroleum),				
solvent-refined				
hydrocracked				
light; Base oil —unspecified				
(A complex				
combination of				
hydrocarbons				
obtained				
by solvent dearomatization				
of the residue of				
		288		

Substances	Index number	EC number	CAS number	Notes
hydrocracked petroleum. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C ₁₈ through C ₂₇ and boiling in the range of from approximately 370°C to 450°C (698°F to 842°F).)				
Lubricating oils (petroleum), C ₁₈ —40, solvent-dewaxed hydrocracked distillate-based; Base oil— unspecified (A complex combination of hydrocarbons obtained by solvent deparaffination of the distillation residue from hydrocracked petroleum. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C ₁₈ through C ₄₀ and boiling in the range of approximately 370°C to 550°C (698°F to 1022°F).)	649-506-00-9	305-594-8	94733-15-0	L
Lubricating oils (petroleum), C ₁₈	649-507-00-4	305-595-3	94733-16-1	L

Substances	Index number	EC number	CAS number	Notes
Substances —40, solvent- dewaxed hydrogenated raffinate-based; Base oil— unspecified (A complex combination of hydrocarbons obtained by solvent deparaffination of the hydrogenated raffinate obtained by solvent extraction of a hydro treated petroleum distillate. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C ₁₈ through C ₄₀ and boiling in the range of approximately 370°C to 550°C (698°F to	Index number	EC number	CAS number	Notes
1022°F).) Hydrocarbons, C _{13,30} , arom rich, solvent- extd. napthenic distillate; Base oil —unspecified	649-508-00-X	305-971-7	95371-04-3	L
Hydrocarbons, C _{16—32} , arom rich, solvent- extd. naphthenic distillate; Base oil —unspecified	649-509-00-5	305-972-2	95371-05-4	L
Hydrocarbons, C _{37—68} , dewaxed deasphalted hydrotreated vacuum distn.	649-510-00-0	305-974-3	95371-07-6	L

Substances	Index number	EC number	CAS number	Notes
residues; Base oil —unspecified				
Hydrocarbons, C _{37—65} , hydrotreated deasphalted vacuum distn. residues; Base oil —unspecified	649-511-00-6	305-975-9	95371-08-7	L
Distillates (petroleum), hydrocracked solvent-refined light; Base oil—unspecified (A complex combination of hydrocarbons obtained by the solvent treatment of a distillate from hydrocracked petroleum distillates. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C ₁₈ through C ₂₇ and boiling in the range of approximately 370°C to 450°C (698°F to 842°F).)	649-512-00-1	307-010-7	97488-73-8	L
Distillates (petroleum), solvent-refined hydrogenated heavy; Base oil —unspecified (A complex combination of hydrocarbons obtained by the treatment of a	649-513-00-7	307-011-2	97488-74-9	L

Substances	Index number	EC number	CAS number	Notes
hydrogenated petroleum distillate with a solvent. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C ₁₉ through C ₄₀ and boiling in the range of approximately 390°C to 550°C (734°F to 1022°F).)				
Lubricating oils (petroleum) C ₁₈ — ₂₇ , hydrocracked solvent-dewaxed; Base oil— unspecified	649-514-00-2	307-034-8	97488-95-4	L
Hydrocarbons, C _{17—30} , hydrotreated solvent-deasphalted atm.distn. Residue, distn. lights; Base oil—unspecified (A complex combination of hydrocarbons obtained as first runnings from the vacuum distillation of effluents from the treatment of a solvent de asphalted short residue with hydrogen in the presence of a catalyst. It consists predominantly	649-515-00-8	307-661-7	97675-87-1	L

Substances	Index number	EC number	CAS number	Notes
of hydrocarbons having carbon numbers predominantly in the range of C ₁₇ through C ₃₀ and boiling in the range of approximatly 300°C to 400°C (572°F to 752°F). It produces a finished oil having a viscosity of 4 cSt at approximately 100°C (212 °F).)				
Hydrocarbons, C _{17—40} , hydrotreated solvent-deasphalted distn. Residue, vacuum distn. Lights; Base oil—unspecified (A complex combination of hydrocarbons obtained as first runnings from the vacuum distillation of effluents from the catalytic hydrotreatment of a solvent de asphalted short residue having a viscosity of 8 cSt at approximatly 100°C (212°F). It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C ₁₇ through C ₄₀ and boiling in	649-516-00-3	307-755-8	97722-06-0	L

Substances	Index number	EC number	CAS number	Notes
the range of approximately 300°C to 500°C (592°F to 932°F).)				
Hydrocarbons, C _{13—27} , solvent-extd. Light naphthenic; Base oil—unspecified (A complex combination of hydrocarbons obtained by extraction of the aromatics from a light naphthenic distillate having a viscosity of 9.5 cSt at 40°C (104°F). It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C ₁₃ through C ₂₇ and boiling in the range of approximately 240°C to 400°C (464°F to 752°F).)	649-517-00-9	307-758-4	97722-09-3	L
Hydrocarbons, C _{14—29} . solvent-extd. Light naphthenic; Base oil—unspecified (A complex combination of hydrocarbons obtained by extraction of the aromatics from a light naphthenic distillate having a viscosity of 16 cSt at	649-518-00-4	307-760-5	97722-10-6	L

Substances	Index number	EC number	CAS number	Notes
It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C ₁₄ through C ₂₉ and boiling in the range of approximately 250°C to 425°C (482°F to 797°F).)				
Hydrocarbons, C _{27—42} , dearomatized; Base oil— unspecified	649-519-00-X	308-131-8	97862-81-2	L
Hydrocarbons, C _{17—30} , hydrotreated distillates, distn. lights; Base oil— unspecified	649-520-00-5	308-132-3	97862-82-3	L
Hydrocarbons, C _{27—45} , naphthenic vacuum distn.: Base oil— unspecified	649-521-00-0	308-133-9	97862-83-4	L
Hydrocarbons, C _{27—45} , dearomatized; Base oil— unspecified	649-522-00-6	308-287-7	97926-68-6	L
Hydrocarbons C ₂₀ _{—58} , hydrotreated; Base oil— unspecified	649-523-00-1	308-289-8	97926-70-0	L
Hydrocarbons C ₂₇ —42, naphthenic; Base oil— unspecified	649-524-00-7	308-290-3	97926-71-1	L
Residual oils (petroleum),	649-525-00-2	309-710-8	100684-37-5	L

Substances	Index number	EC number	CAS number	Notes
carbon-treated solvent-dewaxed; Base oil— unspecified (A complex combination of hydrocarbons obtained by the treatment of solvent-dewaxed petroleum residual oils with activated charcoal for the removal of trace polar constituents and impurities.)				
Residual oils (petroleum), clay- treated solvent- dewaxed; Base oil—unspecified (A complex combination of hydrocarbons obtained by treatment of solvent-dewaxed petroleum residual oils with bleaching earth for the removal of trace polar constituents and impurities.)	649-526-00-8	309-711-3	100684-38-6	L
Lubricating oils (petroleum), C ₂₅ , solvent-extd., deasphalted, dewaxed, hydrogenated; Base oil—unspecified (A complex combination of hydrocarbons obtained by solvent extraction and hydrogenation of vacuum	649-527-00-3	309-874-0	101316-69-2	L

Substances	Index number	EC number	CAS number	Notes
distillation				
residues.				
It consists				
predominantly of hydrocarbons				
having carbon				
numbers				
predominantly				
in the range of				
greater than C ₂₅				
and produces a				
finished oil with				
a viscosity in the order of 32 cSt to				
37 cSt at 100°C				
(212°F).)				
Lubricating oils	649-528-00-9	309-875-6	101316-70-5	L
(petroleum), C ₁₇	049-326-00-9	309-073-0	101310-70-3	L
_32, solvent-				
extd., dewaxed,				
hydrogenated;				
Base oil—				
unspecified (A complex				
combination of				
hydrocarbons				
obtained				
by solvent				
extraction and				
hydrogenation of atmospheric				
distillation				
residues.				
It consists				
predominantly				
of hydrocarbons				
having carbon numbers				
predominantly				
in the range of				
C ₁₇ through C ₃₂				
and produces a				
finished oil with				
a viscosity in the order of 17 cSt				
to 23 cSt at 40°C				
(104°F).)				
Lubricating oils	649-529-00-4	309-876-1	101316-71-6	L
(petroleum), C_{20}	U+7-J47-UU-4	307-070-1	101310-/1-0	L
_35, solvent-				
33, /				

Substances	Index number	EC number	CAS number	Notes
extd., dewaxed,				
hydrogenated;				
Base oil—				
unspecified				
(A complex				
combination of				
hydrocarbons				
obtained				
by solvent				
extraction and				
hydrogenation				
of atmospheric distillation				
residues.				
It consists				
predominantly				
of hydrocarbons				
having carbon				
numbers				
predominantly				
in the range of				
C_{20} through C_{35}				
and produces				
a finished oil				
having a viscosity				
in the order of 37				
cSt to 44 cSt at				
40°C (104°F).)				
Lubricating oils	649-530-00-X	309-877-7	101316-72-7	L
(petroleum), C ₂₄				
_ ₅₀ , solvent-				
extd., dewaxed,				
hydrogenated;				
Base oil—				
unspecified				
(A complex				
combination of				
hydrocarbons				
obtained				
by solvent				
extraction and				
hydrogenation				
of atmospheric				
distillation				
residues.				
It consists				
predominantly				
of hydrocarbons				
having carbon numbers				
predominantly				
predominantiy				

Substances	Index number	EC number	CAS number	Notes
in the range of C ₂₄ through C ₅₀ and produces a finished oil with a viscosity in the order of 16 cSt to 75 cSt at 40°C (104°F).)				
Extracts (petroleum), heavy naphthenic distillate solvent, arom. conc.; Distillate aromatic extract (treated) (An aromatic concentrate produced by adding water to heavy naphthenic distillate solvent extract and extraction solvent.)	649-531-00-5	272-175-3	68783-00-6	L
Extracts (petroleum), solvent-refined heavy paraffinic distillate solvent; Distillate aromatic extract (treated) (A complex combination of hydrocarbons obtained as the extract from the re-extraction of solvent-refined heavy paraffinic distillate. It consists of saturated and aromatic hydrocarbons having carbon numbers predominantly in	649-532-00-0	272-180-0	68783-04-0	L

Substances	Index number	EC number	CAS number	Notes
the range of C_{20} through C_{50} .)				
Extracts (petroleum), heavy paraffinic distillates, solvent-deasphalted; Distillate aromatic extract (treated) (A complex combination of hydrocarbons obtained as the extract from a solvent extraction of heavy paraffinic distillate.)	649-533-00-6	272-342-0	68814-89-1	L
Extracts (petroleum), heavy naphthenic distillate solvent, hydrotreated; Distillate aromatic extract (treated) (A complex combination of hydrocarbons obtained by treating a heavy naphthenic distillate solvent extract with hydrogen in the presence of a catalyst. It consists predominantly of aromatic hydrocarbons having carbon numbers predominantly in the range of C ₂₀ through C ₅₀ and produces a finished oil of	649-534-00-1	292-631-5	90641-07-9	L

Substances	Index number	EC number	CAS number	Notes
at least 19 cSt at 40°C (100 SUS at 100°F).)				
Extracts (petroleum), heavy paraffinic distillate solvent, hydrotreated; Distillate aromatic extract (treated) (A complex combination of hydrocarbons produced by treating a heavy paraffinic distillate solvent extract with hydrogen in the presence of a catalyst. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C ₂₁ through C ₃₃ and boiling in the range of approximately 350°C to 480°C (662°F to 896°F).)	649-535-00-7	292-633-6	90641-09-1	L
Extracts (petroleum), light paraffinic distillate solvent, hydrotreated; Distillate aromatic extract (treated) (A complex combination of hydrocarbons produced by treating a light paraffinic distillate solvent	649-536-00-2	292-633-6	90641-09-1	L

Substances	Index number	EC number	CAS number	Notes
extract with hydrogen in the presence of a catalyst. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C ₁₇ through C ₂₆ and boiling in the range of approximately 280°C to 400°C (536°F to 752°F).)				
Extracts (petroleum), hydrotreated paraffinic light distillate solvent; Distillate aromatic extract (treated) (A complex combination of hydrocarbons obtained as the extract from solvent extraction of intermediate paraffinic top solvent distillate that is treated with hydrogen in the presence of a catalyst. It consists predominantly of aromatic hydrocarbons having carbon numbers predominantly in the range of C ₁₆ through C ₃₆ .)	649-537-00-8	295-335-4	91995-73-2	L
Extracts (petroleum),	649-538-00-3	295-338-0	91995-75-4	L

Substances	Index number	EC number	CAS number	Notes
light naphthenic				
distillate				
solvent, hydro-				
desulphurized;				
Distillate				
aromatic				
extract (treated)				
(A complex				
combination of				
hydrocarbons				
obtained by				
treating the				
extract, obtained				
from a solvent				
extraction				
process, with				
hydrogen in				
the presence				
of a catalyst				
under conditions				
primarily to				
remove sulphur				
compounds.				
It consists				
predominantly				
of aromatic				
hydrocarbons				
having carbon				
numbers				
predominantly in				
the range of C_{15}				
through C_{30} . This				
stream is likely				
to contain 5 wt.				
% or more of 4				
to 6-membered				
condensed				
ring aromatic hydrocarbons.)				
nyurocarbons.)				
Extracts	649-539-00-9	295-339-6	91995-76-5	L
(petroleum),				
light paraffinic				
distillate solvent,				
acid-treated;				
Distillate				
aromatic				
extract (treated)				
(A complex				
combination of				
hydrocarbons				
obtained as a				

Substances	Index number	EC number	CAS number	Notes
fraction of the	Index number	LC number	C115 Humber	110103
distillation of an				
extract from the				
solvent extraction				
of light paraffinic				
top petroleum				
distillates that				
is subjected				
to a sulphuric				
acid refining.				
It consists				
predominantly				
of aromatic				
hydrocarbons				
having carbon				
numbers				
predominantly in				
the range of C_{16}				
through C_{32} .)				
Extracts	649-540-00-4	295-340-1	91995-77-6	L
(petroleum),				
light paraffinic				
distillate				
solvent, hydro-				
desulphurized;				
Distillate				
aromatic				
extract (treated)				
(A complex				
combination of				
hydrocarbons				
obtained by				
solvent extraction of a light paraffin				
distillate and				
treated with				
hydrogen to				
convert the				
organic sulphur				
to hydrogen				
sulphide which				
is eliminated.				
It consists				
predominantly				
of hydrocarbons				
having carbon				
numbers				
predominantly				
in the range of				
C_{15} through C_{40}				
and produces				
		201		

Substances	Index number	EC number	CAS number	Notes
a finished oil having a viscosity of greater than 10 cSt at 40 C.)	muca number	EC number	CAS number	Hous
Extracts (petroleum), light vacuum gas oil solvent, hydrotreated; Distillate aromatic extract (treated) (A complex combination of hydrocarbons obtained by solvent extraction from light vacuum petroleum gas oils and treated with hydrogen in the presence of a catalyst. It consists predominantly of aromatic hydrocarbons having carbon numbers predominantly in the range of C ₁₃ through C ₃₀ .)	649-541-00-X	295-342-2	91995-79-8	L
Extracts (petroleum), heavy paraffinic distillate solvent, clay-treated; Distillate aromatic extract (treated) (A complex combination of hydrocarbons resulting from treatment of a petroleum fraction with natural or modified clay in either a contact	649-542-00-5	305	92704-08-0	L

Substances	Index number	EC number	CAS number	Notes
or percolation process to remove the trace amounts of polar compounds and impurities present. It consists predominantly of aromatic hydrocarbons having carbon numbers predominantly in the range of C ₂₀ through C ₅₀ . this stream is likely to contain 5 wt. % or more 4-6 membered ring aromatic hydrocarbons.)				
Extracts (petroleum), heavy naphthenic distillate solvent, hydro- desulphurized; Distillate aromatic extract (treated) (A complex combination of hydrocarbons obtained from a petroleum stock by treating with hydrogen to convert organic sulphur to hydrogen sulphide which is removed. It consists predominantly of aromatic hydrocarbons having carbon numbers predominantly in the range of	649-543-00-0	297-827-4	93763-10-1	L

Substances	Index number	EC number	CAS number	Notes
C ₁₅ through C ₅₀ and produces a finished oil with a viscosity of greater than (19 cSt at 40°C).)				
Extracts (petroleum), solvent-dewaxed heavy paraffinic distillate solvent, hydrodesulphurized Distillate aromatic extract (treated) (A complex combination of hydrocarbons obtained from a solvent dewaxed petroleum stock by treating with hydrogen to convert organic sulphur to hydrogen sulphide which is removed. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C ₁₅ through C ₅₀ and produces a finished oil with a viscosity of greater than 19 St at 40°C.)	649-544-00-6	297-829-5	93763-11-2	L
Extracts (petroleum), light paraffinic distillate solvent, carbon-treated; Distillate aromatic extract (treated) (A complex combination of	649-545-00-1	309-672-2	100684-02-4	L
		307		

Substances	Index number	EC number	CAS number	Notes
hydrocarbons obtained as a fraction from distillation of an extract recovered by solvent extraction of light paraffinic top petroleum distillate treated with activated charcoal to remove traces of polar constituents and impurities. It consists predominantly of aromatic hydrocarbons having carbon numbers predominantly in the range of C ₁₆ through C ₃₂ .)				
Extracts (petroleum), light paraffinic distillate solvent, clay-treated; Distillate aromatic extract (treated) (A complex combination of hydrocarbons obtained as a fraction from distillation of an extract recovered by solvent extraction of light paraffinic top petroleum distillates treated with bleaching earth to remove traces of polar constituents and impurities. It consists predominantly	649-546-00-7	309-673-8	100684-03-5	L

Substances	Index number	EC number	CAS number	Notes
of aromatic hydrocarbons having carbon numbers predominantly in the range of C ₁₆ through C ₃₂ .)				
Extracts (petroleum), light vacuum, gas oil solvent, carbontreated; Distillate aromatic extract (treated) (A complex combination of hydrocarbons obtained by solvent extraction of light vacuum petroleum gas oil treated with activated charcoal for the removal of trace polar constituents and impurities. It consists predominantly of aromatic hydrocarbons having carbon numbers predominantly in the range of C ₁₃ through C ₃₀ .)	649-547-00-2	309-674-3	100684-04-6	L
Extracts (petroleum), light vacuum, gas oil solvent, clay- treated; Distillate aromatic extract (treated) (A complex combination of hydrocarbons obtained by solvent extraction of light vacuum petroleum gas	649-548-00-8	309-675-9	100684-05-7	L

Substances	Index number	EC number	CAS number	Notes
oils treated with bleaching earth for removal of trace polar constituents and impurities. It consists predominantly of aromatic hydrocarbons having carbon numbers predominantly in the range of C ₁₃ through C ₃₀ .)				
Foot oil (petroleum); Foots oil (A complex combination of hydrocarbons obtained as the oil fraction from a solvent deoiling or a wax sweating process. It consists predominantly of branched chain hydrocarbons having carbon numbers predominantly in the range of C ₂₀ through C ₅₀ .)	649-549-00-3	265-171-8	64742-67-2	L
Foots oil (petroleum), hydrotreated; Foot's oil	649-550-00-9	295-394-6	92045-12-0	L

Mutagenic substances of Category 2

Substances	Index Number	EC number	CAS number	Notes
hexamethylphosp triamide; hexamethylphosp		211-653-8	680-31-9	
diethyl sulphate	016-027-00-6	200-589-6	64-67-5	

Substances	Index Number	EC number	CAS number	Notes
benzo[a]pyrene; benzo[d,e,f]chryse	601-032-00-3 ene	200-028-5	50-32-8	
1,2-dibromo-3- chloropropane	602-021-00-6	202-479-3	96-12-8	
ethylene oxide; oxirane	603-023-00-X	200-849-9	75-21-8	
methyl acrylamidomethon (containing >= 0,1% acrylamid)	607-190-00-X xyacetate	401-890-7	77402-03-0	
methyl acrylamidoglycola (containing >= 0,1% acrylamide)		403-230-3	77402-05-2	
ethyleneimine; aziridine	613-001-00-1	205-793-9	151-56-4	
acrylamide	616-003-00-0	201-173-7	79-06-1	

Toxic for reproduction substances of Category 1

Substances	Index Number	EC number	CAS number	Notes
carbon monoxide	006-001-00-2	211-128-3	630-08-0	
lead hexafluorosilicate	009-014-00-1	247-278-1	25808-74-6	
lead compounds with the exception of those specified elsewhere in this Annex	082-001-00-6			
lead alkyls	082-002-00-1			
lead azide	082-003-00-7	236-542-1	13424-46-9	
lead chromate	082-004-00-2	231-846-0	7758-97-6	
lead di(acetate)	082-005-00-8	206-104-4	301-04-2	
C. L. A.	T. I. Nl.	EC l	CAG	NT. 4
Substances	Index Number	EC number	CAS number	Notes
trilead bis (orthophosphate)	082-006-00-3	231-205-5	7446-27-7	
lead acetate	082-007-00-9	215-630-3	1335-32-6	
lead (II) methanesulphonate	082-008-00-4	401-750-5	17570-76-2	

Substances	Index Number	EC number	CAS number	Notes
C.I. Pigment Yellow 34; [This substance is identified in the Colour Index by Colour Index Constitution Number, C.I. 77603.]	082-009-00-X	215-693-7	1344-37-2	
C.I. Pigment Red 104; [This substance is identified in the Colour Index by Colour Index Constitution Number, C.I. 77605.]	082-010-00-5	235-759-9	12656-85-8	
lead hydrogen arsenate	082-011-00-0	232-064-2	7784-40-9	
warfarin; 4- hydroxy-3- (3-oxo-1- phenylbutyl) coumarin	607-056-00-0	201-377-6	81-81-2	
lead 2,4,6- trinitroresorcinoxi lead styphnate	609-019-00-4 de,	239-290-0	15245-44-0	

Toxic for reproduction substances of Category 2

Substances	Index Number	EC number	CAS number	Notes
nickel tetracarbonyl	028-001-00-1	236-669-2	13463-39-3	
benzo[a]pyrene; benzo [d,e,f] chrysene	601-032-00-3	200-028-5	50-32-8	
2- methoxyethanol; ethylene glycol monomethyl ether	603-011-00-4	203-713-7	109-86-4	
2-ethoxyethanol; ethylene glycol monoethyl ether	603-012-00-X	203-804-1	110-80-5	
2-methoxyethyl acetate;	607-036-00-1	203-772-9	110-49-6	

Substances	Index Number	EC number	CAS number	Notes
methylglycol acetate				
2-ethoxyethyl acetate; ethylglycol acetate	607-037-00-7	203-839-2	111-15-9	
2-ethylhexyl 3,5-bis (1, 1- dimethylethyl) 4- hydtoxyphenyl methyl thio acetate	607-203-00-9	279-452-8	80387-97-9	
binapacryl (ISO); 2-sec-butyl-4,6- dinittrophenyl-3- methylcrotonate	609-024-00-1	207-612-9	485-31-4	
Substances	Index Number	EC number	CAS number	Notes
dinoseb; 6- sec-butyl-2, 4- dinitrophenol	609-025-00-7	201-861-7	88-85-7	
salts and esters of dinoseb, with the exception of those specified elsewhere in this Annex	609-026-00-2			
dinoterb; 2- tert-butyl-4, 6- dinitrophenol	609-030-00-4	215-813-8	1420-07-1	
salts and esters of dinoterb	609-031-00-X			
nitrofen (ISO); 2, 4 dichlorophenyl 4-nitrophenyl ether	609-040-00-9	217-406-0	1836-75-5	
methyl-ONN- azoxymethyl acetate; methyl azoxy methyl acetate	611-004-00-2	209-765-7	592-62-1	
ethylene thiourea; imidazolidine-2- thione; 2- imidazoline-2- thiol	613-039-00-9	202-506-9	96-45-7	

Substances	Index Number	EC number	CAS number	Notes	
N, N-	616-001-00-X	200-679-5	68-12-2		
dimethylformamide;					
dimethyl					
formamide					

Note

The name of the substances is the same as that used for the substance in annex 1 to Directive 67/548/EEC (OJ 196, 16.8.1967, p. 1. Whenever possible dangerous substances are designated by their Einecs (European Inventory of Existing Commercial Chemical Substances) of Elincs (European List of Notified Chemical Substances) names. Other entries not listed in Einecs or Elincs are designated using an internationally recognized chemical name (eg ISO, IUPAC). An additional common name is included in some cases.

The index number is the identification code given to the substance in Annex 1 of Directive 67/548/EEC. Substances are listed in the Schedule according to this index number.

The EC number for each substance listed in the European Inventory of Existing Commercial Chemical Substances (Einecs) there is an identification code which starts at 200-001-8. For each new substance notified under the Directive 67/548/EEC an idenfication code has been defined and published in the European List of Notified Chemical Substances (Elincs). The code starts at 400-010-9.

The CAS number is the number assigned to the substance by the "Chemicals Abstract Service".

EXPLANATORY NOTE

(This note is not part of the Regulations)

These Regulations amend the Chemicals (Hazard Information and Packaging for Supply) Regulations 1994 (S.I.1994/3247) ("the principal Regulations") as amended by the Chemicals (Hazard Information and Packaging for Supply) (Amendment) Regulations 1996 (S.I. 1996/1092). They partially implement Article 1(2) of Commission Directive 97/56/EC (O.J. No. L333, 4.12.1997, p.1) which amended for the sixteenth time Council Directive 76/769/EEC. These Regulations combined with the Dangerous Substances and Preparations (Safety) (Consolidation) (Amendment) (No. 2) Regulations 1999 (S.I. 1999/3193) fully implement Article 1(2) of Directive 97/56/EC.

These Regulations amend Part III of Schedule 6 to the principal Regulations by adding to and consolidating the list of carcinogenic and mutagenic substances, and certain substances toxic for reproduction, contained therein. The principal Regulations require that a substance specified in that list or a preparation containing such a substance must in certain circumstances be labelled with the phrase "Restricted to professional users".

A Regulatory Impact Assessment is available, copies of which have been placed in the libraries of both Houses of Parliament. Copies are also available from the Consumer Affairs Directorate of the Department of Trade and Industry, Room 433, 1 Victoria Street, London SW1H 0ET.