SCHEDULE 1

Regulation 3(1)

- 1.—(1) For the purposes of these Regulations, "paints and varnishes" means products listed in the sub-categories below, excluding aerosols. They are coatings applied to buildings, their trim and fittings, and associated structures for decorative, functional and protective purpose.
 - (2) The sub-categories referred to in sub-paragraph (1) are—
 - (a) "matt coatings for interior walls and ceilings" means coatings designed for application to indoor walls and ceilings with a degree of gloss $\leq 25@60^\circ$;
 - (b) "glossy coatings for interior walls and ceilings" means coatings designed for application to indoor walls and ceilings with a degree of gloss >25@60°;
 - (c) "coatings for exterior walls of mineral substrate" means coatings designed for application to outdoor walls of masonry, brick or stucco;
 - (d) "interior/exterior trim and cladding paints for wood, metal or plastic" means coatings designed for application to trim and cladding which produce an opaque film. These coatings are designed for either a wood, metal or a plastic substrate. This subcategory includes undercoats and intermediate coatings;
 - (e) "interior/exterior trim varnishes and woodstains" means coatings designed for application to trim which produce a transparent or semi-transparent film for decoration and protection of wood, metal and plastics. This subcategory includes opaque woodstains. Opaque woodstains means coatings producing an opaque film for the decoration and protection of wood, against weathering, as defined in EN 927-1, within the semi-stable category;
 - (f) "minimal build woodstains" means woodstains which, in accordance with EN 927-1:1996, have a mean thickness of less than 5μm when tested according to ISO 2808: 1997, method 5A;
 - (g) "primers" means coatings with sealing and/or blocking properties designed for use on wood or walls and ceilings;
 - (h) "binding primers" means coatings designed to stabilise loose substrate particles or impart hydrophobic properties and/or to protect wood against blue stain;
 - (i) "one-pack performance coatings" means performance coatings based on film-forming material. They are designed for applications requiring a special performance, such as primer and topcoats for plastics, primer coat for ferrous substrates, primer coat for reactive metals such as zinc and aluminium, anticorrosion finishes, floor coatings, including for wood and cement floors, graffiti resistance, flame retardant, and hygiene standards in the food or drink industry or health services;
 - (j) "two-pack performance coatings" means coatings with the same use as one-performance coatings, but with a second component (e.g. tertiary amines) added prior to application;
 - (k) "multicoloured coatings" means coatings designed to give a two-tone or multiple-colour effect, directly from the primary application;
 - (l) "decorative effect coatings" means coatings designed to give special aesthetic effects over specially prepared pre-painted substrates or base coats and subsequently treated with various tools during the drying period.
- **2.**—(1) For the purposes of these Regulations, "vehicle refinishing products" means products listed in the sub-categories below. They are used for the coating of road vehicles as defined in Directive 70/156/EEC(1), or part of them, carried out as part of vehicle repair, conservation or decoration outside of manufacturing installations.

1

⁽¹⁾ O.J. L42, 23.2.1970, p.1, as last amended by Directive 2004/3/EC, O.J. L49, 19.2.2004, p.36.

- (2) The sub-categories referred to in sub-paragraph (1) are—
 - (a) "preparatory and cleaning" means products designed to remove old coatings and rust, either mechanically or chemically, or to provide a key for new coatings:
 - (i) preparatory products include gunwash (a product designed for cleaning spray-guns and other equipment), paint strippers, degreasers (including anti-static types for plastic) and silicone removers;
 - (ii) "precleaner" means a cleaning product designed for the removal of surface contamination during preparation for and prior to the application of coating materials;
 - (b) "Bodyfiller/stopper" means heavy-bodied compounds designed to be applied to fill deep surface imperfections prior to the application of the surfacer/filler;
 - (c) "primer" means any coating that is designed for application to bare metal or existing finishes to provide corrosion protection prior to application of a primer surfacer:
 - (i) "surfacer/filler" means a coating designed for application immediately prior to the application of topcoat for the purpose of corrosion resistance, to ensure adhesion of the topcoat, and to promote the formation of a uniform surface finish by filling in minor surface imperfections;
 - (ii) "general metal primer" means a coating designed for application as primers, such as adhesion promoters, sealers, surfacers, undercoats, plastic primers, wet-on-wet, non-sand fillers and spray fillers;
 - (iii) "wash primer" means coatings containing at least 0,5 % by weight of phosphoric acid designed to be applied directly to bare metal surfaces to provide corrosion resistance and adhesion; coatings used as weldable primers; and mordant solutions for galvanised and zinc surfaces;
 - (d) "topcoat" means any pigmented coating that is designed to be applied either as a single-layer or as a multiple-layer base to provide gloss and durability. It includes all products involved such as base coatings and clear coatings:
 - (i) "base coatings" means pigmented coatings designed to provide colour and any desired optical effects, but not the gloss or surface resistance of the coating system;
 - (ii) "clear coating" means a transparent coating designed to provide the final gloss and resistance properties of the coating system;
 - (e) "special finishes" means coatings designed for application as topcoats requiring special properties, such as metallic or pearl effect, in a single layer, high-performance solid-colour and clear coats, (e.g. anti-scratch and fluorinated clear- coat), reflective base coat, texture finishes (e.g. hammer), anti-slip, under-body sealers, anti-chip coatings, interior finishes; and aerosols.

(3) In this Schedule—

"coating" means any preparation, including all the organic solvents or preparations containing organic solvents necessary for its proper application, which is used to provide a film with decorative, protective or other functional effect on a surface;

"film" means a continuous layer resulting from the application of one or more coats to a substrate;

"organic solvent" means any VOC which is used—

- (i) alone or in combination with other agents to dissolve or dilute raw materials, products, or waste materials;
- (ii) as a cleaning agent to dissolve contaminants;

Status: This is the original version (as it was originally made).

- (iii) as a dispersion medium;
- (iv) as a viscosity adjuster;
- (v) as a surface tension adjuster;
- (vi) as a plasticiser; or
- (vii) as a preservative;

[&]quot;preparation" means mixtures or solutions composed of two or more substances; and

[&]quot;substances" means any chemical element and its compounds, as they occur in the natural state or as produced by industry, whether in solid or liquid or gaseous form.