

SCHEDULE 14

Signs for traffic control by light signals, signs for crossings, and signs for lane control

PART 6

The Schedule 14 General Directions

- 45.**—(1) This general direction applies where the lamp is specially mounted on a post.
- (2) Paragraph (3)—
- (a) applies where a yellow globe is also attached to the post; and
 - (b) is subject to paragraph (7).
- (3) The part of the post between ground level and the point where the globe is attached must be coloured black and white in alternate horizontal bands and—
- (a) the lowest band must be coloured black and be not less than 275 mm nor more than 1 metre deep; and
 - (b) each other band shall be not less than 275 mm nor more than 335 mm deep.
- (4) The remaining part of the post must be coloured in accordance with paragraph (6).
- (5) Paragraph (6) applies—
- (a) if no globe attached to the post; or
 - (b) for the purposes of paragraph (4),
- and is subject to paragraph (7).
- (6) The post must be coloured grey or black but with two white bands (each band being not less than 275 mm nor more than 335 mm deep) arranged so that—
- (a) not less than 275 mm nor more than 335 mm extend between the nearest edges of the two bands; and
 - (b) the upper edge of the uppermost band is not less than 275 mm nor more than 335 mm below the lowest part of the lamp,
- and the white bands may be internally illuminated.
- (7) Where the post is made of aluminium, concrete or galvanised metal it may remain in its natural colour.