

## SCHEDULE 7

Road markings and miscellaneous upright signs that indicate stopping, waiting, loading and parking controls

### PART 3

#### Provisions applying to road markings in Part 4

1. A restriction or prohibition of a description in column 2 of an item in the Part 4 sign table must be conveyed by road markings of the size, colour and type shown in—

- (a) the diagram in column 3; or
- (b) that diagram as varied in accordance with the paragraph in Part 5 whose number appears in column 4 of the item.

2.—(1) Where the road marking at item 9 is placed in a lay-by, studs may also be placed.

(2) The studs must incorporate—

- (a) green reflectors;
- (b) green retroreflecting material; or
- (c) a light source that emits, during the hours of darkness, a steady green light,

or any combination.

(3) The studs must be placed in the gaps between the broken line that indicates the edge of the lay-by to drivers of approaching vehicles.

(4) The external part of the stud that is visible when the stud is in place must be—

- (a) green
- (b) white;
- (c) of a natural metallic finish;
- (d) of another neutral colour; or
- (e) clear,

or any combination (but see sub-paragraph (5) for an exception).

(5) The external part of a stud that is visible when the stud is in place temporarily during road works must be fluorescent green-yellow except to the extent—

- (a) it consists of green reflectors or retroreflecting material; or
- (b) it is necessary for it to be a different colour or clear in order for the stud to emit green light.

3. Section 36 of the 1988 Act applies to the markings at items—

- (a) 9; and
- (b) 10 where the marking is placed in the circumstances mentioned in paragraph 3 of Part 6.